

Douglas County Surveyor's Record of
Government Corners Renewed

T 22 T. S. R 10 R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

74

CONT.

Gary Langlitz
M. Ladig
P. Earle, K. Cheney
June 21, 1976
C.S. 59/15

the only remaining orig. BT, WE SET: a 1" x 30" I. Pipe 26" in the ground, with brass cap attached stamped: Douglas Co. Surveyor

	T 22 S	
S13	$\frac{S7}{S18}$	CC
R11W		R10W

From Which:

An orig. BT, a 16" now 54" D. Fir bears N.45°E., 39.6 ft.
New BT - A 12" D. Fir bears S.20°E., 21.5 ft. scribed "CC T22S R10W S18 CS BT" in a double blaze.

Note: The NE corner of Sec. 13, T22-11 bears approx North 50 ft.

6/2/76

75

Section corner for Secs. 1 and 12 only, T22-11.

Found - A stone, 16"x12"x7" with 1 notch on northerly edge & 5 notches on southerly edge, "X" chiseled on top. Stone located at the base of a small slide area.

A Fir, 12" now 29", bears N.18"W., 45.6 ft. (Rec. N.13°W., 43.6 ft.) I partially open blaze & find scribing "S1".

A Fir, 36" now a 55" windfall, badly rotted, bears S.8°W., 72.0 ft. approx. (Rec. S.6°50'W., 70.0 ft.) Tree scribed "R11W".

Set - Brass cap at corner stamped "Douglas County Surveyors Office"

	T 22 S	
R 11	$\frac{S 1}{S 12}$	S 6 R 10
W 1976		W

Set original corner stone on southerly side of cap & place witness sign & fence post on east side of cap.

New BT's - A D. Fir, 10" bears S.58 1/2°W., 10.7 ft. double blazed & scribed "T22S R11W S12 CS BT".

Original 12" Fir, bears N.13°W., 43.6 ft.

6/24/76

76

M.C. Lots 3 and 4. (Sec. 8)

Found - 3/4" Iron pipe. (See M 19 - 14)

From which:

36" now 42" Spruce bears N.32°W., 31.5 ft. with healed blaze. Tree is alive.

20" now 32" Spruce bears S.68°W., 9.8 ft. Tree is alive with healing blaze.

Note: Corner lies 64 ft. east of right bank of Umpqua River.

WE DO NOT RENEW

7/21/76

77

M.C. for Sec. 6; and Sec. 1, T22-11.

Found - A 2" x 30" I.P. with pump bell .3 ft. below ground in marshy area.

A 58" Spruce, bears S.8°E., 111.5 ft. with re=scribing by Baughman "S6 MC BT" (See C.S. file M56-56), center rotted, top dead, with creek, course N-NW, under tree.

No other orig. trees found.

Set - A 1" x 30" I.P. with brass cap 27" in the ground mkd:

	T 22 S	
Douglas Co. Surveyor	M.C.	
1976	$\frac{S 1}{S 6}$	R 10
W		W

Cap set in position of Pd. pipe as per bearing and dist. from Pd. BT. Cap set in mound of stone 1 1/2° & 1 ft. below surface of ground. Cap stands .3 ft. above ground.

Place I.P. on N. edge of cap.

Cor. falls in old N-S fence line.

Set - Sign and post 2 ft. south of cor., 32" above ground.

No other BT's available for scribing in west quads.

10/25/76

78

Closing corner for Secs. 6 and 7 only. West side.

Found - A 5/8" I.R. set by Baughman in 1976 survey (See M56-56) M65-12

From which:

A 14" Madrone bears N.6°E., 18.6 ft. with bark scribing "CC T22S R10W S6 BT" visible.

CONT. NEXT PAGE

L.E. Monrean, County Surveyors Office
P. Earle; J. Cook; K. Cheney
June 24, 1976
C.S. 59/15

M. Lenora Ladig
Surveyors Office
J. Cook and K. Cheney
July 21, 1976
C.S. 59/18

L.E. Monrean
K. Cheney
Oct. 25, 1976
C.S. 59/24

G. Langlitz
P. Earle
Oct. 25, 1976
C.S. 59/24

Douglas County Surveyors Office