

Douglas County Surveyor's Record of
Government Corners Renewed

T. 22 S. T. S. R. 10 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21981

Richard J. Hintz
For: International
Paper Company
June 1983
M 94 - 48

1/4 Corner for Section 35 only, South side. 87
Found - 1970 iron pipe with brass cap, BLM. (See also Ren. #6)
20" maple (sawed stump) bears N.33° 15'E., 32.3 ft., 1970 BT,
Set - 50 d. nail in top, center of maple stump.
5/8" x 36" iron rod with stamped cap (P.L.S. 497) in top,
center of a 48" sawed fir stump which bears N.56°00'E., 18.90 ft
6/83

1/4 Corner for Secs. 13 and 24. 88
Set - 1" iron pipe with brass cap marked 1/4 S13, S14, T22S R10W.
New BTs- 14" Alder, S.81°W., 16.9 ft.
9" Alder N.28°E., 5.0 ft.

FD. B.C.
4 BTs 9/91
M114-11
G. SOLARZ

Eugene Wobbe, LS #1093
For: International
Paper Company
June 15, 1983
M 94 - 51

1/4 Corner for Section 24 only (west side) 89
Set - 1" iron pipe with brass cap marked 1/4 S24 T22S R10W. (S24 only).
New BTs- 18" alder, N.66°E., 24.2 ft.
14" Hemlock, S.16°E., 10.5 ft.
Note: This corner is N.02°19'51"W, 103.56 ft. of the Douglas County
Surveyors Office Renewal #55 recording as 1/4 corner for secs. 23 and 24
by the Oregon State Board of Forestry, 1969.

1/4 corner for Sec. 24; and Sec. 19 of T.22-9. 90
Set - 1" iron pipe with brass cap marked 1/4 S19, R9W, S24 R10 W T22S.
New BTs- 16" hemlock, N.30°W., 9.1 ft.
18" hemlock, N.63°W., 21.2 ft.

6/15/83

Lloyd D. Smith
Witness: James
McIntosh
For: OSBF
Sept. 13, 1983
C.S. 58/164

1/4 Corner for Sec. 23 only, (east side) 91
Found - A reestablished corner by A.G. Gibson, 1969, a 1 1/2" x 36"
galv. I.P. 34" in ground from which: Ren. #55
24" hemlock bears S.12 3/4°E., 36.0 ft.; now 25" in place, (I
obliterate face).
45" fir bears N.82 1/2° W., 35.6 ft.; now 47" in place, face
closed.
Set - Remarkd 1/2" x 36" Galv. I.P. with 3" bronze cap "OREGON STATE
BOARD OF FORESTRY T22S R10W 1/4 S23 1983 LS1101".
New BT - 33" fir bears S.42 1/2°W., 31.3 ft. to face; scribed 1/4 S23 BT.
Note - A 4" x 4" x 72" white painted cedar post (1969) NE 1.3 ft. from
corner pipe. Oregon State Forestry Dept. metal location poster
on 47" fir (1969) N.82 1/2°W., 35.6 ft.

9/13/83

Richard J. Hintz
For: International
Paper Company
January 1985
M 98 - 9

1/4 Corner for Sections 33 and 34. 92
Found- Original 5" fir corner tree, now 16" dia. with 1/4 S scribing
visible on partially opened west face.
From Which: I mark new BTs:
28" fir bears N.57°30'E., 32.4 ft. scribed 1/4 S34 BT.
24" fir bears N.17°00'W., 8.2 ft. scribed 1/4 S33 BT.

RE-RENEWED CORNER NO. #112

Donald L. Peel LS 752
April 26, 1985
C.S. 58/256

1/4 Corner for Sections 15 and 16 93
Found - 39" x 28" x 18" (above ground) stone mkd. "+".
30" rotted and burnt fir stub, N.77°W., 13.1 ft. (to face),
scribing visible at eye height "1/4 S".
A rotted fir stub (westerly 2/3 broken off and missing)
S.71°E., 33 ft. 35.2 ft. to whats left of tree.
Set - At corner point, drilled a hole in the rock and cemented in a
2 1/2" brass cap marked "T22S R10W 1/4 S16 S15 PLS 752 1985"
New BTs - 19" fir, S.28 1/2° E., 23.2 ft. scribed 1/4 S15 BT.
22" fir, S.38 1/2°W., 20.2 ft. scribed 1/4 S16 BT.
Note: Corner lies 30 to 40 ft. east of draw, 1750 ft. more or less northerly
up draw. The draw empties into upper end of Housmann's pasture.

4/26/85