

**Douglas County Surveyor's Record of
Government Corners Renewed**

22 T. S. 10 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

James W. Prochnau
PLS #1305
For: U.S. Forest
Service
August, 1985
M 99 - 21 A&B

Section Corner for secs. 1 (T22-11) and Sec. 6 (T22-10) ONLY. 94
Found - Original stone, 6" x 12" x 22" in upright position. Buried Stone.
BT's - Possible remains of original cedar BT, now a windfall out of position.
Set - A U.S. Forest Service 3 1/4" aluminum cap with magnet on a 2 1/2" x 30" aluminum flared pipe. Mkd. PLS #1305. Also set rock-mound.
New BT's - 7" R. Cedar, bears S.14°W., 24.8 ft., scribed T22S R11W S1 BT.
11" R. Alder, bears S.22°W., 41.2 ft., scribed T22S R10W S6 BT.

South 1/4 Corner for Section 31 Only (T21-10) 95
Found - A 1" iron pipe, set by GLO, in 1919.
BT's - 56" Hemlock, bears N.2°E., 29.0 ft., rotten face. (Orig)
50" D. Fir stump, bears N.60°W., 19.1 ft., visible scribe.(Orig)
Set - A U.S. Dept. of Agriculture brass cap, mkd. T21S R10W 1/4 S31 T22S R10W PLS 1305 1985.

Witness Corner for Meander Corner, Sec. 6, Rg.10 and Sec. 1, Rg. 11. 96
Set - 3 1/4" USFS alum. cap with magnet on a 2 1/2" x 30" alum. pipe with flared base. Cap properly marked and with PLS #1305. Cap and pipe bears N.0°39'52"E., 23.26 ft. on line from true position.
New BTs- 34" D. fir bears S.21°E., 10.5 ft. scribed "X" BT.
10" maple bears N.16°W., 7.8 ft. scribed "X" BT.

Daniel W. Baker
For: International Paper
April 1987, M 104 - 19
C.S.63/50

1/4 Corner for Section 36 Only. 97
Set - A 5/8" x 30" iron rod and cap.
BT's - A 18" fir bears N 4°E, 38.1 ft. Scribed "1/4 S36 BT".
Set - 18" fir bears N80°E, 38.5 ft. Scribed " 1/4 S36 BT".
Note: Distances to 7" spike in side and center, bearings magnetic Var. 20°.

Section Corner for Section 35 & 36. 98
Found - A Oregon State Board of forestry brass cap "1958". Ren. #5
BT's - A 33" Hemlock bears N44°E, 9.0 ft. OSBF
60" fir stump bears S75°W, 76.0 ft. 1894
54" fir stump bears N75°W, 34.5 ft. 1894
16" hemlock bears N66°W, 33.0 ft. 1970 BLM BT

Ronald Stuntzner
L.S. 1342
For: Westbrook
Land & Timber
July, 1989
M 108 - 41

1/4 Corner for Sections 13 and 14 99
Found - 48" Fir (original) now a 10 ft. high snag N.89°E., 26.4 ft. with face. Scribes are rotted away.
Creek is 4.0 chains South and matches GLO distance.
Set - A 3/4" iron rod with 2" alum. cap 30" long, stamped Stuntzner Engr.
New BTs - I scribed a 36" Fir, N.81°W., 14.4 ft.
I scribed a 14" Chittum, N.41°E., 41.1 ft.
July, 1989

Arnold Gibson
For: Dept. of
Forestry
Nov. 12, 1974
M 55 - 13

East 1/4 Corner for Section 17 only 100
Set - Oregon state Board of Forestry 1 1/2" x 36" galv. I.P. and 3" bronze cap. 28" in the ground.
BTs - 11" cedar, S.31°E., 57.3 ft. with RS 359
3" Fir, S.77°W., 35.4 ft.
4"x4"x72" white painted cedar post bears S.13°E., 1.5 ft.

Ronald Stuntzner
For: Siuslaw Nat'l
Forest
Sept. 1989
M 108 - 75

1/4 Corner for Sections 8 and 9 101
Found - Original corner stone with 1/4 S chiseled on west face.
4" D. fir (now 43") S.77°W., 15.3 ft. (faintly visible face on NW quad. 1894 BT.
36" D. fir (now rotted remains) N.18°E., 21.3 ft. 1894 BT.
Set - 2" x 30" alum. pipe with 3" alum. cap mkd. "T22S R10W 1/4 | S9 1989 LS 1342.
New BTs - 17" D. fir N.65°E., 8.0 ft. scribed 1/4 S9 BT.
13" D. fir N.19°E., 24.0 ft. scribed 1/4 S9 BT.

9/89