

**Douglas County Surveyor's Record of  
Government Corners Renewed**

T. 22      T. S.      R. 10      R. W. W. M.

FORE-CHAPMAN CO., EUGENE, ORE. 21881

Closing Corner for sections 14 & 15. 107  
 Found - Stone as called for in original G.L.O. notes, marks plain.  
 Rotted fir snag bears S. 1°E., 79.7 ft. (89.1 ft. orig.)  
 Rotted fir stump bears N.3°W., 36.3 ft. (orig.)  
 The original SW bearing tree is down.  
 New BT's 6" fir bears S.38°W., 17.3 ft. scribed "S15 BT" w/X and tag.  
 6" fir bears S.34°E., 4.6 ft. scribed "S14 BT" w/X and tag.  
 Oct. 1991

Standard Corner for sections 10 & 11. 108  
 Set - 3/4" X 30" iron rod with 2" aluminum cap at original position.  
 Fnd BT's - Rotten fir snag bears N.72°W., 121.1 ft. (orig. 125.4 ft.)  
 Rotten fir snag bears N.5°E., 84.1 ft. (orig. 99.0 ft.)  
 Rotten fir snag bears S.84°E. 52.5 ft. (orig. 54.8 ft.)  
 New BT's 38" fir bears N.86°W., 11.3 ft. scribed "T22SR10W S10 BT" w/X and tag.  
 18" alder bears N.25°E., 48.5 ft. scribed "T22SR10WS11 BT" w/X and tag.  
 Oct. 1991

1/4 Corner for Sections 15 & 22. 109  
 Found - 2 1/2" brass cap with original stone alongside  
 Fnd BT's 43" fir stump bears N.37°W., 20.5 ft. w/healed face.  
 48" fir stump bears S.38°E., 29.0 ft. w/healed face.  
 New B.O. Power pole no. 9E bears N.31°E., 81.3 ft.  
 Oct. 1991

Section Corner for Sections 11, 12, 13 & 14. 110  
 Fnd. BT's - Fir snag bears N.21°W., 46.2 ft. (orig)  
 Fir snag bears S.80°E., 57.4 ft. (orig)  
 Fir snag bears N.83°E., 57.4 ft. (orig)  
 Set - 3/4" X 30" iron rod w/aluminum cap marked "Stuntzner Engineering  
 T.22S R10W S11, S12, S13, S14 1991 LS 2244"  
 Oct. 1991

1/4 Corner for Sections 13 and 14. 111  
 This 1/4 corner has been reset from the original position as  
 set. (See Stuntzner's survey M 108 - 41). Pulled out the old  
 iron rod and chopped off the blazes on the BT's. The new  
 1/4 corner bears N.64°08'08"E., 147.67 ft. from old corner.  
 Set - 3/4" iron rod w/aluminum cap marked "Stuntzner Engineering  
 T.22S R.10W 1/4 S14 | S13 1991 LS 2244".  
 New BT's - 15" fir bears S.81°W., 19.3 ft. scribed "1/4 S14 BT" w/X and tags.  
 15" alder bears N.83°E., 33.0 ft. bark scribed "1/4 S13 BT"  
 w/X and tags.  
 17" alder bears S.27°E., 43.4 ft. bark scribed "1/4 S13 BT"  
 w/X and tags.  
 51" fir bears S.16°W., 43.3 ft. scribed "1/4 S14 BT" w/X and tags.  
 Oct. 1991

1/4 Corner for Sections 33 and 34 112  
 Found - 5" now 16" dia. D. Fir with scribing visible on opened  
 west blaze "1/4". Original Corner tree.  
 28" now 29" dia. D. Fir with a partially healed sinlge blaze,  
 illegible scribing visible, bears N.51 1/2°E , 32.4 ft. (agrees  
 with record) Ren. No. 92  
 24" now 27" dia. D. Fir with a partially healed single blaze  
 scribing visible " /4 S33 BT" bears N.17°W., 8.2 ft. (agrees  
 with record) Ren. No. 92  
 New BTs - 24" dia. D. Fir double blazed and scribed "1/4 S33 CS BT" bears  
 S.22°W., 5.2 ft.  
 14" D. Fir double blazed and scribed "1/4 S34 CS BT" bears  
 S.87°E., 21.7 ft.

3/4/92

For: Jerry Harris  
 By: Harvey Wilcox  
 LS 2244  
 M 113 - 76 A & B  
 Aug. 1991

Douglas County  
 Surveyors Office  
 Randall Smith  
 March 4, 1992  
 C.S. File 64/24