

Douglas County Surveyor's Record of
Government Corners Renewed

22 T. S. 11 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97196

H.L. Eppstein
P. Wolford
G. Sparr

$\frac{1}{4}$ Section Corner to Sec. 3 North
Drove 2" x 4" Galv. Iron Pipe in ground where old stake
was almost rotted. **33**
Jan. 10, 1926

Section Corner to Secs. 3 & 10 only. (N.E. of Sec. 10 & S.E. of Sec. 3.)
Found Pile of Stone.
Set a 36" Angle Iron with Brass Cap inscribed - Survey Point - **25**
Wilford N. Haines, 239. from which:
12" Fir N.20°W., 26.0 ft.

Section Cor. to Sec.s 2 & 11 only. (N.W. of Sec. 11 & S.W. of Sec. 2)
Found Pile of Stones & Stub of Orig. Fir B.T. S.78°E., 151 lks.
Set 36" Angle Iron with Brass Cap inscribed - Survey Point -
Wilford N. Haines 239.
Marked 2 trees: 16" Fir S.20°E. 8.2 ft.
30" Fir N.72°30'E. 29.3 ft. **61**

$\frac{1}{4}$ Section Corner to Secs. 2 & 3.
Found Rock
Marked 2 Trees: 18" Fir N.35°W. 7.8 ft.
10" Fir N.47°E. 17.0 ft.

Meander Corner to Secs. 2 & 3.
Place for Meander Corner not Set because it would be destroyed by
Road Construction.
Set Witness Corner for Meander Cor. S.03°19'E., 136.84 ft. from
point for Corner.
Set a 36" Angle Iron with Brass Cap inscribed - Survey Point -
Wilford N. Haines 239., from which:
A Spruce bears N.46°36'W. 39.55 ft.
B. O. on rock, N.80°06'E., 35.76 ft.

$\frac{1}{4}$ Corner to Secs. 7 & 8.
Identify Corner from the Orig. BT's:
30" Fir, (now 54") N.5°E., 41.0 ft.
10" Cherry, (now rotten stump) S.45°W., 9.2 ft.
The 12" Cherry tree corner is gone. We drive an Iron Pipe, from which:
10" Myrtle, N.29°W., 14.5 ft. (scribed $\frac{1}{4}$ S7 BT)
54" Fir, N.5°E., 41.0 ft. (scribed bark - $\frac{1}{4}$ S8 BT)
In place of a Post, we Mark a 72" Myrtle, North, 6.5 ft. $\frac{1}{4}$ Corner.

$\frac{1}{4}$ Corner to Secs. 7 & 18
We identify Corner from Orig. BT's:
12" Alder, S.55°E., 7.9 ft. (down & rotted)
10" Alder; N.85°W., 33.0 ft. (down)
We also find a Myrtle Post (not original) at the correct location of Cor.
Set Stone, Iron Pipe, & Post from which:
24" Fir S.5°E. 25.3 ft. (mkd. $\frac{1}{4}$ S18 BT)
16" Cherry, N.31°E., 45.0 ft. (mkd. $\frac{1}{4}$ S7 BT)

Closing Corner to Secs. 7 & 18 on West Boundary of Twp.
Identify Corner from Orig. BT's of latest Gov't Survey:
60" Fir, N.31°E., 32.0 ft. (remarked)
72" Fir, S.65°E., 39.0 ft. (chopped out - scribing visible)
Set Iron Pipe & Post from BT's; From the size of the BT's. &
examination of our available notes, we question whether the last
Gov't survey set this corner in the location of the original survey. **# 143**

Wilford N. Haines
January, 1956
C. S. File No. 42/121

S. O. & H. J. Newhouse
For Cape Arago Lumber Co.
March, 1957
C. S. File No. 42/256
Map File M 1 - 54