

Douglas County Surveyor's Record of
Government Corners Renewed

22 T. S. 11 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97196

(continued)

Mark a 60" D. Fir N.8°30' W. 34.0 ft.
This Cor. lays on a West Slope at the N.E. edge of the clear
area mentioned before about 50' North & 40'E. of a draw
going N. W.

Corner to Sections 8 & 9. (Closing Corner) 16
Set 1" x 36" Pipe from the Orig. BT's.
The Alder is present but face is rotted out, so scribe a new tree:
D. Fir 64" DBH S.14°30'W. 22.9 ft.

 $\frac{1}{4}$ Section Corner for Secs. 8 & 9. 17
Set a Pipe from which a:
D. Fir 20" DBH bears N.64° E. 28.2 ft.
D. Fir 22" DBH bears S.48°W. 2.0 ft.

Center Section $\frac{1}{4}$ Corner. (Sec. 8) 18
Move this Corner(Newhouse) North 9.0 ft.
Use Same BT's: D. Fir 48" DBH bears N.87°W. 28.4 ft.
Myrtle 10" DBH bears S.10°30'E. 13.8 ft.
This Corner lays South about 12 ft. from the top of EW ridge.

C. C. Common to Sections 31 & 32. 19
Original: Post (now missing) from which a:
14" Maple bears N63E 135 lks.; now 24" clump.
14" Cherry bears N20" 228 lks.; now 16", faint bark scribe visible.
50" Burnt Fir bears S32E 189 lks.; now rotted & burnt stub, 6' high
North $\frac{1}{4}$ Section 6 bears N88° 55' W. 39.6 ft.; in place(see
records for restoration).
Restored: Set 1 $\frac{1}{2}$ " x 36" galvanized Iron Pipe with 3" Bronze Cap marked,
"OREGON STATE BOARD OF FORESTRY T22S R11W CC S31 S32 R11W S6
1958 RS359", 33" in ground, & from which a:
21" Alder bears S38E 19.0 ft.; bark scribed RS 359.
10" Myrtle " N50E 8.0 ft.; bark scribed T22S R11W S32 BT.
26" Maple bears N17W 105.2 ft.; wcribed T22S R11W S31 BT.
Set 4 x 4 x 72" white painted Cedar Post 1.5 ft. NW of pipe.
Oregon State Board of Forestry metal location poster on 10" Myrtle BT.

Township Corner Common to Secs. 1 & 6, T.23S. R.11 & R.12W. 20
Original: Post (now missing, $\frac{1}{2}$ " Iron Rod set in place by Elliott
State Forest Survey) from which A:
20" Maple bears N67W 50 lks.; now missing, clump in place.
10" Maple bears N82E 40 lks.; now 15", chopped out by
unknown party, no scribed visible.
Closing Township Corner bears West 480 lks.; in place(see
restoration records).
Restored by Clifford Stephens, 1952. (58/37)
8" Fir bears S81E 39.6 ft.; now 13", scribed BT S6T2 R11 visible.
Restored: Set 1 $\frac{1}{2}$ " x 36" galvanized Iron Pipe with 3" bronze cap
marked "OREGON STATE BOARD OF FORESTRY T22S R11W S31 T23S
R11W R12W S1 S6 1958 RS 359", 33" in ground over $\frac{1}{2}$ " Iron
Rod, and from which a:
17" Myrtle (inclump) bears S24W 58.6 ft. bark scribed T23S
R12W S1 BT.
28" Fir bears N49E 67.6 ft.; scribed RS 359.
Set 4 x 4 x 72" White painted Cedar Post 1.0 ft. NW of Pipe.
Oregon State Board of Forestry metal location poster on 8" Fir BT.

Warren D. Hootman
For Cape Arago Lumber Co.
August, 1958
D. S. File No. 42/386
Map File No. M 12 - 47

Arnold G. Gibson
Elbert Driver, Transitman
Witnesses: Robert Banks & Derald Timmons
November, 1958
C. S. File No. 42/403

RE-RENEWED CORNER NO. #114

RE-RENEWED CORNER NO. #176