

Douglas County Surveyor's Record of
Government Corners Renewed

22 T. S. 11 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97196

OREGON STATE BOARD OF FORESTRY
Arnold G. Gibson Filed Feb. 24, 1958
By Elbert Driver
Witnesses: Derald Timmons
Ron Witham
C. S. File No. 42/340

Section Corner common to Sections 3 & 10 (East Side) 25
Orig. - Post in Stone Mound (Post missing & Stone mound distrbd
by uproot).
Resurvey by William Whipple, 1893.
Stone 20 x 12 x 10" (now missing)
Restored by Wilford Haines, Jan. 1956. - SEE REN. NO. 2
36" angle iron with brass cap (found in place 1" sheet metal
cap) from which a:
12" Fir N.20°W. 26.0 ft.; now 13", scribed T22S R11W S3 BT visible.
Restored: Set 1½" x 36" galvanized iron pipe with 3" bronze cap marked
"Oregon State Board of Forestry T22S R11W S3 S10 S11 1958
RS 359," over above angle iron, 33 in. in ground, in mound
of stone, and from which a:
11" Madrone bears N.51°W. 43.4 ft. scribed T22S R11W S3 BT.
28" Fir bears N.85°W. 53.5 ft. scribed RS 359
17" Fir Stump " S.50°W. 12.5 ft. scribed T22S R11W S10 BT.
Set 4x4x48" white painted cedar post 1.0 ft. S.W. of pipe.
Oregon State Board of Forestry metal location poster on 10" Fir N.81°E.25.2'.

¼ Corner common to Sections 3 & 10. 26
No evidence of Original corner found.
Reestablished: Set 1½" x 36" galvanized iron pipe with 3" bronze
cap marked "Oregon State Board of Forestry T22S R11W S3 S10 1958 RS 359,"
33 inches in ground, in mound of stone, and from which a:
24" Fir bears S.52°W. 114.9 ft. scribed ¼ S10 BT.
21" Maple (stump) S.41½°W. 101.0 ft. scbd. RS 359.
Set 4x4x48" white painted Cedar post 1.5 ft. N.W. of pipe.
Oregon State Board of Forestry metal location poster on 25" Fir
stump S.66°W. 68.5 ft.

FD. OK 5/85
K. DeGroot
M 98-57108
F. OK 3/86
L. Smith
M100-30
27

Section corner common to Sections 3 & 10 (West Side).
Original - Stone 12"x10"x7" (found lying down in place, 5 notches on S.
& 3 notches on E. 4x4x48" white painted cedar post algside).
12" Dead Cedar bears N.30°E. 22 lks.; now missing.
Resurvey by William Whipple, 1893.
4" Willow bears N.74°E. 10 lks.; now missing.
3" Alder bears S.31°W. 50 lks.; now missing.
5" Willow bears N.11°W. 8 lks.; now missing.
A 4 ft. rock bluff bears South 4 lks; now in place.
Restored: Reset orig. Stone in ground in mound of rock, & from which a:
32" Fir bears S.82½°E. 77.6 ft.; scribed T22S R11W S10 BT.
12" Fir stp. bears S.27½°W. 9.7 ft. ; scribed RS 359.
4" high rock bluff bears S.5½°W. 5.0 ft. scribed X B0(2' up from bottom)
Reset 4x4x48" white painted Cedar post 2.5' NE of corner stone.
Oregon State Board of Forestry metal location poster on 14" Alder N.67°E.27.0'

¼ Corner common to Secs. 4 & 9. 28
Original - Post (now missing, found rotted stake point in place &
4x4x48" white painted Cedar post 6" from stake hole).
4" Cherry bears N.2°E. 27 lks.; now missing.
48" Fir bears S.65°W. 44 lks.; now 56", uncovered scribes
S 4, remainder unexposed.
Restored:- Set 1½" x 36" galvanized iron pipe with 3" bronze cap marked
"Oregon State Board of Forestry ¼ S4 S9 1958 RS 359," 33 in.
in ground, and from which a:
16" Fir bears N.54°E. 10.0 ft.; scribed ¼ S4 BT.
12" Fir bears S.61°E. 6.5 ft.; scribed RS 359.
Reset 4x4x48" white painted Cedar post 1.5' SW of pipe.
Oregon State Board of Forestry metal location poster on 8" Fir S.31°W. 7.0'.

Closing Corner common to Sections 4 & 9 (East Side) 29
Original - Post (now missing, found 4 x 4 x 48" white cedar post in
stone mound) from which a:
4" Fir bears S.16°W. 39 lks.; now 26", uncovered burnt face,
original axe work visible.
3" Fir bears N.63°W. 51 lks.; now 28" stump, face unexposed,
distance is 13.9 ft.
8" Alder bears S.57°E. 195 lks.; now missing.

(cont'd over)