

Douglas County Surveyor's Record of
Government Corners Renewed

22 T. S. 11 R. W. W. M.

KORE-CHAPMAN CO., EUGENE, ORE. 97196

C.C. Sections 4 & 9 (East Side)

29

Restored - Set 1½" x 36" galvanized iron pipe with 3" bronze cap marked "OREGON STATE BOARD OF FORESTRY T22S R11W CC S4 S9 S10 1957 RS 359," 33 inches in ground, in mound of stone, and from which a:
20" Fir bears S.52°W. 5.7 ft.; scribed T22S R11W S9 BT.
28" Fir stump(orig.) bears N.63°W. 13.9 ft.; scribed BT.
26" Fir bears S.86°E. 16.8 ft.; scribed RS 359.
Set 4 x 4 x 48" white painted Cedar Post 1.5 ft. N. of pipe.
Oregon State Board of Forestry metal location poster on 28" Fir stump BT.

Arnold G. Gibson
Elbert Driver
Feb. 24, 1958
C. S. File No. 42/340

¼ Corner common to Sections 10 & 15.

Original - Post (now missing, found 4x4x48" white painted cedar post in stone mound out of place), from which a:
8" Fir bears S.72°E. 75 lks.; now 33", face unexposed.
12" Fir bears N.80°E. 74 lks.; now 36", uncovered, scribed ¼ S, remainder unexposed.

(This corner not common on gov't plat. Field Notes & Plat do not agree. Consult Mr. Berlin's Office.)

Restored - Set 1½" x 36" galvanized iron pipe with 3" bronze cap marked "OREGON STATE BOARD OF FORESTRY ¼ S10 S15 1957 RS 359," 33 inches in ground, in mound of stone, and from which a:
28" Fir bears S.4¼°W. 24.8 ft.; scribed RS 359.
33" Fir(orig) bears S.72°E. 49.5 ft.; scribed BT.
Reset 4 x 4 x 48" white painted Cedar post 1.0 ft. N.E. of pipe.
Oregon State Board of Forestry metal location poster on 36" Fir BT.

see Below

30

¼ Corner for Section 10(South Side).

Original - Post (now missing, found 4 x 4 x 48" white painted Cedar post in stone mound out of place) from which a:
8" Fir bears S.72°E. 75 lks.; now 33", face unexposed.
12" Fir bears N.80°E. 74 lks.; now 36", uncovered scribed ¼ S, remainder unexposed.
Restored - Set 1½" x 36" galvanized iron pipe with 3" bronze cap marked "OREGON STATE BOARD OF FORESTRY ¼ S10 1958 RS359", 33 in. in ground, in mound of stone, & from which a:
28" Fir bears S. 4¼°W. 24.8 ft.; scribed RS359.
41" Fir bears N.57½°E.79.8 ft.; scribed ¼ S10 BT.
Oregon State Board of Forestry metal location poster on Orig. 12" Fir BT.

Arnold G. Gibson
Elbert Driver, Transittman
D. Timmons - R. Witham
July 11, 1958
C.S. File No. 42/340

31

Section Corner common to Secs. 5 & 6 (North Side), T.23S. R.11W.

Original - Post(now missing from which a:
40" Cedar bears N32E 85 lks.; now missing, roots in place.
40" Fir bears S52W 50 lks.; now rotted & burnt up-root.
60" Fir bears S57E 298 lks.; now 54" burnt & rotted stub, scribed T23S R11W S5 remaining.
8" Alder bears N20W 46 lks.; now missing.
Restored by Wm. R. Whipple, 1893
Stone 14 x 12 x 6" (found in place, 5 notches on the East) from which;
50" Burnt Fir bears N87E 115 lks.; now missing.
Restored: Built mound of stone around orig. stone, from which a:
11" Fir bears S89½E 59.1 ft.; scribed T23S R11W S5 BT.
20" Fir bears S37W 94.2 ft.; scribed T23S R11W S6 BT.
5" Fir bears N72W 10.5 ft.; scribed RS359.
Ore. St. Bd. of Forestry metal location poster on above 5" Fir.
Set 4x4x72" White painted Cedar Post 1.5 ft. SE of pipe.

Arnold G. Gibson
Elbert Driver, Transittman
R. Banks - D. Timmons
November, 1958
C. S. File No. 42/403

¼ COR. COMMON TO SEC. 6 (NORTH SIDE) T.23S. R.11W. - - -

Original - Post (now missing) from which a:
10" Myrtle bears N2E 115 lks.; now 14" clump in place, no scribed visible.
50" Fir bears S72E 235 lks.; now 32" x 5 Ft. high rotted & burnt stub.
Closing Corner 31 & 32 bears S88° 55'E 39.6 ft.; in place.
Note: The Elliott State Forest Survey Party of 1939 found this corner.
Restored: Set 1½" x 36" Iron Pipe with 3" bronze cap mkd, "Ore. St. Bd. of Forestry ¼ S6 1958 RS 359", 33" in ground & from which a:
13" Fir bears S2W 78.7 ft.; scribed ¼ S6 BT.
15" Fir bears S30W 92.0 ft.; scribed ¼ S6BT RS 359.
Set 4x4x72" white painted cedar post 1.5' SW of Pipe. Metal Poster on 32" Myrtle N46½E 26.5'

32