

Douglas County Surveyor's Record of
Government Corners Renewed

22 T. S. 11 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21801

Warren D. Hootman
For Western Lane
Logging Co.
July 1, 1959
C. S. File No. 51/30
M/15-23

33
1/4 Corner common to Section 3, T22S, R11W, & Sec. 34, T21S R11W.
Said Point being marked by a 1 1/4" Pipe & witnessed by a Ren. #1
57" Spruce Tree. This is the Orig. BT. for Sec. 3, the
face has grown closed, so I rescribed this tree in a
different place. It is now a Spruce 57" DBH, bearing
S.31°30'E. 47.3 ft. I also mark, A forked Spruce 40" DBH,
bears N.70°00'W., 14.5 ft. 60
This Corner lays in a swamp 131.8 ft. South of the shoulder of
the Deans Creek Road.

Wilford N.
Haines
July 20,
1960
C.S. File
No. 51/109

34
1/4 Section Corner to Sections 6 and 7.
I find Iron Pipe; REN. #12
Fir B.T., now a Stump
Myrtle B. T. Gone.
I drive a 1" x 1" x 48" T. Iron 24" in ground by Pipe.
No new Bearing Trees.

Wilford N. Haines
August 1960
C. S. File No. 51/109+

35
Witness Corner to Sec. 7, T22-11W. & Sec. 12, T22S-12W.
Found - 30" Tree marked for Angle Wit. Point on the East Line of
Sec. 12 at 62.45 chs. This tree is now a stump,
it apparently was 24" when scribed, it is now 32"
inside the bark. There is a "R" on the stump and the
old scar goes down about 10"-12". I found an S 7 on
a log that came off the stump.
I drove a 1" x 1" x 24" T. Iron about 12" in the center of the
Stump for A.W.P. Corner.
Drove a 1" x 16" Bolt in center of a 42" Fir Stump N.21°W. 23.6 ft.
Drove a 1" x 5" lag screw in the center of a 54" Fir Stump N.72°W. 34.6 ft.

Arnold G. Gibson
For Ore.St.Bd. of Forestry
Transitman: E. Driver
July 1960
C.S. File No. 42/403+

36
C. C. common to Secs. 17 and 20 (East Side)
Original: Stone 14" x 12" x 7" (found a badly weathered stone in
place, no trace of notches) from which a:
30" Fir bears S.2°W. 215 lks.; now a rotted stub.
20" Cherry " N.42°W 118 lks.; missing.
60" Fir bears N.86°E. 65 lks.; now 73", portion of
face exposed by unknown party, scribe 1 visible,
remainder unexposed.
Restored: Set 1 1/2" x 36" gal. I. P. with 3" bronze cap mkd "Ore.St.Bd. of
Forestry T22S R11W S17 S20 S21 CC 1960 RS359", 14" in grd.
down to solid rock, in mound of stone, and from which a:
14" Fir bears S.41 1/2°W. 16.3 ft.; scribed T22S R11W S20 CC BT.
25" Fir bears N.17°E. 6.7 ft.; scribed RS359.
Oregon State Board of Forestry metal location poster on 14" Fir BT.
Corner falls on top of spur ridge sloping North.

C. S. File
No. 42/403
Dec. 1960

FOUND OK 5/91
NEW ACCESSORIES
M 112-29

37
Witness Point common to Secs. 19 & 24, T22S R11 & 12W.
Orig.-12" Line Tree at 57.89 ch. S. on E. boundary Sec. 24, 2 notches
North & South sides(found uprooted, notches remaining, root hole
in place) from which a: Ridge, course E & W, bears S.21 lks.
now in place.
Restored - Set 1 1/2" x 36" gal. Iron Pipe with 3" Br. cap mkd: "Ore.St.
Bd. of Forestry W P S24 S19 1960 RS359", 30" in gr., in
mound of rock, & from which a:
26" Dbl. Fir bears S. 7°W. 15.2 ft.; scribed WP S24 BT RS359.
17" Fir bears S.56°E. 10.3 ft.; scribed WP S19 BT.
3' high by 6' wide rock face bears S.39°W. 2.7 ft.; scribed X.