

Douglas County Surveyor's Record of
Government Corners Renewed

22 T. S. 11 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21801

Line Tree common to Secs. 19 & 25, T22S, R11 & 12W, 38
Orig. - 14" Fir Line Tree at 7.63 ch. S. on the E. boundary of Sec. 25
with 2 notches on the N. & S. sides (now 28" in place, exposed
one notch on S. side 67 years old.

Ridge top at 6.90 ch. S. on the E. Boundary of Sec. 25 (now in CCC Rd.)
Restored - Scribed Line tree as Witness Point, WP S19 on East side
and WP S25 RS359 on W. side, from which a:
41" Fir bears N. 88 $\frac{1}{2}$ ° E. 56.8 ft.; scribed WP S19 BT.
36" Fir bears S. 43° W. 12.4 ft.; scribed WP S25 BT.

FIND OK 5/91
NEW ACCESSORIES
SEE M 112-29

Closing corner common to Secs. 19 & 30. 39
Orig. - Stone 14 x 12 x 6 (fd. portion of stone with marks CC X &
3 notches remaining) from which a:

12" Hemlock bears N. 51° E. 57 lks.; now 20", scribe R visible
on exposed portion of face, recent scribed BT CC S19 T22 R10 399 also visible.
40" Cedar bears S. 42° E. 53 lks.; now 61", grown over, recent scribes BT CC S30
T22 R11 399 visible.
30" Cedar bears S. 42° W. 26 lks.; now 40", grown over, recent scribes BT CC
S25 T22 R11 visible. Stream, 1 lk., course NE, bears N. 49 lks.; in place.

Restored - Set 1 $\frac{1}{2}$ " x 36" Gal. iron pipe with 3" Br. cap mkd: "Ore. St. Bd. of Forestry
T22S R12W R11W S25 S19 S30 CC 1960 RS359" 33 " in gr. with cor. stone alongside:
49" Cedar bears N. 83 $\frac{1}{2}$ ° W. 26.3 ft.; scribed T22S R12W S25 CC BT RS359.

RE-OPENED CORNER NO. 168

40

Line Tree common to Secs. 25 and 30, T22S, R11 & 12 W.
Orig - 10" Fir Line Tree at 36.27 chs. S. on E. boundary of Sec. 25
with 2 notches on N & S sides (now 20" in place, exposed one
notch on N side 67 years old). Top of ridge, E, at 36.40 chs. in place.

Restored - Scribed Line tree as Witness Point, WP S30 on E. side,
WP S25 RS359 on W. side, from which a:
48" Fir bears N. 62 $\frac{1}{2}$ ° W. 52.0 ft.; scribed WP S30 BT.
43" Fir bears N. 46 $\frac{1}{2}$ ° E. 18.0 ft.; scribed WP S30 BT.

FIND OK 5/91
M 112-29

Arnold G. Gibson
OREGON STATE BOARD OF FORESTRY
Wit: E. Driver
J. Hollingsworth

Dec. 1960 and Jan. 1961
C. S. File No. 42/403

Angle Point corner common to Secs. 25 & 30 (Whipple's 1893 East $\frac{1}{4}$ Cor. 41
25), T22S, R11 & 12W.

Orig. - Stone 14 x 10 x 6 (now missing) from which a:
8" Cedar bears S. 65° W. 25 lks.; now 22", exposed Orig. scribe 4,
recent scribes BT $\frac{1}{2}$ S25 T22 R12W 399 outside.
6" Chittum bears S. 22° E. 29 lks.; missing.
Ridge, course E. bears North 360 lks. in place.
10" Line tree bears N. 373 lks.; in place (restored as WP).

Note - Also fd. a 5/8" iron pin S. 16° E. 3.5 ft. & a 22" Cedar
N. 49 $\frac{1}{2}$ ° W. 25.4 ft. scribed BT $\frac{1}{2}$ S25 T22S R11.
Restored - Set 1 $\frac{1}{2}$ " x 36" gal. iron pipe with 3" br. cap mkd.
"Ore. St. Bd. of Forstry AP S25 S30 1960 RS359", 35" in gr.,
in mound of stone, and from which a:

30" Cedar bears N. 26° W. 45.9 ft.; scribed AP S25 BT RS359.
Ore. St. Bd. of Forestry metal location poster on Orig. 8" Cedar BT.
Note - We erased the recent scribed "4" on above trees S. 65° W. & N. 49 $\frac{1}{2}$ ° W.

RE-OPENED CORNER NO. 133

42

$\frac{1}{4}$ Section Corner common to Secs. 11 and 14.

Orig. - 15" Alder (now 17" windfall, faces rotten) from which a:
30" Cedar bears S. 45° W. 37 lks.; now 61", rotten face
exposed, no scribe marks visible.
14" Alder bears N. 45° E. 31 lks.; now 21" rotten stump.
Dry Creek, course North, bears East 85 lks.; in place.
Restored: Set 1 $\frac{1}{2}$ " x 36" gal. I. P. with 3" bronze cap mkd: $\frac{1}{4}$ S11 S14 1961 RS359,
in mound of stone, and from which a:
61" Cedar (Orig) bears S. 47 $\frac{1}{2}$ ° W. 21.7 ft.; scribed $\frac{1}{4}$ S14 BT.
60" Cedar bears N. 58° W. 29.1 ft.; scribed $\frac{1}{4}$ S11 BT.
14" Cedar bears S. 87 $\frac{1}{2}$ ° E. 16.9 ft.; scribed RS359.

Oregon St. Bd. of Forestry metal location poster on 14" Cedar BT.
Set 4" x 4" x 6" white painted Cedar Post 1.7' SE of pipe.

Feb. 6, 1961