

Douglas County Surveyor's Record of
Government Corners Renewed

T 22 S. T. S. R. 11 W. R.W.W.M.

KOYE-CHAPMAN CO., EUGENE, ORE. 21881

James W. Byron, County Surveyor
John M. Powell & Crew
For: Doug. County--Feb.- June, 1971
C.S. File 56/5 Map M 42 - 27

1/4 Corner to Section 6 only, T22-11W. 106
This corner set by survey & lies in bottom of ravine, runs N-S.
Set-Brass Cap at Cor.Mkd: County Surveyor's R T 22 S R
Office 12 1 11
1971 W 4 S 6 W
Bearing Tree: 80" Cedar S.80°W. 63.4 ft. scribed " 1/4S6 CS BT"
No other trees available. 7/9/71

Cl. Corner to Sections 6 and 7, T22-11W. 107
This corner set from survey.
Set-Brass Cap at Cor.Mkd: County Surveyor's R T 22 S R
Office 12 S 6 11
1971 W S 12 S 7 W
Bearing Tree: 13" Alder S.14°W. 15.3 ft. mkd: "T22S R12W S12 CS B"
8" Alder S.20°E. 17.9 ft. mkd: "T22S R11W S7 CC CSBT"
B.O.: 5/8" I.Rod N.46°E. 20.0 ft. This rod lies on westerly
edge of marshy ground. 6/8/71

JAN. 1972

Arnold Gibson
Ore.St.Bd.of
Forestry
8/13/71
Map File
M 44 - 32

S 1/16 Corner between Sections 9 and 8. 108
Established. Obliterated Hootman's 1/16th corner S.23°08'E.
58.41 ft., as per agreement with him.
Set-Ore.St.Bd.of Forestry I.P. & 3" Bronze Cap, inground.
31" Fir Stump N.59 1/2°W. 22.1 ft. (RS359) YMLP.
"X" on 8'x20' Rock Face, in slide out draw, N.21 1/2°E. 43.4 ft.
9" (X BO) 4"x4"x72" White painted Cedar Post, N.54°E. 3.6 ft.

Arnold Gibson
Ore.St.Bd.of
Forestry
8/11/71
M 44 - 34

East 1/4 Corner Section 4, established Witness Corner. 109
Witness Corner N.00°44'E. 15.27 feet.
Set -Ore.St.Bd.of Forestry I.P. with 3" Bronze Cap, in ground. #178
"X" on 3'x4'x5' Boulder in stream bed S.63°W. 72.9 ft.
8" Myrtle (in clump of 12) S.33 1/2°W. 58.0 ft. (RS359)
Yellow Metal Location Poster North 1.5 ft.

Arnold G. Gibson, Ore. State Dept. of Forestry
June, 1971 Map File M 44 - 33

AP Corner Section 24, ^{T22-12W} reestablished. (Orig. Cor. 13 & 24 Whipple
Set-Ore.St.Bd.of Forestry I.P. with 3" Bronze Cap 34" IG. (1893)
9" Alder S.89 3/4°W. 14.2 ft., YMLP 110
11" Cedar S.29 1/2°W. 50.8 ft. (RS359)
White Painted Cedar Post N.W. 1.5 feet. 6/23/71

Closing Corner to Sections 13 and 24 only, T22-12W. 111
Reestablished, Set-Ore.St.Bd.of Forestry I.P. & 3" Bronze Cap,
34" in ground.
6" Alder N. 45 1/4°W. 20.2 feet. (RS359)
4" Alder S. 58°W. 19.9 ft., YMLP.
4"x4"x72" White Painted Cedar Post NW 2.2 feet. 6/23/71

1/4 Corner Section 24 only, T22-12W. 112
Set - Ore.St.Bd.of Forestry I.P. with 3" Bronze Cap 20" in
(1 1/2" x 24" OSBF) concrete in sandstone.
23" Burnt Fir Stump S.79 1/2°W. 99.22 ft. (RS359)
37" Hemlock Stump N.8°W. 98.10 feet
4"x4"x72" White Painted Cedar Post north 4.0 ft. YMLP. #165

A.P. Corner Section 24, ^{T22-12W} reestablished. 113
(Orig. 1/4 Corner 24 by Whipple 1893)
Set-Ore.St.Bd.of Forestry I.P. with 3" Bronze Cap, 52" in ground,
on south edge of Scholfield Ridge Road.
4"x4"x72" White painted Cedar post S.21 3/4°W. 27.5 ft. YMLP
6/23/71

FND OK
5/91 M 112-29