

Douglas County Surveyor's Record of  
Government Corners Renewed

T.22 S. T.S. R. 11 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 31881

114

1/4 Corner common to Sections 8 and 9.  
No evidence of original corner found.  
Reestablishment by Hootman, 1958:  
Iron Pipe(missing) from which a: 20" Fir bears N.64°E. 28.2';  
now 21", scribe marks visible in partially closed face.  
22" Fir bears S.48°W. 2.0 ft.; now 26", scribes 1S  
visible in partially closed face.  
Set-I.P. with 3" Bronze cap mkd: Ore.St.Bd.of Forestry 1/4  
S8 S9 1971 RS359, 34" in ground & from which a:  
27" Fir bears S. 3 1/2°W. 92.7 ft.to face;  
scribed " 1/4 S8 BT RS359".  
21" Fir bears N.34 1/2°E. 73.5 ft.to face;  
scribed 1/4 S9 BT.  
Set 4"x4"x72" White Painted Cedar Post 3.5 ft. N.21°E. of  
corner pipe. Ore.St.Forestry Dept. Metal Location Poster  
on 21° Fir BT N.34 1/2°E. 73.5 ft.  
Also Poster on 26" Fir BT (Hootman) S.48°W. 2.0 ft. (Ren.#17)

115

1/4 Corner common to Sections 25 and 36.  
Orig. 4" Fir(now rotted fir root system, inplace) from which:  
10" Fir bears N.50°W. 12 lks.; now 32", face grown over(N30W)  
50" Burnt Fir bears S.87°E. 18 lks.; now,inplace,  
scribes 1/ visible in rotted face.  
Set-I.P. with 3" Bronze Cap mkd:"Ore.St.Bd.of Forestry 1/4  
S25 S36 1971 RS359", 34" in ground & from which a:  
22" Fir bears N.3 1/2°W. 19.9 ft., toface; scribed 1/4 S25BT.  
22" Fir bears S.48°W. 13.9 ft., to face;scribed 1/4 S36 BT  
RS359.  
Set 4"x4"x72"White painted cedar post 2.1 ft. S.71°W. of  
corner pipe. Ore.St.Forestry Dept. metal location poster  
on 22" Fir BT, N. 3 1/2°W.

116

Angle Point Corner for old North 1/4 of Sec. 2, T23-11W.  
Orig.8" Alder(now missing) from which a:  
8" Fir bears N.23°E. 40 lks.; now 23",in place, scribes  
BT P exposed.  
50" Dead Fir bears S.7°W. 100 lks.; missing, in small slide.  
Set-I.P. with 3" Bronze Cap mkd:"Ore.St.Bd.of Forestry S2 T23S  
R11W AP 1971 RS359", 34" in ground & from which a:  
20" Fir bears N.27°W. 45.7 ft., toface; scribed AP S35 BT.  
19" Fir bears S.3°W. 14.9 ft., toface; scribed AP S 2 BT.  
Set 4"x4"x72" white painted cedar post 2.2 ft. N.65°W. of  
corner pipe. Ore.St.Forestry Dept. metal location poster  
on 19" Fir BT S.3°W. 14.9 ft.

117

1/4 Corner for Section 36 (East Side)  
Orig. Stone 20"x14"x10"(Missing) from which a:  
5" Fir bears N.87°W. 11 lks.; missing.  
40" Burnt Fir bears N.81°E. 32 lks.; in place,  
scribes 1/4 S BT visible  
Set-I.P. with 3" Bronze Cap mkd:"Ore.St.Bd.of Forestry  
1/4 S36 1971 RS359", 34" in ground, & from which a:  
39" Fir bears N.53°W. 31.0 ft. to face;scribed 1/4S36BT RS359.  
32" Fir bears S.54 1/2°W. 86.8 ft.to face;scribed 1/4 S36 BT.  
Set 4"x4"x72" white painted cedar post 1.2 ft. N.55°W. of  
corner pipe. Ore.St.Forsty.Dept.metal location poster on 32"  
Fir BT.

118

Center 1/4 Corner Section 3.

Set 1 1/4" Pipe for center of section.  
No Bearing Trees marked.

May 13, 1972

Hootman,  
Warren D.  
M 45 - 5

Arnold G. Gibson, Oregon State Dept. of Forestry  
Dated October 1971 C. S. File No. 55/233

RE-RENEWED, SEE CORNER NO. #157

SEE CORNER NO. #174