

Douglas County Surveyor's Record of
Government Corners Renewed

22 T. S. 11 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORG. 31881

119

Closing Corner common to Sections 30 & 31, T22S R10 W.
Original Stone 36" x 20" x 10" (in place, CC on west, 5 notches on north,
and 2 notches on east) from which a:
8" Fir, bears N.58°E., 60 lks.; now 23" in place, face grown over
(bearing N.63°E.).
6" Fir, bears S.65°E., 20 lks.; now 29" in place, face grown over.
4" Fir, bears N.46°W., 35 lks.; now missing.
29" Fir, (not recorded) bears S.75°W., 18 ft.; scribe 0 exposed,
approx. 18 years old by ring count.
Set - 4" x 4" x 72" white painted Cedar post N.80°E., 2.6 ft. from above
stone, from which a:
20" Fir bears S.33½°E., 44.9 ft. to face; scribed T22S R10W S31 CC BT.
23" Fir, (orig) bears N.63°E., 40 ft. to face; scribed RS 359.
Set - 4" x 4" x 72" white painted Cedar Post 2.6 ft. N.80°E., of corner stone
Oregon State Forestry Department metal location poster on 29" Fir BT
(orig) S.65°E., 12.3 ft.

Section corner Common to Sections 25 and 36 (East End).
Original 18" x 12" x 18" stone(missing) from which a:
60" Burnt Fir, bears S.59°W., 167 lks.; now 60" snag, in place, scribes
T23S R11W 36 visible.
10" Alder, bears N.41°W., 36 lks.; missing, in slide out.
Set - 1½" x 36" galv. iron pipe with 3" bronze cap marked "OREGON STATE
BOARD OF FORESTRY T22S S25 S36 R11W T22S S31 R10W 1971 RS 359", 35"
in ground, in mound of rock, and from which a:
19" Fir, bears N.41°W., 69.0 ft. to face; scribed T22S R11W S25 BT RS 359.
35" Fir, bears West 100.8 ft. to face; scribed T22S R11W S36 B.
Set - 4" x 4" x 72" white painted Cedar post 3.0 ft. N.50°W., of corner
pipe. Oregon State Forestry Department metal location poster on 19"
Fir BT N.41°W., 69.0 ft.

5/30/72

¼ Corner Common to Sections 35 and 36.
Original Post (missing) from which a:
20" Fir, bears N.56°W., 22 lks.; now 27" freshly cut stump, scribes
1/ visible.
10" Alder, bears N.78°E., 13 lks.; missing.
Set - 1½" x 36" galv. iron pipe with 3" bronze cap marked "OREGON STATE
BOARD OF FORESTRY ¼ S35 S36 1971 RS 359", 34" in ground, in side draw
(course N.30°W.), and from which a:
4' wide rock draw, course N.30°W., bears S33½°E., 8.0 ft.; chiseled
6" x B0
4' high x 20' rock face bears N.54¼°W., 44.6 ft.; chiseled 6" x B0.
Set - 4" x 4" x 72" white painted Cedar post 4.3 ft. S.84°E. of corner pipe.
Oregon State Forestry Department metal location poster on 24" Fir
stump (orig. BT) N.56°W., 13.4 ft. Also poster on 4' high x 20 ft.
rock face N.54¼°W., 44.6 ft.

5/30/72

Southeast Township Corner, Section 36 only, T.22S., R.11W.
Set - 1½" x 36" Iron pipe with 3" bronze cap, 34" in ground, from which a:
36" Fir, N.22½°W., 59.6' With yellow metal location poster. (RS 359)
21" Fir, N.63°W., 79.7 ft.
Set - 4" x 4" x 72" White Painted Cedar Post S.25°E., 2.0 ft.

1/21/72

Angle Point Corner for Sec. 1, (originally ¼ Cor. for Sec. 1), T.23-11.
Found - Original 17" x 12" x 6" Stone, (badly sluffed 4" x 10" stone found
place) from which a:
50" Burnt Fir, bears N.20°E., 38 lks.; now 47" x 20' high Fir snag
in place.
40" Burnt Fir, bears S.41°W., 31 lks.; now rotted root system, 30'
rotted log on ground.
Set - 1½" x 35" Gal. I.P. with 3" bronze cap marked "OREGON STATE BOARD
OF FORESTRY AP S1 T23S R11W 1971 RS369", 35" in ground, with
original stone alongside, and from which a:
28" Fir, bears S.38½°E., 21.4 ft. to face; scribed T23S R11W S1 AP BT.
25" Fir, bears S.14°W., 11.0 ft. to face; scribed T23S R11W S1 AP BT
RS359.
Set - 4" x 4" x 72" WPCP 2.3 ft. S.11°W of corner pipe. OSFD metal location
poster on 25" Fir, S.14°W., 11.0 ft.

11/24/71

Oregon State Board of Forestry - Arnold Gibson
Charles W. Cook, Engineer
May 30, 1972
C. S. File 55/233

Oregon State Board of forestry
Arnold Gibson
Charles Cook, Engineer
May 30, 1972
C.S. File 55/265