

Douglas County Surveyor's Record of  
Government Corners Renewed

22 T. S. 11 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21001

124

Closing Corner Sections 1 and 2 only, T23-11.

- Set - 1 1/2" x 12" OSBF iron pipe with 3" bronze cap 6" in concrete 12' x 7' high sandstone bluff in stream bed crs N.45°W., S.27°E., 65.0 ft., 6" (X BO).  
2' x 3' high sandstone face S.76 1/2°W., 34.1 ft., 6" (X BO).  
30' x 10' high sandstone face S.05 1/2°W., 39.8 ft. with yellow metal location poster.  
1/21/72

125

1/4 Corner, Section 36 only (South).

- Set - 1 1/2" x 36" OSBF iron pipe with 3" bronze cap 34" in ground from which:  
42" Fir, N.81 1/2°E., 22.1 ft. with yellow metal location poster.  
26" Fir, N.59°W., 42.6 ft. (RS 359).  
4" x 4" x 72" white painted cedar post, East 1.1 ft.  
5/30/72

126

Angle point corner for Section 2 only, (orig. sec. cor. 2 and 1, T23-11.

- ound - Orig. stone (missing) from which a:  
50" Dead fir, bears N.67°W., 40 lks.; now 27" x 10' high rotted Fir stub, in place.  
50" Dead fir, bears S.77°E., 72 lks.; now in place, scribes R11W., remaining.  
4" Alder, bears S.81° W., 68 lks.; ;missing.  
Set - 1 1/2" x 36" gal. iron pipe with 3" bronze cap marked "OREGON STATE BOARD OF FORESTRY S2 T23S R11W AP 1971 RS 359", 35" in ground, and from which a:  
35" Fir, bears S.70 1/4°W., 19.6 ft. to face; scribed T23S R11W S2 AP BT.  
28" Fir, bears S.57 3/4°E., 27.1 ft. to face; scribed T23S R11W S2 AP BT RS 359.  
Set - 4" x 4" x 72" white painted cedar post 3.5 ft. S.76°W. of corner pipe. Oregon State Forestry Department metal location poster on 35" Fir, BT S.70 1/4°W., 19.6 ft.  
5/30/72

127

Closing Corner for Sections 35 and 36 only.

- Set - OSBF gal. iron pipe 35" in ground from which:  
34" Fir, N.88°W., 93.5 ft. with yellow metal location poster.  
42" Fir, N.48°E., 39.3 ft. (RS 359).  
Set - 4" x 4" x 72" white painted cedar post South 1.6 ft.  
1/21/72

128

1/4 Corner for Secs. 8 and 17.

- Set - Ore. St. Bd. of Forestry I.P. with 3" Brass cap 34" in ground.  
5" Alder, S.20°W., 11.3 ft. See also Ren. No. 9  
6" Alder, S.87°E., 2.9 ft. yellow metal location poster (RS359)  
4" x 4" x 72" White painted cedar post N.60°E., 1.2 ft.

Oregon State Bd. of Forestry  
Arnold Gibson  
M 51 - 28  
August 1, 1971  
1973

129

1/4 corner for Secs. 17 and 18.

- Set - OSBF I.P. with 3" Brass Cap 33" in ground  
66" Fir, N.38°E., 104.5 ft. YMLP (RS 359).  
4" x 6" sandstone S.38°W., 17.7 ft., 9" (X BO)  
White painted cedar post N.55°E., 3.5 ft.

130

Center 1/4 corner for Section 17.

- Set - OSBF I.P. 34" in ground with brass cap in mound of rock.  
21" Cedar, N.02°E., 33.8 ft. YMLP (RS 359)  
33" Cedar, S.53°W., 102.3 ft.  
White painted cedar post N.83°E., 3.0 ft.

131

1/4 Corner for Section 17 only. East side.

- Set - OSBF I.P. with brass cap 34" in ground in mound of rock.  
6" Alder S.77°W., 57.7 ft. YMLP (RS 359)  
1' x 2' Rock point, S.04 1/2°E., 27.1'4" (X BO)  
White painted cedar post N.65°W., 3.2 ft.

Oregon State Board of Forestry - Arnold Gibson  
Charles Cook - Engineer  
January 21, 1972  
C. S. File 55/265

RENEWED, SEE CORNER NO. #161