

Douglas County Surveyor's Record of
Government Corners Renewed

T. 22 T.S. R. 11 R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21991

132

Oreg. St. Bd. of Forestry by
Arnold Gibson
M 51 - 28
August 1, 1973

1/4 corner for Secs. 16 and 21.
Set - Ore. St. Bd. of Forestry I.P. with 3" Brass Cap 34" in ground
34" Fir, S.28°E., 21.8 ft. Yellow Metal location poster (RS359)
23" Fir, N.65°E., 18.7 ft.
4" x 4" x 72" White painted cedar post S.10°E., 1.8 ft.

133

Angle Point for Corner Section 25, T22-12 only.
(Orig. East 1/4 25)

Found - 14"x10"x6" Stone (missing) from which a:
8" Cedar bears S.65°W., 25 lks. now 19" in place, face buried by side cast debris from road construction, excavated 7.0 ft. to face, scribes BT exposed.
6" Chittum bears S.22°E., 29 lks.; missing.
10" Linetree bears North 373 lks.; in place.
Ridge, course East, bears North 360 lks.; in place.

Restoration by A.G. Gibson, 1961. Ren. No. 41

1 1/2"x36" Gal. I.P. with 3" Bronze cap (missing covered by road construction) from which a:
30" Cedar bears N.26°W., 45.9 ft.; now 22" in place, face now buried by sidecast debris, and inaccessible.
22" cedar bears N.49 1/2°W., 25.4 ft.; now 18" in place, face buried by sidecast debris, and inaccessible.

Set - 1 1/2" x 36" gal. I.P. with 3" bronze cap mkd. "Oregon State board of Forestry T22S S25 R12W AP 1974 RS359" 35 inches in ground, in fill section of road, and from which a:

19" Cedar (orig. 8") bears S.65°W., 16.5 ft. to face; scribed RS359 (7.0 ft. above old face).
22" Cedar bears N.26°W., 46.5 ft. to face; scribed APS 25 BT (at new ground level).

Set - 4"x4"x72" White painted cedar post 8.0 ft. S.47°E. of corner pipe. OSFD metal location poster on 22" Cedar BT N.26°W., 46.5 ft.

6/18/74

134

Angle Point Corner for Section 25 (Whipples 1893 Cor. 25 and 36) T.22-12 only.

Found - Orig. 20"x10"x5" Sandstone (found in place, outer surface decomposed, P remaining) from which a:
8" Maple bears S.48°W., 41 lks.; now 19" in place, expose scribe T.

10" Maple bears ~~N.43°W~~^{N.43°W} 29 lks. now 18" in place, face rotte out.

14" Alder bears S.26°W., 20 lks. missing.

Hootman's Closing Cor. 25 and 36 bears South 104 lks.; in place.

Set - Remarked orig. 20"x10"x5" Sandstone with AP, from which a 27" Myrtle bears S.83°W., 52.3 ft. to face; scribed APS 25 BT RS359.

Set - 37" Fir bears N.8°W., 79.3 ft. to face; scribed APS 25 BT

Set - 4"x4"x72" White painted Cedar post 5.7 ft. N.12°W. of cornerstone. OSFD metal location poster on Orig. 19" Maple BT S.48°W., 27.1 ft.

6/18/74

135

Closing Corner common to Sections 30 and 31.

Found - Orig. 18"x12"x8" Stone (found in place, 5 notches on North side) from which a:

36" Fir stub bears N.65°E., 45 lks.; now 20" x 24" high stub, in place, burnt and badly decayed, no scribes visible.

40" Fir stub bears S.45°E., 192 lks.; missing, in new slide out draw.

36" burnt Fir bears S.43°W., 193 lks.; missing

Spur Ridge bears East 131 lks.; in place.

Rewitnessed: 45" Fir bears N.67°E., 5.3 ft. to face; scribed T22S R11W S30 CC BT.

27" Fir bears S.48°E., 49.1 ft. to face; scribed T22S R11W S31 CC BT RS359.

Set 4"x4"x72" WPCP 2.8ft. N.33°W. of corne-rstone. OSFD metal location poster on 20" Fir North 20.0 ft.

6/17/74

Oregon State Board of Forestry
Arnold G. Gibson
Restored by William E. Metcalf
Present and Witnessed by A. J. Klosterman and J. L. Shumway
June, 1974
C.S. 57/4

J. 1075