

Douglas County Surveyor's Record of
Government Corners Renewed

T 22 T. S. R 11 R. W. W. M.

HOKE-CHAPMAN CO., EUGENE, ORE. 31881

136

1/4 Corner for Section 25 only, T22-12.
Set - OSBF pipe and cap 34" in the ground.
BT's - 22" Cedar, S.53 1/2°W., 53.0 ft. RS 359, with yellow metal location poster.
18" Myrtle, N.80°W., 78.2 ft.
White painted cedar post, S.49°E., 5.9 ft.

4/75

137

Closing corner for Sections 25 and 36 only, T22-12.
Set - 1 1/2" x 10" OSBF pipe and cap 10" in concrete.
BT's - 11" Myrtle, S.32°W., 45.3 ft.
36" Fir, N.79°W., 124.2 ft. RS 359, with yellow metal location poster.
White painted cedar post, S.70°W., 17.9 ft.

138

1/4 Corner for Section 36 only, T22-12.
Set - OSBF pipe and cap 35" in the ground.
BT's - 23" Maple, N.13°W., 74.60 ft. RS 359 with yellow metal location poster.
6" X on 5' x 4' rock face, S.85°E., 7.4 ft.
White painted cedar post, S.70°E., 3.5 ft.

139

1/4 Corner for Section 9 only. South boundary.
Set - Oregon State Board of Forestry 1 1/2" x 36" Galv. I.P. & 3" bronze cap. 35" in ground in mound of rock.
New BT's - 32" Fir, N.33°W., 21.5 ft. with yellow metal location poster, RS 359.
15" Fir, N.55 1/2°E., 18.5 ft. with YMLP
4"x4"x72" white painted cedar post, N.67 1/2°E., 8.0 ft.
1941 Elliot survey post bears S.77 1/2°W., 2.9 ft.

6/5/75

140

Center 1/4 Corner for Section 9.
Set - 1/2" I. P. at CE 1/4
From which:
I scribed: 30" W.R. Cedar, S.38°E., 85.5 ft.
48" D.Fir, N.82°E., 36.3 ft.

6/20/75

State of Oregon
Dept. of Forest
Arnold Gibson
Restored by:
W. Metcalf
June 5, 1975
C.S. 58/56

Ronald E. Stuntz
for: Moore Mill
& Lumber
June 20, 1975
M 57 - 54

West 1/16 corner common to Sec. 3 & 10
Found 1 1/2" x 36" GIP in mound of rock (A Gibson, 1958) in place
From which- 6" Alder bears N.01 E., 68.3 ft. to barkscribes W 1/16 S3 BT
RS 359.
20" Fir stump bears S.84 1/2 W., 44.2 ft. to face; scribed W 1/16
S10 BT

141

Set 4"x4"x72" white painted Cedar post S 43E 2.8 ft. from corner pipe.
Oregon State Forestry Department metal location poster on orig. 31" Fir
stump BT S 61 1/2 W., 12.1 ft.
Jan. 20, 1976

Jan. 20, 1976
CS59/4
State of Oregon
Dept. of Forestry
Arnold G. Gibson
Restored by Anthony J Klosterman
and crew

142

Sec. Cor. common to Secs. 3 & 10, (west side)
Original - Stone 12"x10"x7" (found in place, 5 notches on S & 3 notches
on E from which a: 12" Dead Cedar bears N.30°E., 22 lks.;
missing.

Resurvey by Wm. Whipple, 1893,
4" Willow bears N.74°E., 10 lks.; missing.
3" Alder bears S.31°W., 50 lks.; missing
5" Willow bears N.11°W., 8 lks.; missing.
A 4' rock bluff bears South 4 lks.; now in place.

Restoration by A. Gibson, 1958 Ren. #27
Reset orig. stone in ground in mound of rock (found in place)
From which a:
32" Fir bears S.82 1/2°E., 77.6 ft.; missing, point now in
slide area.
12" Fir stump bears S.27 1/2°W., 9.7 ft.; now 12" stump in
place., scribes RS359 visible.

4' high rock bluff bears S.5 1/2°W., 5.0 ft.; now 4' rock bluff
in place, scribes XBO (2" letters) 2' up from bottom.

Arnold G. Gibson
For: State of Ore.
Dept. of Forest
Witness: James M
McIntosh
June 8, 1976
C.S. 58/31