

Douglas County Surveyor's Record of  
Government Corners Renewed

22 T. S. 11 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

C O N T.

142

Arnold G. Gibson  
For: State of Oregon  
Dept. of Forest  
Witness: James M.  
McIntosh  
C.S. 58/31

4"x4"x48" WPCP bears NE 2.5 ft.; found out of place down hill.  
Rewitnessed: From above stone in mound of stone, a:  
17" Alder bears N.65°E., 25.4 ft. to bark scribes T22S R11W S3 BT.  
10" Alder bears S.06°E., 29.5 ft. to bark scribes T22S R11W S10 BT  
RS359.  
Reset 4"x4"x48" white painted cedar post S.15°E., 5.3 ft. from cornerstone.  
Oregon State Forestry Department metal location poster on 17" Alder BT.  
Also poster on 10" Alder BT.

6/8/76

Closing Corner for Secs. 12 and 13 only. East side.

143

Found - In an area approx. 50 ft. North of C.C. secs. 7 and 18, T22-10,  
we find: A 4" now 14" orig. rotten alder snag with scar. Cut  
into tree. Found no trace of scribing. Bears S.58°W., 2.6 ft.  
A 52" burnt rotten snag bears South 27.0 ft. This tree was called  
as line tree in orig. GLO notes. Found no trace of the line blaze.  
Found no trace of NW BT or orig. corner monument.

At true corner point as determined by the record bearing & dist. of the orig.  
SW BT: WE SET - A 1" x 36" I. Pipe with brass cap mkd.

"Douglas Co. Surveyor" T22S  
1976 S12 | S7  
S13 |  
R11W R10W

New BT's - A 18" D. Fir bears N.61°W., 39.5 ft. scribed "T22S R11W S12 CS BT"  
in double blaze.  
A 11" D. Fir bears S.24°W., 44.4 ft. scribed "T22S R11W S13 CS BT"  
in double blaze with lower blaze starting approx. 2 ft. from  
ground.

Compass declination setting: 20° East.

6/21/76

144

Closing corner for Secs. 7 and 18 only, T22-10.

Found - An orig. BT, a 16" now 54" D. Fir, in good condition with scribing  
"S7 visible on previously opened blaze.

We do not find any trace of the remaining orig. BT's or the orig.  
corner monument.

At the true corner point as determined at the record bearing & distance from  
the only remaining orig. BT, WE SET: A 1" x 30" I. Pipe 26" in the ground,  
with brass cap attached stamped: Douglas Co. Surveyor

T 22 S  
S13 | S7 | CC  
S18 |  
R11W R10W  
1976

From which:

An orig. BT, a 16" now 54" D. Fir bears N.45°E., 39.6 ft.

New BT - A 12" D. Fir bears S.20°E., 21.5 ft. scribed "CC T22S R10W S18 CS BT"  
in a double blaze.

Note: The NE corner of Sec. 13, T22-11 bears approx. North 50 ft.

6/21/76

Section corner for Secs. 1 and 12 only.

145

Found - A stone, 16"x12"x7" with 1 notch on northerly edge & 5 notches  
on southerly edge, "X" chiseled on top. Stone located at the  
base of a small slide area.

A Fir, 12" now 29", bears N.18°W., 45.6 ft. (Rec. N.13°W., 43.6 ft.)  
I partially open blaze & find scribing "S1".

A Fir, 36" now a 55" windfall, badly rotted, bears S.8°W., 72.0 ft.  
approx. (Rec. S.6°50'W., 70.0 ft.) Tree scribed "R11W"

Set - Brass cap at corner stamped "Douglas County Surveyors Office"

R T 22 S R  
11 S 1 | S 6 10  
W S 12 | W  
1976

Set original corner stone on southerly side of cap & place witness sign &  
fence post on east side of cap.

New BT's - A D. Fir, 10" bears S.58 1/2°W., 10.7 ft. double blazed & scribed  
"T22S R11W S12 CS BT"

Original 12" Fir, bears N.13°W., 43.6 ft.

6/24/76

Gary L. Langlitz, Douglas Co. Surveyors Office  
M. Lenora Ladig  
Peter L. Earle, Karen Cheney  
June 21, 1976  
C.S. 59/15

L.E. Monrean, County Surveyors Office  
P. Earle; J. Cook; K. Cheney  
June 24, 1976  
C.S. 59/15