

Douglas County Surveyor's Record of
Government Corners Renewed

T 22 T. S. R 11 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97101

146

M.C. for Sec. 1; and Sec. 6, T22-10
Found - A 2" x 30" I.P. with pump bell .3 ft. below ground in marshy area.
A 58" Spruce, bears S.8°E., 111.5 ft. with re-scribing by
Baughman "S6 MC BT" (See C.S. file M 56 - 56), center rotted,
top dead, with creek, course N-NW, under tree.
No other orig. trees found.

Set - A 1" x 30" I.P. with brass cap 27" in the ground mkd:
Douglas Co. Surveyor T 22 S
1976 M.C.

R 11 S 1 S 6 R 10
W W

Cap set in position of fd. pipe as per bearing and dist. from fd. Bt. Cap set in mound of stone 1 1/2" & 1 ft. below surface of ground. Cap stands .3 ft. above ground.
Place I.P. on N. edge of cap.
Cor. falls in old N-S fence line.
Set - Sign and post 2 ft. south of cor., 32" above ground.
No other BT's available for scribing in west quads.

RE-RENEWED, SEE CORNER NO. #175

10/25/76

147

Closing Corner for Secs. 6 and 7 only of T22-10
Found - A 5/8" I.R set by Baughman in 1976 survey (See M 56 - 56, Aug. 1976)

From Which:
A 14" Madrone bears N.6°E., 18.6 ft. with bark scribing "CC T22S R10W S6 BT" visible.
A 10" D.Fir bears S.50°E., 18.1 ft. with scribing "CC T22S R10W S7 BT" visible on an unhealed single blaze.
A 24" D.Fir bears S.5°W., 29.3 ft. (Rec. per M56-56, 20" Fir, S10°W., 29.3 ft.) with scribing "CC T22S R11W S12 BT", visible on an unhealed single blaze.

We remove the iron rod and Set a 1" x 30" I. P. 27" in the ground with brass cap attached for the closing corner mkd:

Douglas Co. Surveyor T 22 S R
1976 11 S 12 S 6 CC 10
W S 7 W

We place the iron rod along the east side of the brass cap.
Note: This cor. is located approx. 20 ft. west of a ridge top running N.20°W. and S.20°E.

10/25/76

148

Closing Corner for Sec. 18, and Sec. 7, ~~T22-12~~.
Found - Orig. BT's of latest Government Survey. See Also Ren. #8
A 60" Fir (now a stump) bears N.31°30'E., 31.7 ft.
A 72" Fir (now a stump) bears S.65°00', 38.9 ft.

Note: I will set a brass cap at this corner after logging is finished. M 65-4 C.S. 58/139

2/24/77

149

West 1/4 Corner for Sec. 18 only.
Set - 3/4" x 36" Galv. I.P. with brass cap.
BT's - 24" Hemlock, S.28°0'W., 36.8 ft.
10" Fir, S.58°0'E., 44.0 ft.

R. B. Ward Jr.
(as above)

150

1/4 Corner for Secs. 15 and 16.
Set - From the possible orig. 8" alder BT (now 20") which bears N.48°E., 14.5 ft.; axe/marks but no scribe, I SET a 3/4" I.P. from which
32" Cedar bears N.20°E., 6.44 ft. mkd. 1/4 S15 BT.

Richard J. Hintz
For: James Peck
March 9, 1977
C.S. 58/140

3/9/77

L. E. Monrean
K. Cheney
Oct. 25, 1976
C.S. 59/24

Douglas County Surveyor's Office

Gary L. Langlitz
P. Earle
Oct. 25, 1976
C.S. 59/24

Robert B. Ward Jr.
For: Champion
International Corp.
Feb. 24, 1977