

Douglas County Surveyor's Record of
Government Corners Renewed

T 22 T. S. R 11 R.W.W.M.

FOKE-CHAPMAN CO., EUGENE, ORE. 21991

150

Section Corner Common to Secs. 11, 12, 13, and 14.

Found - Orig. 12" x 10" x 5" stone, (missing, X in place on bare rock, see below) from which:

8" Fir bears N.15°E., 36 lks.; now 22" stump in place, face closed.

12" Fir bears S.29°E., 100 lks. now 50" stump in place, faces closed, bearing S.39°E.

12" Alder bears S.80°W., 60 lks. missing, point falls in slid out draw.

24" Alder bears N.52°W., 73 lks.; missing, point falls in slide area.

Restoration by A. Gibson 1961, Ren. #43

X on bedrock for corner point (in place) from which a:

13" Cedar bears S.69 1/2°W., 32.0 ft. now 17" stump in place, scribes T22S R11W visible.

10" Cedar bears N.33 1/2°W., 42.9 ft. missing, point falls in slide out draw.

30' x 5' rock ledge bears S.45°E., 11.4 ft.; in place scribes BO X visible.

Restored:

Set 3" bronze cap mkd. "Oregon State Board of Forestry T22S R11W S11 S12 S14 S13 1977 RS359", 3 inches in ground, in concrete in bedrock, in place of X and from which a:

Orig. 50" Fir stump bears S.39°E., 66.0 ft. to face; scribed RS359. 2/10/77

151

1/4 Corner for Sec. 28 (west side)

Original:

3" x 3" x 36" Post 24" in ground (missing, found 1 1/2 I.P. and cap in place, see below) from which a:

10" Fir bears S.48°W., 87 lks; now 37" in place, face closed.

8" Fir bears S23°E., 57 lks.; now 33" in place, broke off at base scribes 1/4S visible on broken off portion of tree 1 ft. downhill.

Restoration by A. Gibson, 1966:

1 1/2" x 36" G.I.P. with 3" bronze cap in mound of rock (in place) from which a:

Creek 12" course NE, bears S.23°E., 78.0 ft. in place.

4" x 4" x 72" WPCP bears South 2.0 ft.; in place.

Rewitnessed:

From above 1 1/2" x 36" G.I.P. a:

27" Fir bears N.08°E., 11.3 ft. to face; scribed 1/4S28BTRS359. 2/10/77

152

1/4 Corner for Sections 5 and 6

Found - Original 30" Fir, now a stump, bears N.2°W., 76.6 ft. opened face plainly visible.

Original Maple bears N.15°E., 8 ft. No definite point to take a bearing and distance to.

Set - 1 1/4" Iron pipe with stamped brass cap.

1/4 Corner for Sections 5 and 8 Ren. #14

153

Found - 12" Maple, part of a cluster bears N.47°W., 21.9 ft. (See C.S. 42/256 and C.S. 42/386).

1/2" Iron pipe bears S.40°E., 2.83 ft. (See C.S. 42/256 and C.S. 42/386).

Set - 1 1/4" Iron pipe with stamped brass cap.

New BT- 50" Cedar bears S.7°E., 48.4 ft. scribed.

Note - Distance is taken to a 50d nail in the face of the bearing tree.

154

Sec. cor. to Sec's 3, & 4, and Sec's. 33 & 34 of T.21-11.

Found - 18" x 18" x 6" sandstone with "x" on top. Renewal #19 in T.21-11.

BT's - 34" D. Fir bears N.39°E., 14.3-ft. w/healed face. sameRen.#19

47" D. Fir bears S.82°W., 57.7-ft. w/healed face. sameRen.#19

(CONTINUED)

Arnold G. Gibson
For: State of Oregon - Department of Forestry
February 10, 1977
C.S. 58/31

Richard J. Hintz LS# 497
For: International Paper Co.
May 1980
M 83 - 57

Earnesto Alvarado, USFS
Deputy Douglas Cou.
Surveyors Office
Carol Dickison and
Colin Long
Oct. 2, 1981
C.S. 61/29