

Douglas County Surveyor's Record of
Government Corners Renewed

T. 22 S. T. S. R. 11 W. R. W. W. M.

HOKE-CHAPMAN CO., EUGENE, ORE. 21881

154

(Continued)

BT's -

Earnesto Alvarado, USFS
Deputy Douglas Cou.
Surveyors Office
Carol Dickison and
Colin Long, wit.
Oct. 2, 1981
C.S. 61 / 29

S.E. Cherry BT is uprooted w/part of scribing visible. Ren. #19.
43" D. Fir bears N.21°W., 20.5-ft. Face was shopped out app.
48 years ago. All heartwood is rotten (powder). No scribing
found. Traces of axe marks found. Tree has dead top. (Cut
out, found the upper bevel part of blaze).
Set - 2 1/2" B. C. on 1" I.P. 30" long w/flanged bottom, stamped
Douglas County Surveyor's Office T21S R11W S33 S34 T22S
R11W S4 S3 1981.
New BT's - 6" D. Fir bears S.46°E., 25.2-ft. "x" scribed at breast height
lower blaze scribed CSBT.
Location - Go East along Hwy. #38 approx. 4.6-mi. from Reedsport to Alder
wood Farm. Walk West on road So. side of creek (So. edge
of pasture) approx. 600-ft. to location poster on Alder
on South side of road. From poster, go S.10°W., 500-ft.
to corner.

10/2/81

155

Closing township corner common to Secs. 31; and 36 of T.22-12
Found - 24" x 12" x 6" stone, lying face down, notches on north face
badly eroded.
Three orig. trees described by Gibson in 1958 now missing.
Mound of stones by Gibson now scattered. Ren. #21
25" fir, now 28" x 4 ft. high stub in place, badly decayed scribes
22S R11W S31 visible, bears N.17°E., 19.4 ft.
29" fir now 32" windfall 5 ft. downhill, face closed (Rec. N.30°W
103.6 ft.)
31" fir now 31" windfall, face closed. (Rec. S.20°E., 25.8 ft.)
Set - 1 1/2" x 36" alum. pipe with 3 3/4" alum. cap marked "STATE OF
OREGON DEPARTMENT OF FORESTRY T22S R11W R12W CC S36 S31 T23S
R12W S1 1982 LS1101" 34 inches in ground, placed original 24" x
12" x 6" stone alongside, and from which:
New BTs - 25" cedar bears N.13°W., 36.8 ft. to face; scribed T22S R12W S36
CC BT.
9" cherry bears N.80°E., 59.7 ft. to face; scribed T22S R11W S31
CC BT.
Set - 4" x 4" x 72" white painted cedar post S.49°W., 2.4 ft. from
corner pipe. Oregon State Forestry Department metal location
poster on 25" cedar N.13°W., 36.8 ft.

Lloyd D. Smith
L.S. #1101
For: Oregon Dept. of
Forestry
Witnessed by Anthony
J. Koreiva
December 22, 1982
C.S. 58/164

12/22/82

156

1/4 Corner for Section 3; and Sec. 34 of T.21-11.
Found - 1 1/2" iron pipe. (no record).
Orig. BT, a 62" spruce bears S.30°E., 50.1 ft. (S.31 1/2°E.,
47.5 ft. record) healed face.
Hootman BT a 26" forked spruce bears N.70°E., 16.3 ft. (Rec.
N.70°W., 14.5 ft. healed face. Ren. #60
Set - 3" alum. cap on 2 1/2" x 30" alum. pipe. Cap stamped per BLM
manual and with PLS 1305. Rock mound.

James W. Prochnau
PLS #1305
For: U.S. Forest Serv.
Feb. 1984
M 96 - 65 A-B
C.S. 58/294

157

Center 1/4 Corner for Section 3
Set - A 5/8" x 30" iron rod with a plastic survey cap mkd. "Baughman
Tech. Serv."
From which:
A 12" spruce bears N. 29° E., 18.3 ft. scribed "C 1/4 S3 BT" with
a brass washer "LS 1941" nailed in lower blaze.
A 6" spruce bears S. 12 1/2° E., 12.8 ft. scribed "C 1/4 S3 BT"
with a brass washer "LS 1941" nailed in lower blaze.
A 1" iron pipe bears S. 57° 48' 43" E., 22.46 ft. as set by
Hootman for the C 1/4 in 1972. (M 45-5) See Ren. #118

Kristian DeGroot
L.S. #1941
Baughman Tech. Co.
For: Dr. Clinton
Faber
May 1985
M 98 - 57 A&B

5/85