

Douglas County Surveyor's Record of
Government Corners Renewed

22 T. S. 11 R. W. W. M.

ROKE-CHAPMAN CO., EUGENE, ORE. 21881

James W. Prochnau
PLS #1305
For: U.S. Forest Service
August 1985
M 99 - 21 A & B

Section Corner for secs. 1 and Sec. 6 (T22-10) ONLY. 158
Found - Original stone, 6" x 12" x 22" in upright position. Buried stone.
BT's - Possible remains of original cedar BT, now a windfall out of position.
Set - A U.S. Forest Service 3 1/4" aluminum cap with magnet on a 2 1/2" x 30" aluminum flared pipe. Mkd. PLS #1305. Also set rock-mound.
New BT's - 7" R. Cedar, bears S.14°W., 24.8 ft., scribed T22S R11W S1 BT.
11" R. Alder, bears S.22°E., 41.2 ft., scribed T22S R10W S6 BT.

Witness Corner for Meander Corner, Sec. 1, R.11 and Sec. 6, R. 10. 159
Set - 3 1/4" USFS alum. cap with magnet on a 2 1/2" x 30" alum. pipe with flared base. Cap properly marked and with PLS #1305. Cap and pipe bears N.0°39'52"E., 23.26 ft. on line from true position.
New BTs - 34" D. fir bears S.21°E., 10.5 ft., scribed "X" BT.
10" maple bears N.16°W., 7.8 ft. scribed "X" BT.

7/15/85

160

Lloyd D. Smith
For: State of Oregon
Department of Forestry
December 30, 1986
M 103 - 42

True township corner for Section 31; and Sec. 36 of T.22-12
Set - Oregon State Dept. of Forestry 1 1/4" x 36" alum. pipe with 3 3/4" alum. cap and magnetic insert, 34" in ground.
New BTs - 31" fir, N.08°W., 79.2 ft. scribed T22S R12W S36 CC BT with bearing tree tag.
27" cedar, N.25°W., 17.3 ft. to nail in base of face (OSDF 1982 Northwest BT) and bearing tree tag.
Oreg State Dept. of Forestry pipe and cap, S.0°10'02"W., 20.97 ft. stamped AM. See Ren. #155
4"x4"x72" white painted cedar post, N.69°E., 1.2 ft.
Original closing corner bears S.0°10'02"W., 20.97 ft.

12/86

161

Lloyd D. Smith
For: Oregon Dept. of Forestry
Aug. 1989
M 108 - 58

1/4 Corner for Sections 17 and 18
Found - 1972 OSBF pipe with cap. Ren. #129
66" Fir, N.38°E., 104.5 ft. (now 60" x 2 ft. high rotted stump in place, face closed, RR spike in top center of stump, YMLP)
4 ft. x 6 ft. high sandstone face S.38°W., 17.7 ft. to 9" (XBO) (in place)
REWITNESSED:
Orange carsonite boundary marker, CBM-250R, S.50°E., 4.7 ft. to base.
Orange carsonite boundary marker, CBM-250R, N.32°W., 2.7 ft. to base.
White painted cedar post, N.69°E., 3.1 ft.

162

Douglas County
Surveyors Office
Randall Smith
Stephen Flause
Jan. 23, 1990
C.S. 64/5

East 1/4 Corner for Section 1 of T.22-12
Found - 1971 County brass cap on a 1 1/4" O.D. iron pipe, protrudes 15" above ground. Ren. No. 105
18" now 20" dia. 4 ft. high hemlock stump, with a rotted partially healed blaze scribing visible "1/4S" bears N.40°E., 11.3 ft. (agrees with record Ren. No. 105)
5" now 7" dia. 7 ft. high hemlock stump, with a partially healed double blaze, scribing visible "1/4 S1 CS BT" bears N.40°W., 48.3 ft. (Rec. N.40°W., 49.2 ft. dist. is a slope measurement) Ren. No. 105
New BTs - 11" dia. alder bark scribed "1/4 S1 CS BT" 4 ft. above ground, bears N.34°W., 23.3 ft.
8" dia. spruce double blazed and scribed "1/4 S1 CS BT" bears N.5 1/2°W., 37.8 ft.
18" dia. alder double blazed and scribed "1/4 S1 CS BT" bears S.20 1/2°W., 44.8 ft.
8" dia. hemlock double blazed and scribed "1/4 S1 CS BT" bears S.28 1/2°W., 59.3 ft.

Corner lies on a steep northeast slope, approx. 250 ft. south of state hwy. 38, and 45 ft. easterly of a power line easement clearing.

1/23/90