

Douglas County Surveyor's Record of
Government Corners Renewed

T 22 T. S. R 11 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

163

Ref. Mon. #1, on Range Line Sec. 6, and Sec. 1, T.22-12
Monument gone; apparently dug out. Ren. #104
Found - A 3" "+" marked in high rock bluff approx. 4 ft. above
ground, bears S.55°E., 17.9 ft. Ren. No. 104
(5/8" I.R. and SW "cross" from Ren. No. 104 NOT FOUND.)
Set - A 2 3/8" dia. DCSO brass cap on a 1 3/8" O.D. x 32" long I.P.
at a point N.55°W., 17.9 ft. from previously described "+"
in rock bluff. BC/IP protrudes 14" above ground is
surrounded by a 2 1/2" ft. dia. mound of sand stone. Cap stamped
DOUGLAS COUNTY SURVEYORS T22S RM 1 R12W S1 S6 R11W
RESET 1990.

New Accessories:

5/8" x 30" long I.R. with DCSO alum. cap stamped "BO 1"
protrudes 3" above ground under east guard rail bears
N.24 1/2°E., 51.4 ft.
A 5" "+" marked in high rock bluff approx 4 1/2 ft. above ground
bears S.72°W., 10.0 ft.
DCSO drill cap stamped "T22S RM2 R12W S1 S6 R11W 1990" bears
N.68 1/2°W., 111.7 ft. RM 2 drill cap set 6" below ground in
sandstone. Two boat spikes are set over drill cap for future
magnetic detection.

Note: Following new accessories are for RM #2 only:

A found 6" "+" on high rock bluff approx 5 ft. above drill cap
bears S.84°W., 11.4 ft.
Marked a 6" "+" on high rock bluff approx 5 ft. above drill
cap, bears S.10°E., 11.4 ft.
A DCSO BC/IP marked "T22S RM1 R12W R11W S1 S6 RESET 1990" bears
S.68 1/2°E., 111.7 ft.

Douglas County
Surveyors Office
Jan. 18, 1990
Randall Smith
Steven Flause
C.S. 64/5

164

Section corner for sections 18 & 19 only.

Found - Ore.State Bd. of Forestry 3" bronze cap dated 1960 on 1 1/2" X 36"
galv. I.P. and stone on North edge.
BTs - 12" fir (orig.) N.60°W., 24 lks.--now 47" X 10' high stump, face
partially closed and burnt, some scribes visible, in place
U.S. Plywood tag. See renewal # 23
50" fir (orig.) N.60°W., 15.8 ft.-- now N.46°W., 14.3 ft., 47" X 10'
high stump, face partially closed and burnt, U.S. plywood tag.
12" hemlock, 1910, N.72°E., 7 lks,-- now uprooted stump,
axe work visible.
23" fir, 1960, S.9°E., 11.5 ft.-- now 31" face closed in place,
U.S. Plywood tag.
31" fir, 1960, N.88°W., 10.5 ft.-- now 36" X 3' high stump
face closed, in place, U.S, Plywood tag.
New BTs- 5" fir N.64°E., 14.9 ft. scribed "T22SR11W S18 BT" & bearing tree tag
New Accessories
Orange carsonite marker N.33°E., 6.3 ft. to base.
Orange carsonite marker S.70°E., 4.9 ft. to base.
White painted 4 X 4 cedar post S.85°W., 2.2 ft.

6/91

E 1/4 corner for section 24 only, T.22-12W

165

Found - Oregon State Board of Forestry 3" bronze cap on 1 1/2" X 36" I.P.
BTs - 23" burnt fir stump S.79 1/2°W., 99.22 ft.--scribes visible in place.
37" hemlock stump N.8°W., 98.1 ft. -- now 33" badly decayed,
scribes found on slabs at base of stump, in place.
White painted 4 X 4 cedar post, in place. See renewal # 112

New Accessories:

16" fir N.19°W., 26.8 ft. scribed "1/4 S24 BT" & bearing tree tag
9" fir S.82°W., 13.7 ft. scribed "1/4 S24 BT" & bearing tree tag
Orange carsonite marker N.31°W., 5.8 ft. to base. 6/91

W 1/4 Corner for section 19 only.

166

Set - Oregon State Board of Forestry 3" bronze cap on 1 1/2" X 36" galv.
I.P. 34" in ground.
BTs - 73" fir N.9°E., 76.6 ft. bark scribed "1/4 S19 BT" & brng. tree tag
75" hemlock N.28°E., 49.2 ft scribed "1/4 S19 BT" & brng. tree tag
45" fir N 38°E., 67.7 ft scribed "1/4 S19 BT" & brng. tree tag
65" fir South 77.0 ft scribed "1/4 S19 BT" & brng. tree tag.
White painted 4 X 4 cedar post S 79°E, 1.5 ft.

6/91

Lloyd D Smith L.S. 1101
For: State of Oregon Dept of Forestry
May 1, 1991
M 112 - 29