

Douglas County Surveyor's Record of
Government Corners Renewed

T 22 T. S. R 11 R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

Douglas County
Surveyors Office
Randall Smith, Deputy
Stephen Flause
Feb. 22, 1993
C.S. File 64/39

Closing Corner for Secs. 30 and 31 only of T.22-10

Found - Original stone, 36" x 20" x 10", laying on side with marks
CC on top, 5 notches on North edge and + on East edge.
6" now 29" dia. 7 ft. high burnt D.Fir stump, with a fully
healed blaze, bears S.65°E., 13.2 ft. (orig. BT)
8" now 25" dia. 4 ft. high burnt D.Fir stump with a fully healed
single blaze, bears N.63°E., 40.8 ft. (Rec. Ren. No. 119
N.63°E., 40.0 ft.) Orig. BT.
29" dia. 3 ft. high burnt D.Fir stump with a fully healed blaze
bears S.80°W., 10.0 ft. (Rec. S.75°W., 10.0 ft. ren. No.119)
20" dia. 2 ft. high burnt D.Fir stump with evidence of a
healed lower blaze, bears S.33½°E., 43.7 ft. (Rec.
S.33½°E., 44.9 ft. possible slope dist. to blaze) Ren.119
No white cedar post from Ren. No. 65 found.

Set - A 2 3/8" dia. brass cap on a 1 3/8" x 32" long Iron Pipe is
set at a position determined from bearing trees. BC/IP
protrudes 4" above ground. Cap marked:

DOUGLAS COUNTY SURVEYORS

		T 22 S	
R	S 25	S 30	R
1		S 31	1
1		1993	0
W		Office	W

Original stone is placed along southerly edge of BC/IP on top of ground.
2/22/93

Corner for Sections 1 & 12 only.

Found - 1/2" dia. iron rod protruding 2 1/2 ft. above ground. Source
unknown, possibly set in area of corner from a recent
survey. Note- I.R. is loosely set. DCSO BC/IP not found.

Accessories Found - See renewal # 99.

10" now 18" dia. D.Fir with a fully healed double blaze,
bears N.77½°E., 21.6 ft. (rec. N.77½°E., 24.0 ft. dist.
could be a slope measurement)
14" now 23" dia. D.Fir with a fully healed double blaze,
bears S.40°W., 60.2 ft.
10" now 12" dia. Maple with a fully healed single blaze,
bears N.86½°W., 41.5 ft. (rec. west, 41.5 ft., bearing to
Maple is difficult to see)

Monument Set -

At a position determined from bearing trees that were
scribed for M42-27. Set a 2 3/8" dia. Brass Cap on a 1
3/8" O.D. by 32" long iron pipe, protrudes 6" above
ground and is marked -

DOUGLAS COUNTY SURVEYORS

		T 22 S	
R	S 1	S 6	R
1		S 12	1
2			1
W			W
		1993	
		OFFICE	

1/2" I.R. bears N.52½°W., 2.1 ft. from BC/IP.
BC/IP is surrounded by an 18" dia. mound of sandstone.

New Accessories -

17" Alder bark scribed "T22S R12W S12 CS BT" bears S.8°W.,
37.5 ft.

Note - Corner lies in bottom of a ravine running north - south.

Douglas County Surveyors Office
Randall W. Smith, Stephen J. Flause
Oct. 13, 1993
C.S. File 64/47