

Douglas County Surveyor's Record of
Government Corners Renewed

22 T. S. 12 R. W. W. M.

Nov. 9, 1936
Arthur Poyer D.C.
W.E. Richardson
Chas. Clark
Witnesses

Nov. 10, 1936
Arthur Poyer Dep C.S.
W.E. Richardson
Chas. Clark
Witnesses

James W. Byron, Deputy Co. Surveyor.
Ray Irving, A. West,
F. C. Cox, John Fee.
March 3, 1955.
C. S. S. File 46/110.

James W. Byron, Deputy County Surveyor
Survey for Warren Waggoner
Aug. 9, 1956
C. S. S. File No. 47/129.

RENEWED CORNER NO. 45
COR. BET. 6 & 7
Set from Unit. Pt. Winchester Bay Camasite, Set by Gene Robinson, and from stumps of spruce trees which check close, could find no signs of scribed blazes. Set 1 1/2" x 36" C. Iron pipe on W. side of draw from which
Orig. N.T. 40" stump bears N.30°E. 11.9' to 12" dia.,
Orig. E.T. stump 40" bears S.81°W. 4.6 ft, Marked
6" Alder which bears S.89°30'W. 8.1' 1/2 S. 6 C.S. P.T.
and a 48" Spruce stump which bears S.29°E., 9.2' marked 1/2 S. 7. C.S. N.T.

RENEWED CORNER NO. 47
MEANDER COR. BET. 6 & 7 (At Umpqua Riv. on Winchester Bay)
1124.6' N. of 1/2 Cor. Sec. 6, Cor. Bet. 6 & 7, Set 1 1/2" x 36" C.I. Pipe, from which A. 12" Spruce bears N.1.5' Marked C.S.P.T. and at point 1140.0' W. of 1/2 Cor. bet. 6/7. Large cross is on S.S. Rock Bluff. Note, the pipe is on top of bluff and cross is on side of bluff to the West. -SEE FOUND CORNER M 33-24-

MEANDER COR. ON N. & S. MID. SEC. LINE SEC. 6 and in Cove or inlet of Umpqua River on W. Side of Cove at edge of Rock Bluff at bot. of Bluff set 1 1/2" x 36" Galv. Iron Pipe driven 24" d down to bedrock and on rock bluff cut cross: No trees. Pipe is 1632 ft. N. of 1/2 Cor. bet. 6 and 7.

N.W. COR.

Section corner to secs. 30, and 31, T22S, R12W., and secs. 25 and 36; T22S, R13W
Found 1 1/2 inch Axle 1 foot above ground. A 12 inch Pine bears S.71°E., 15.7 feet, knife scribed 31 BT; A 12 inch Pine bears S.68°W., 33.8 feet, knife scribed 30 BT; Bottom of old Pine stump, S.5°E., 37.6 feet and bottom of old Pine stump, N.28°E., 5.9 feet. (Both trees check for original B.Ts.)

Blazed and scribed four new B. T.s:
6 inch Pine, N.12°W., 15.5 feet, R13W., S 25 CS BT.
6 inch Pine, S.47°W., 47.4 feet, R13W., S 36 CS BT.
7 inch Pine, S.82°E., 26.3 feet, R12W., S 31 CS BT.
7 inch Pine, N.37°E., 23.6 feet, R12W., S 30 CS BT.
FEB. 1971 - B. KISCHEL FOUND AXLE & 2 BT'S. AXLE LOST IN SAND
F.D. OK 2/12/75 L.E.M. C.S. 59/46

1/4 section corner to section 31, T22S, R12W., and section 36, T22S, R13W.
Found 1/2 inch X 10 foot iron pipe at 3 inch X 3 inch sq. post, scribed 1/4 corner on North face, 31 on East face, 36 on West face and D.L. on South face.
RD 7976 L.E.M. C.S. 60/12 NO ORIG. EVIDENCE FD.

1/4 sec. corner to sec. 3, T22S, R12W., and sec. 34, T21S, R12W.
Position of corner established from tie shown on amended plat of R. R. Addition and monument at 10th and Winchester used for control. Corner falls in street so no monument set. Bearing objects are chiseled "4" in concrete on East abutment of bridge, and bear S.35°16'W., 191.1 feet; S.55°28'W., 159.0 feet. Northwest corner of Texaco Service Station bears N.59°22'E., 236.3 feet. Note - Co. Surveyor's Brass Cap Set in 1956 - Recorded Nov. 1967.

Section corner to secs. 2 & 3, T22S, R12W., and secs. 34 & 35, T21S, R12W.
Position of corner determined by tie (N.15°W., 253.3 feet) shown on amended plat of R. R. Addition and ties made on Winchester Ave. Set an iron pipe with brass cap at corner point mkd. 3 1/2 T21S R12W., 3 1/2 T22S
County Surveyor's Office, 1956.
Blazed and scribed:
1 1/2 inch Cedar, N.20°28'30"E., 283.83 feet mkd. S 35, T21S, R12W., CS B. T.

1/4 sec. corner to secs. 2 and 3.
Found 24 inch rotted Fir stump - original B. T., 18 inch Fir, S.12°E., 13.2 feet scribed B. T.
Set and iron pipe with brass cap marked T 22 S, R 12 W., 1/4 S 3/2 County Surveyor's Office, 1956.
From which:
10 inch Hemlock bears S.48°E., 10.6 feet, scribed 1/4 S 2 C S BT.
8 inch Hemlock bears N.9°W., 19.6 feet, scribed 1/4 S 3 C S BT.