

Douglas County Surveyor's Record of  
Government Corners Renewed

22 T. S. 12 R. W. W. M.

9

Section corner to secs. 3, 4, 9 and 10.  
Found original 12 inch, Now 30 inch, Cedar, N.12°W., record bearing and dist. alive but partly rotted. We open and find scribe marks.  
Found also original 18 inch, now 30 inch, spruce, N.85°E., 29 feet. Tree in good condition and we do not open - shows good blaze.  
Both orig. BTs check for bearing and distance.  
Set an iron pipe with brass cap at corner point mkd.  $\frac{4}{3}$ / $\frac{9}{10}$  T22S, R12W., County Surveyor's Office, 1956.  
Blazed and scribed:  
10 inch Hemlock, N.40°W., 19.6 feet mkd. T22S, R12W., S 4 CS BT.  
12 inch Hemlock, S.71°W., 25.0 feet mkd. T22S, R12W., S 9 CS BT.  
12 inch Cedar, N.12°W., mkd. S 4, CS. BT. (original BT)  
No trees in SE Quad.

Fd. by SHANER  
SEE R.M. 3-59  
JUNE, 1982  
9/93  
M117-64

James W. Byron, Deputy County Surveyor  
Survey for Warren Waggoner  
Aug. 9, 1956  
C. S. File No. 47/129.

10

$\frac{1}{4}$  sec. corner to secs. 3 and 10.  
Corner could not be found after thorough search.  
Position of corner established on true line at mid point between section cors.  
Set an iron pipe with brass cap mkd.  $\frac{1}{4}$  S 3/10, T22S, R12W., County Surveyor's office, 1956.  
Blazed and scribed:  
5 foot spruce, S.66°E., 13.71 feet, mkd.  $\frac{1}{4}$  S 10 CS BT.  
20 inch cedar, S.16°E., 19.24 feet, mkd.  $\frac{1}{4}$  S 10 CS BT.

Fd. OK by SHANER  
JUNE, 1982  
SEE R.M. 3-59

11

Section corner to secs. 2, 3, 10 and 11.  
Position of corner determined from original BTs. in fair condition. No other trees near so did not scribe new BTs.  
Set an iron pipe with brass cap at corner point mkd.  $\frac{3}{12}$ / $\frac{11}{11}$  T 22 S, R 12 W,  
County Surveyor's Office, 1956.

12

Center  $\frac{1}{4}$  corner to section 3.  
Position of corner established by intersection of N - S and E - W centerlines.  
Set an iron pipe with brass cap at corner point mkd. Center  $\frac{1}{4}$  corner S. 3, T22S, R12W., County Surveyor's Office, 1956.  
Blazed and scribed:  
12 inch spruce, S.12°W., 29.5 feet mkd. C  $\frac{1}{4}$  S. 3 C. S. BT.  
18 inch Cedar, S.75°E., 36.91 feet mkd. C  $\frac{1}{4}$  S. 3 C. S. BT.

13

$\frac{1}{4}$  Section Corner common to Sections 11 and 14. (N 3° E, 31.0')  
I find the stump of the original bearing tree for Section 11. Part of the scribing is still visible. The stump in Section 14 is gone and its position is in a cat road.  
I set a 1" X 36" galvanized iron pipe at the call distance from the original bearing tree stump and marked two new bearing trees as follows:  
D. Fir 10 inch DBH, bears S.36° 30'W. a distance of 107.5 feet.  
Hemlock 4 inch DBH, bears N.78° 30'E. a distance of 40.2 feet.  
Sept. 10, 1957

Warren D. Hootman  
For Cape Arago Lmbr.  
Sept. 10, 1957  
C. S. File No. 42/309

14

$\frac{1}{4}$  Section Corner to Sections 11 & 12.  
Found - 1 1/2" Iron Pipe at Corner & Both Orig. BT's.:  
Orig. 15", now 32" Hemlock Stump East 47.5 ft., shows good scribing "1/2 S".  
Orig. 24", now 36" Hemlock Stump S.38°W. 31.7 ft., shows good scar. I do not open.  
Note - Bearings check record but distances measured on slope.  
Set Brass Cap alongside Iron Pipe Mkd: County Surveyor's Office, 1959.  
 $\frac{1}{4}$  S11/S12 T22S R12W  
Note - Corner in bottom of North South Draw.  
New BT: 12" Hemlock bears S.85°E. 34.5 ft. scribed  $\frac{1}{4}$  S12 CS BT.  
No trees near to West.

Fd. OK  
A. PALOS  
M 87-93  
MAY 1982

James W. Byron, Deputy  
S. A. Bilow  
June 3, 1959  
C. S. File 49/153

15

$\frac{1}{4}$  Section Corner to Sections 10 & 11.  
Found - Orig. 60", now 60" Fir Stump S.85°W. 16.5 ft., previously opened, shows good scribing, "4S". I find No trace of Original N.E. BT.  
Set Brass Cap at Corner Mkd: County Surveyor's Office, 1959  
 $\frac{1}{4}$  S10/S11 T22S R12W CS BT.  
(continued next page)

Fd. OK by SHANER  
JUNE, 1982  
SEE R.M. 3-59

B. BELT  
M 97-63  
10/84