

Douglas County Surveyor's Record of
Government Corners Renewed

22 T. S. 12 R. W. W. M.

ROSE-CHAPMAN CO., EUGENE, ORE., 21881

Center of Section 28.

I Set a 1" Pipe from which:

- Alder 14" DBH bears N.18°00'W. 3.3 feet.
- Alder 15" DBH bears S.22°30'E. 6.2 feet.

24

(See Over)
Warren D.
Hootman
CS. File
No. 51/61

Closing Corner for Sections 25 and 36.

Set a 4" Post and marked trees as follows:

- Maple 23" DBH, bears N.53°E. 20.7 feet.
- Chittum 12" " bears S.75°W. 10.2 feet.
- Myrtle 28" DBH, bears N. 47°W. 31.1 feet.

25

Warren D. Hootman
For Cape Arago Lumber Co,
Empire, Oregon
Nov. 20, 1959
C. S. File No. 51/62

1/4 Corner for Section 25.

Set on the true line at the proportioned distance between the closing corner for Sections 30 and 31, T.22S., R.11W., and the closing corner for Sections 25 and 36, T.22S., R.12W., as follows:

Set a 3/4" X 36" Iron Rod for 1/4 Corner and mark new trees as follows:

- Cedar 20" DBH, bears S. 73° 30'W. 17.7 feet.
- Cedar 20" DBH, bears N. 47° 30'W. 29.3 feet.

26

Section Corner to Sections 1, 2, 11 and 12.

Found - Both Orig. Fir BT's., down. Found scribe on both trees. Set a 1" x 1" x 36" T. Iron for corner

S 2 | S 1
S11 | S12 T22S R12W

Scribed: 22" Hemlock N.25°W. 20.7 ft. S-2 T22S R12W BT.

10" Hemlock S.64°E. 14.3 ft. S-12T22S R12W BT.

Scribed B.T. on a 24" R. Cedar S.52°W. 14.5 ft., this tree may be Orig. S. W. Tree.

27

F.B. H-249

Wilford N. Haines
August 1960
C. S. File No. 51/109

Witness Corner East Line of Sec. 12, T22-12W.

Found - 30" Tree marked for Angle Wit. Point on the East Line of Section 12 at 62.45 chs. This tree is now a Stump; it apparently was 24" when scrbd, now 32" inside the bark. There is an R on the Stump and the old scar goes down about 10-12".

I found an S 7 on a log that came off the stump.

I drove a 1" x 1" x 24" T. Iron about 12" in the center of the stump for A. W. P. Corner.

I drove a 1/2" x 16" bolt in center of a 43" fir Stump N.21°W 23.6 ft.

I drove a 1/2" x 5 1/4" Lag Screw in the center of a 54" Fir Stump N.72°W. 34.6 feet.

28

Section Corner common to Secs. 24 & 25(East Side).

Orig. - Post (now missing) from which a:

- 14" Chittem bears S.61°W. 14 lks.; now missing.
- 5" Hazel bears N.84°W. 5 lks.; now 5", down & rotted, no scribes.
- 20" Alder bears N.40°W. 22 lks.; now 24", exposed portion of T & other scribes, bears N.40°E.
- 30" Fir Line tree bears N. 6.16 chains, fd. in place.
- Ridge, course East, bears South 1.80 chains; in place.
- 14" Fir Line tree bears South 7.63 chains; fd. in place.

Restored: Set 1 1/2" x 36" Gal. Iron Pipe with 3" Br. Cap Mkd: "Ore. St. Board of Forestry T22S R11W R12W S19 S24 S25 1960 RS359",

30" in ground, and from which a:

- 45" Fir bears S.73°W. 15.3 ft.; scribed T22S R12W S25 BT RS359.
- 27" Cedar bears N.56°W. 47.6 ft.; scribed T22S R12W S24 BT.
- 24" Orig. Alder BT bears N.40°E. 14.5 ft.; scribed BT(above Orig. face

Ore. St. Bd. of Forestry metal location poster on 27" Cedar BT.

Set 4" x 4" x 72" white painted Cedar post 1.5 ft. SE of pipe.

29

Oregon State Board of Forestry
Arnold G. Gibson
Sit. E. Driver & Hollingsworth
Dec. 1960
C.S. 42/403