

Douglas County Surveyor's Record of
Government Corners Renewed

22

T. S.

12

R. W. W. M.

MOKE-CHAPMAN CO., EUGENE, ORE. 21881

Angle Point corner common to Sections 25 and 30, T22S, R11 & 12W. 30
(Whipple's 1893 East $\frac{1}{4}$ Corner 25)
Orig.-Stone 14 x 10 x 6 (now missing) from which a:
8" Cedar bears S.65°W. 25 lks.; now 22", exposed Orig. Scribe 4,
recent scribes BT $\frac{1}{4}$ S25 T22 R12W 399 outside.
6" Chittum bears S.22°E. 29 lks.; missing.
Ridge, course East, bears North 360 lks. in place.
10" Line tree bears North 375 lks. in place (restored as WP).
Note-Also found a 5/8" iron pin S.16°E. 3.5 ft. and a 22" Cedar N.49 $\frac{1}{2}$ °W.
25.4 ft. scribed BT $\frac{1}{4}$ S25 T22S R11.
Restored-Set 1 $\frac{1}{2}$ " x 36" gal. iron pipe with 3" Br. Cap Mkd: "Ore.St.Bd. of
Forestry AP S25 S30 1960 RS359", 35" in gr, in mound of
stone, and from which a:
30" Cedar bears N.26°W. 45.9 ft.; scribed AP S25 BT RS359.
Ore. St. Bd. of Forestry metal location poster on Orig. 8" Cedar BT.
Note - We erased the recent scribes " $\frac{1}{4}$ " on above trees S.65°W. & N.49 $\frac{1}{2}$ °W.

Line Tree common to Secs. 25 & 30, T22S, R11 & 12W. 31
Orig-10" Fir Line Tree at 36.27 chs. S. on E. boundary of Sec. 25
with 2 notches on N & S sides (now 20" in place, exposed
one notch on N side 67 years old).
Top of ridge, course East, at 36.40 chs.; in place.
Restored-Scribed line tree as Wit. Point, WP S30 on E. side,
WP S25 RS359 on W. side, from which a: FND OK 5/91
M 112-29
48" Fir bears N.62 $\frac{1}{2}$ °W. 52.0 ft.; scribed WP S30 BT.
43" Fir bears N.46 $\frac{1}{2}$ °E. 18.0 ft.; scribed WP S30 BT.
Ore. St. Bd. of Forestry metal location poster on 13" Hemlock N.72°W. 9.8 ft.

Witness Point - Line Tree common to Secs. 19 & 25, T22S, R11 & 12W. 32
Orig - 14" Fir line tree at 7.63 chains S. on the E. boundary of Sec. 25
with 2 notches on the N. & S. sides (now 28" in place, exposed
one notch on S. side 67 years old).
Ridge top at 6.90 chains S. on the E. boundary of Sec. 25
(now in CCC road) FND OK 5/91
NEW ACCESSORIES
SEE M 112-29
Restored-Scribed Line tree at Witness Point, WP S19 on E. side and WP S25
RS359 on W. side, from which a:
41" Fir bears N.88 $\frac{1}{2}$ °E. 56.8 ft.; scribed WP S19 BT.
36" Fir bears S.43°W. 12.4 ft.; scribed WP S25 BT.
Ore. St. Bd. of Forestry metal location poster on Orig. Fir Line Tree.
Also poster on 4" x 4" x 72" white painted Cedar post S.89 $\frac{1}{2}$ °E. 38.8 ft. on
East edge of CCC road.

Witness Point common to Section 19 and 24, T22S, R11 & 12W. 33
Orig-12" Line Tree at 57.89 chains S. on E. boundary Sec. 24, 2 notches
N. & S. sides (fd. uprooted, notches remaining, root hole in place)
from which a: Ridge, course E & W, bears S. 21 lks.; now in place.
Restored-Set 1 $\frac{1}{2}$ " x 36" gal. iron pipe with 3" br. cap mkd: "Ore.St.Bd. of
Forestry W P S24 S19 1960 RS359", 30" in gr. in mound of rock,
26" dbl. Fir bears S. 7°W. 15.2 ft.; scribed WP S24 BT RS359.
17" Fir bears S.56°E. 10.3 ft.; scribed WP S19 BT.
3' high by 6' wide rock face bears S.39°W. 2.7 ft.; scribed X. FND OK 5/91
NEW ACCESSORIES
SEE M 112-29
Ore. St. Bd. of Forestry metal location poster on 26" Fir BT.
Set 4x 4x 72" white painted Cedar post 1.0 ft. East of pipe.

Witness Point - Line Tree common to Secs. 19 & 24, T22S, R11 & 12W. 34
Orig-30" Fir Line Tree at 73.84 chains S. on the E. boundary of Sec. 24
with 2 notches on N. & S. sides (now 48", in place, exposed one
notch on S. side, 67 years old).
Restored-Scribed Line Tree at Witness Point, WP S19 on E. side & WP S24
RS359 on W. side, from which a:
60" Fir bears S.31 $\frac{1}{2}$ °W. 31.0 ft.; scribed WP S24 BT.
52" Fir bears N.66 $\frac{1}{2}$ °E. 39.4 ft.; scribed WP S19 BT. FND OK 5/91
NEW ACCESSORIES
SEE M 112-29

OREGON STATE BOARD OF FORESTRY

Arnold G. Gibson

Witnessed by Elbert Driver & J. Hollingworth

December 20, 1960 - Jan. 18, 1961

C. S. File No. 42/403.