

Douglas County Surveyor's Record of
Government Corners Renewed

T. 22 S. T. S. R. 12 W. R.W.W.M.

ROCK-CHAPMAN CO., EUGENE, ORE. 21881

James W. Byron, County Surveyor
John M. Powell & Crew
For: Douglas County Feb. thru June, 1971
C. S. File No. 56/5 Map M 42 - 27

FD #USED BY ASHD
(0-1) 6-87

Witness Corner to $\frac{1}{4}$ Cor. for Secs. 1 and 2. # 149
This corner set from survey & is 9.8 ft. S. of South Rail of RR Track,
364.99 ft. N. of $\frac{1}{4}$ corner.
Wit. Corner set on Section Line of Sections 2 and 1.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1971 T 22 S R 12 W
S 2 | S 1
1/4

Bearing Objects: $\frac{5}{8}$ " Iron Rod N.49°W. 33.0 ft. This rod 7.3 S. of south rail of RR Tracks.
 $\frac{5}{8}$ " Iron Rod N. 2° W.30.9 ft. This rod 9.2 ft. N. of north rail of RR Tracks.

Reference Monument on E-W Center Line for CW 1/16. 76
Point Set on Line, center Section Line.
Set - Brass Cap Mkd: County Surveyor's Office 1971 T 22 S R 12 W
C RM 4 C

Bearing Trees: 20" D.Fir N.30°W. 28.4 ft. scribed "RM 4 CC S1 CS BT".
27" D.Fir S.71°E. 4.5 ft. scribed "RM 4 CC S1 CS BT".

Witness Corner C. W. 1/16. 77
This corner set from survey & point lies at base of cut bank 17.0 ft. to north rail of RR Tracks. 619.08 ft. S. of E-W Center Line Sec. 1.
Set - Brass Cap for Cor. Mkd: County Surveyor's Office 1971 T 22 S R 12 W
W. C.
C W 1/16
S 1

Bearing Objects: $\frac{5}{8}$ " I.Rod S.3°W. 5.8 ft., 9.0 ft. to S. rail RR Tracks.
 $\frac{5}{8}$ " I.Rod S.21°E. 14.5 ft., 10.5' to N. Rail RR Tracks.
Bearing Tree: 8" Hemlock S.53°W. 53.5 ft. scribed "W.C. W 1/16 S1 CS BT".
6/11/71

Witness Corner for West 1/16th Corner Section 1 and 12. 78
Corner set from survey.
Set - Brass Cap for W.C. Mkd: County Surveyor's Office 1971 T 22 S R 12 W
W. C.
W 1/16
S 1

Bearing Trees: 34" Spruce S.22°W. 61.5 ft. scribed "W C W 1/16 S1 CS BT"
28" Spruce S.36°W. 57.6 ft. scribed "W C W 1/16 S 1 CS BT".
6/11/71

Reference Monument #1 on Range Line btwn. Sec. 1, T22-12 & Sec. 6, T22-11. 79
Set - Brass Cap at Cor. Mkd: Douglas County Surveyor's Office 1971 R T 22 S R
12 RM #1 11
W S 1 S 6 W #236

Bearing Objects: $\frac{5}{8}$ " I Red N. 1°E. 47.4 ft. Rod on N. edge of Highway.
3" Cross S.84°W. 11.4 ft., this cross about 4 ft. above ground on high rock bluff.
3" Cross S.55°E. 17.9 ft., this cross about 4 ft. above ground on high rock bluff.
6/10/71

EAST
 $\frac{1}{4}$ Corner for Sec. 1 only, T22-12W. FD OK FEB ST Hwy
MAP (0-1) 6-87 80
Corner Set from survey.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1971 R T 22 S R
12 W S 1 | 1/4 11W

New BL's: 5" Hemlock N.40°W. 49.2 ft. scribed " $\frac{1}{4}$ S1 CS BT".
18" Hemlock N.40°E. 11.3 ft. scribed " $\frac{1}{4}$ S CSBT".
7/9/71

$\frac{1}{4}$ Corner for Section 6 only, T22-11W 81
Corner set from survey & lies in bottom of Ravine, running N - S.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1971 R T 22 S R
12 W 1/4 | S 6 11 W

Bearing Tree: 80" Cedar S. 80° W. 63.4 ft. scribed " $\frac{1}{4}$ S6 CS BT".
No other trees available.