

Douglas County Surveyor's Record of
Government Corners Renewed

T 22 T. S. R 12 R.W.W.M.

KORE-CHAPMAN CO., EUGENE, ORE. 21881

115

Section Corner common to Sections 25 and 36 (west end).
Found - Orig. Fir Post (Found in place, badly decayed with one notch on South side) from which a:
14" Fir bears S.28°E., 28 lks.; now 27" in place, scribe S exposed.
9" Alder bears N.77°E., 9 lks.; missing. #169
Set - 1 1/2" x 36" gal. I. P. with 3" Bronze cap mkd. "Oregon State Board of Forestry S35 T22S S25 S36 R12W 1974 RS359", 34 inches in ground, and from which a:
29" Fir bears N.53°E., 98.4 ft. to face; scribed T22S R12W S25 BT RS359.
Set - 4"x4"x72" White painted Cedar post 4.3 ft. N.7°W., of corner pipe. OSFD metal location poster on 40" Fir N.9°W., 11.7 ft.
6/17/74

Angle Point for Corner Section 25 only. (Orig. East 1/4 25). 116
Found - 14"x10"x6" Stone (missing) from which a:
8" Cedar bears S.65°W., 25 lks. now 19" in place, face buried by side cast debris from road construction, excavated 7.0 ft. to face, scribes BT exposed.
6" Chittum bears S.22°E., 29 lks.; missing
10" Linetree bears North 373 lks.; in place.
Ridge, course East, bears North 360 lks.; in place.
REstoration by A.G. Gibson, 1961. Ren. # 30
1 1/2"x36" Gal. I.P. with 3" bronze cap (missing covered by road construction) from which a:
30" Cedar bears N.26°W., 45.9 ft.; now 22" in place, face now buried by sidecast debris, and inaccessible.
22" Cedar bears N.49 1/2°W., 25.4 ft.; now 18" in place. face buried by sidecast debris, and inaccessible.
Set - 1 1/2"x36" gal. I.P. with 3" bronze cap mkd. "Oregon State Board of Forestry T22S S25 R12W AP 1974 RS359"
35" in ground, in fill section of road, and from which:
19" Cedar (orig. 8") bears S.65°W., 16.5 ft. to face; scribed RS359 (7.0 ft. above old face).
22" Cedar Bears N.26°W., 46.5 ft. to face; scribed APS 25 BT (at new ground level.)
Set - 4"x4"x72" WPCP 8.0 ft. S.47°E., of corner pipe. OSFD metal location poster on 22" Cedar BT N.26°W., 46.5 ft.
6/18/74

Angle Point corner for Section 25 only. (Whipples 1893 Cor. 25 and 36). 117
Found - Orig. 20"x10"x5" Sandstone (found in place, outer surface decomposed, P remaining) from which a:
8" Maple bears S.48°W., 41 lks. now 19" in place, exposed scribe T.
10" Maple bears N.43°W 29 lks. now 18" in place face rotted out.
14" Alder bears S.26°W., 20 lks. missing.
Hootman's Closing Cor. 25 and 36 bears South 104 lks.; in place.
Set - Remarked orig. 20"x10"x5" Sandstone with AP, from which a:
27" Myrtle bears S.83°W., 52.3 ft. to face; scribed APS 25 BT RS359.
37" Fir bears N.8°W., 79.3 ft. to face; scribed APS 25 BT
Set - 4"x4"x72" WPCP 5.7 ft. N.12°W., of cornerstone. OSFD metal location poster on Orig. 19" Maple BT S.48°W., 27.1 ft.
6/18/74

O V E R

Oregon State Board of Forestry
Arnold G. Gibson
Restored by William E. Metcalf
Present and Witnessed by A.J. Klostermand and J.L. Shumway
June, 1974
C. S. 57/4