

Douglas County Surveyor's Record of
Government Corners Renewed

T 22 T. S. R 12 R. W. W. M.

ROKE-CHAPMAN CO., EUGENE, ORE. 21821

129

Closing Corner for Sec. 7, and Sec. 18 of T22-11.

Found - Orig. BT's of latest Government Survey. See also Ren. #8, T22-11.

A 60" Fir (now a stump) bears N.31°30'E., 31.7 ft.

A 72" Fir (now a stump) bears S.65°00'E., 38.9 ft.

Note: I will set a brass cap at this corner after logging is finished.

Robert B. Ward Jr.
For:

Champion Internat'l
Corporation
Feb. 24, 1977
M 65 - 4 C.S.58/139

2/24/77

130

Section Corner for Secs. 13 and 12 only. East Boundary

Set - 3/4" x 36" Galv. I.P. with brass cap.

BT's - 12" Alder, S.51°30'E., 35.1 ft.

12" Alder, S.53°30'W., 21.5 ft.

10" Alder, N.51°30'W., 38.9 ft.

R. B. Ward, Jr.
(as above)

131

Section Corner for Secs. 29, 28, 32 and 33.

Set - A brass cap mkd. S29, S28, S32, S33, T.22S., R.12W. 1977.

From which:

46" Fir stump orig. BT, old bark face bears S.32°E., 11.2 ft.

50" Fir stump orig. BT partial scribes on old bark face bears

S.34 1/2°W., 22.0 ft.

Other orig. BT's missing.

Old 1" Iron pipe alongside brass cap

18" Hemlock blowdown, scribes visible bears S.15°W., 3.8 ft.

8" Hemlock stump, scribes visible bears S.79°E., 10.4 ft.

24" D. Fir with face bears N.75°E., 20.2 ft. I scribe "T22S.

R12W, Sec 28, BT"

12" Spruce bears S.50°W., 17.3 ft. I scribe "T22S R12W Sec. 32 BT"

14" D. Fir bears N.19°W., 12.6 ft. I scribe "T22S R12W S29 BT"

22" D. Fir bears S.70°E., 18.6 ft. I scribed "T22S R12W Sec. 33 BT"

RE-RENEWED SEE CORNER NO. #129

FDOK BY
K Reed Deputy
Douglas Co Surveyor
5/13/80
C.S. 61/6

Bruce A. Shaner
For: Jack Russell
July 30, 1977
M 66 - 30

132

1/4 Corner for Secs. 32 and 33. For Menasha & Margaret Coffey Spd M120-10

Set - Brass cap mkd. 1/4 S32, S33, T22S, R12W, 1977.

From which a:

48" Spruce stump orig. BT scribes "1/4 S visible bears N.78 1/2°E
30.4 ft.

34" Red cedar bears N.43°W., 44.5 ft. I scribe "1/4 S32 BT"

54" Spruce bears N.68°E., 44.4 ft. to scribed face, I scribe

"1/4 S33 BT"

pd 7/90
M112-9

FDOK BY John Minor

FDOK BY
John Minor
For Menasha
& Margaret
Coffey
5/94 M120-10

133

Meander corner, Secs. 32 and 33

At M.C. set tack on tie 0.7 ft. North of North rail of So. Pacific RR.

134

Witness Cor. to M.C. Secs. 32 and 33.

Set - Brass cap mkd. W.C. S 2° W, 49.7 ft. to M.C. S32, S33 T22S
R12W, 1977

From which a:

16" D. Fir bears N.62°W., 18.6 ft. I scribe "T22S R12W, S32 WC BT"

10" D. Fir bears N.8°E., 8.2 ft. I scribe "T22S R12W S33 WC BT"

135

Meander Corner south line of Sec. 33. (East 329.34 ft. from Sec. Cor.
32 and 33.

Found - 2" Iron pipe from which a:

26" D. Fir stump, orig. BT partial scribes "BT" bears S.16°E., 20.5 ft.

36" D. Fir stump, orig. BT scribes visible bears N.2°W., 13.2 ft.

RE-RENEWED SEE CORNER NO. #151
(See also notes in C.S. file 62/35)

136

1/4 Corner for Sec. 18 and Sec. 13 of T22-13

Found - 40" Spruce stump 6 ft. high with previously chopped out blaze. (Orig. BT)

34" Spruce stump 4 ft. high S.1°30'E., 54.0 ft. with blaze on
north side. (Line tree). See Ren. #91

Set - 5/8"x30" I.Rod with a 1 1/2" alum. cap mkd. "OREGON STATE PARKS"
S.50°W., 22.0 ft. from found BT.

Steel post with white paddle mkd. "E 1/4 S13".

BT's - 14" Spruce S.75°45'W., 8.1 ft. scribed "1/4 S13 T22SR13WBT", tagged
with a Parks corner tag.

18" Spruce N.22°30'E., 17.1 ft. scribed "1/4 S18 T22S R12W BT RS 691".

John E. Hollingsworth
For: Oregon State
Parks Survey
Umpqua Lighthouse
State Park
Aug. 26, 1977
M 66 - 64
C.S. 58/152

8/26/77

July 78
1-79