

Douglas County Surveyor's Record of
Government Corners Renewed

T 22 T. S. R 12 R. W. W. M.

KORE-CHAPMAN CO., EUGENE, ORE. 91881

137

Gary L. Langlitz
Larry E. Monrean
S.J. Flause
F.C. Silagy
Doug. Co. Surveyors
Office
Witness: Stephen
Waite.
March 1978
C.S. 59/46

Center 1/4 Corner for Sec. 4 (NOT OF RECORD)

Found - A 1" I.P. nearly rusted away, with wooden plug and nail inside.

Note: This survey marker location was brought to our attention by Mr. Stephen Waite, a resident of Reedsport, Oregon. A 12" Red Alder, alive and in fair condition with illegible scribing visible on partially healed blaze. We open the lower portion of the blaze and find scribing "4 399". This tree bears S.15°E., 27.9 ft. from the found I.P.

An 18" D. Fir alive with well healed single blaze bears S.25°W., 22.0 ft.

Condition report only. No monument or accessories set.

Corner located approx. 100 ft. South of the Catholic Church and approx. 21 ft. East of Power Pole AG 043 4.

3/13/78

1/4 Corner for Secs. 15 and 14.

Set - Stamped 2" I.P. with brass cap from which:

BT's - 40" Fir stump bears N. 12°E., 21.1 ft. Orig. BT.

48" Spruce bears S.47°W., 16.5 ft. Orig. BT.

New BT's

56" Spruce bears S.7°E., 21.7 ft. scribed.

20" Hemlock bears N.52°W., 27.3 ft. scribed.

Richard Hintz:
For: Champion
International
Oct. 1978
M 74 - 4

Section corner for Secs. 10, 11, 15 and 14.

Set - Stamped 2" I.P. with brass cap from which:

BT's - 72" Cedar bears S.65°E., 99.0 ft. Orig. BT.

Set - 50d nail in new face which bears S.65°30'W., 97.7 ft. scribed.

38" Maple, N.24°30'E., 61.7 ft.

20" alder, S.39°W., 30.1 ft. and 28" maple, N.83°W., 89.8 ft.

Center 1/4 Corner for Sec. 14.

Set - Stamped 2" I.P. with brass cap from which:

30" Fir bears S.70°30'W., 56.5 ft. scribed.

BT. IMPR.
ADDED TO RENEWAL
RECORD
8/5/82
J.R.

FD OK BY JOHN Minor 5/94
FOR MENASHA & Margaret Coffey
M120-10

1/4 Corner for Secs. 28 and 33.

Found - Scribed stone recorded by Hootman (marking appears to be a portion of a 4) set flush with ground.

Stone located by measuring from monuments recorded on M 22 - 28

See also C.S. 51/61.

Orig. BT's and orig. monument not found.

New BT's- A D. Fir, 7" double blazed and scribed "1/4 S28 CS BT" bears N.44°W., 179.4 ft.

An alder 15", bark scribed "1/4 S33 CS BT" bears S.68°W., 207.0 ft.

Set a bridge spike midway on most southerly rail (curb) of bridge over Scholfield Creek. Spike is marked "B.O. 1" and abears N.2 1/2°E., 123.7 ft.

A County Surveyor brass cap set in concrete tile marked "SC 14 1975" bears N.86°E., 100.9 ft.

11/28/78

Section corner common to Secs. 26 and 35 only. (East)

Found - 32" Fir bears S.57°W., 17 lks. now 58"x36" High stump in place, face closed.

28" Fir bears N.67°W., 33 lks., now 38"x 36" High stump in place, portion of face exposed, no scribes visible

1 1/2" x 36" G.I.P. in mound of stone (in place) from which a:

44" Fir (Orig.) bears S.57°W., 11.2 ft. Ren. #54

34" Fir (Orig.) bears N.67°W., 21.8 ft.

Rewitnessed:

62" x 36" high Fir stump bears N.16 1/2°W., 60.4 ft. to face scribed RS 1101.

Set - 4"x4"x72" White painted Cedar post S.38 1/2°E., 2.0 ft. from corner pipe. Oregon State Forestry Department metal location poster on 62"x36" high stump, N.16 1/2°W., 60.4 ft.

Also poster on 58"x36" high Fir stump, S.57°W., 11.2 ft.

12/13/78

Larry E. Monrean
P.L. Earle
S.J. Flause
Doug. Co. Surveyors
Office
Nov. 28, 1978
C.S. 60/17

James M. McIntosh
J. Ferguson
S. Ditterick
D. Anders
Oreg. St. Bd. of
Forestry
Dec. 13, 1978
C.S. 58/164

FD OK
New By Lloyd
Smith
M100-35