

Douglas County Surveyor's Record of
Government Corners Renewed

T 22 T. S. R 12 R. W. W. M.

FOKE-CHAPMAN CO., EUGENE, ORE. 97501

148

C O N T. - - - - -

Douglas County
Surveyors Office
S. J. Flause -
L. E. Monrean
C.S. 61/6
March 3, 1980

A 14" Spruce, S.78°W., 33.7 ft. scribed T22S R12W S14 BT on a double blaze.
A 38" Hemlock, N.64°W., (Champion tag read N.66°W., we retag to indicate our measured bearing and distance), 26.6 ft. scribed T22S R12W S11 on a single blaze.
A 24" Alder, N.18°E., 24.1 ft. scribed T22S R12 W S12 BT on a double blaze.
A 27" Alder S.59°E., (Champion tag read S.54°E., we retag) 35.7 ft scribed T22S R12W S13 BT on a double blaze.
We also tag original BT's except Hemlock with DCSO BT tags.
Set - Reference out 3/4" I.P. and remove. Set Standard DCSO brass cap marked "Douglas County Surveyors Office" T22S R12W S11 S12 S14 S13 1980, in pipe's place, then set 3/4" I.P. on north side of cap.

3/80

149

Witness corner for Secs. 1 and 2

Found - 1 1/2" x 36" I.P. with no cap. Obviously taken off. Ren. #75
A 5/8" I. Rod bears N.49°W., 33.0 ft. This rod is 7.3 ft. S. of south rail of RR tracks.
A 5/8" I. Rod bears N.2°W., 30.9 ft. This rod is 9.2 ft. N. of north rail of RR track.
Set - A 1" x 36" Iron pipe with brass cap stamped "Douglas County Surveyor" T22S R12W 1/4 S2 S1 W.C. 365 ft. S. 1980" at the position from iron rods. Ren. #75

Removed old pipe.

No suitable trees.

New B.O. A 5/8" Iron rod bears N.88°E., 46.7 ft. with alum. cap stamped "B0 1"
A 5/8" Iron rod bears S.7°E., 18.2 ft. with alum. cap stamped "B0 2".

3/27/80

150

1/4 Corner for Secs. 27 and 28

Found - 1 1/2" iron pipe protruding 2.1 ft. above ground. Ren. #22
Pipe measures 5 ft. in length
No orig. trees found.

A 16" Alder now an 18" with partially healed blaze (no scribing on face) bears N.42°W., 13.3 ft. Ren. #22
A 22" Alder, now an 18" with partially healed blaze with visible scribe "1/4 S" bears N.85°E., 20.2 ft. Ren. #22

Set - 1" x 36" Iron pipe with brass cap stamped "Douglas County Surveyor" T22S R12W 1/4 S28 S27 1980" at position of pipe, set pipe on east side of cap protruding 2.4 ft. above ground.

New BT's - An 18" Alder scribed "1/4 S27 CS BT" in a double blaze bears S.71°E., 45.6 ft.

A 15" Alder scribed "1/4 S28 CS BT" in a double blaze bears S.70°W 17.3 ft.

Note - Located on slope descending North approx. 330 ft. southerly of RR tracks.

4/2/80

151

M.C. for Secs. 33 and Sec. 5 of T.23-12

Found - 2" ± Iron pipe (2 1/2" O.D.) firmly set 4" above ground. (I believe this monument to be set by Warren D. Hootman L.S. 399 See C.S. 51/55 narrative) See also Ren. #135

Orig. 19" now a 28" Dia. Fir stump 4 1/2 ft. tall with partially healed blaze and fragmentary scribing bears S.16°E., 20.5 ft.

Orig. 24" now a 33" dia. Fir stump with visible blaze and a scribed "S" with other fragmentary scribing bears N.2°W., 13.2 ft
This stump about 2 feet tall.

Not of record, a 5/8" dia. I. Pipe bears S.63 1/2°W., 3.8 ft.

New Accessories:

A 13" Cedar scribed "MC S5 DCSO BT" on a double blaze bears S.29°E. 23.2 feet.

A 28" Fir scribed "MC S33 CS BT" on a double blaze bears N.53 1/2°E., 12.7 ft.

6/3/80

Karen Reed - Deputy Douglas County Surveyors Office
Terrie Plouff, Witness
March - April 1980
C.S. 61/6

Larry E. Monrean
Deputy - Doug. Co.
Surveyors Office
Greg Quibell, Deputy
June 3, 1980
C.S. 61/11

See Also
Notes in
C.S. 62/38