

Douglas County Surveyor's Record of
Government Corners Renewed

T 22 T. S. R 12 R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 91881

152

Section corner for Secs. 18 and 19; and 13 & 24 of T.22-13
 Found - Unrecorded 5/8" x 41" I.R., 9" out of the ground, S.18°W., 1.15 ft.
 from 4" x 4" x 8 ft. white post.
 Orig. 30" spruce now 36" rotted stump with possible opened face
 bears N.15°W., 10.6 ft. A small piece of wood with BLM BT tag
 was lying on stump. See Ren. #90
 Orig. 24" spruce now 46" stump with "S19 T" visible in opened
 blaze bears S.72°E., 44.9 ft.
 All other BTs appear to be completely gone.
 Set - At the position of the 5/8" I.R. I SET brass cap stamped "Douglas
 Co. Surveyor T22S R13W S13 S24 S18 S19 R12W 1981" 7"
 above ground. The 5/8" I.R. was set flush with brass cap
 along its northerly edge.
 New BT's- 19" spruce bears S.54°W., 35.4 ft. (to center of tree trunk)
 scribed "T22S R13W S24 CS BT" in double blaze.
 18" spruce bears N.28°W., 30.4 ft. scribed "T22S R13W S13 CS BT"
 in double blaze.
 24" spruce bears S.8 1/2°E., 71.4 ft. scribed "T22S R13W S13 CS
 BT" in double blaze.
 Center of door of chlorination plant bears S.67°W., approx. 150 ft.
 - - - - - 5/19/81

153

Witness Corner to 1/4 cor. of Sec's. 1 & 12.
 Found - 1" I.P. with Brass Cap stamped: Renewal # 82.
 County Surveyors Office T22S R12W W.C. To 1/4 S1 S12 1971 .
 This monument set in concrete.
 *NOTE - A review of the survey notes filed in the County Surveyors
 Office shows this monument not set on the section line.
 Accessories
 Found - Orig. 1/4 cor. BT's not found. Renewal # 82.
 13" R.Cedar (Orig. 5"), with well healed blaze, bears
 S.18 1/2 °W. (REC S.20°W.), 141.3-ft.
 1" I. Bolt at S.W. corner of bridge bears N.31 1/2 °E., 38.3-ft.
 (REC N.33°E., 38.45-ft.).
 1" I. Bolt at S.E. corner of bridge bears N.57 1/2 °E., 44.6-ft.
 (REC N.59°E., 44.74-ft.).
 1" Drill Steel bears N.87 1/2 °E., 32.1-ft. (REC N.88°47'E.,
 32.16-ft.).
 The following accessories are from Ren.#82, but the distances
 are from the 1981 monument.
 1" Drill Steel bears N.60°E., 53.9-ft.
 13" R. Cedar with healed blaze bears S.17°W., 111.8-ft.
 Set - At the true position of witness corner as determined by survey
 (see Doug. Co. Surveyors files C.S. 56/5, & M 42 - 27),
 we set a 1" x 30" I.P. with attached Brass Cap marked:
 Douglas County Surveyor T22S R12W WC TO 1/4 S1 S12 1981,
 from which the 1/4 corner S1 S12 bears S.88°47'W., 170.57'
 per survey M 42 - 27.
 We leave the 1971 B.C. Mon. set firmly and RESTAMP; it is
 now marked: Douglas County Surveyor SC7 RESTAMP 1981 1971
 This Mon. bears N.27 1/2 °E. of the Witness Corner.
 See sketch in file C.S. 61/27. ^{30.09 ft. 2/8 3/8/89}
 - - - - - 7/29/81

154

Section corner for Secs. 33 and 34 only.
 Found - 2" x 36" galv. I.P. firmly set protruding 8" out of ground. Ren#145
 20" cherry (now dead) with scribed "BT S T" visible in partially
 burned unhealed face, bears N.33°E., 19.2 ft. (rec. 18.4 ft.)
 70" hemlock now 48" stump with scribed "BT S4 T23 R12" visible
 in unhealed face bears S.53°E., 78.3 ft. (Rec. 75.4 ft.)
 34" hemlock now 65" stump with scribed "S33 T22 R12" visible in
 unhealed face, bears S.79°30'W., 40.6 ft. (rec. 38.0 ft.)
 Note: Rec. distances were possibly taken to face of tree instead of
 center. (Recn. #145)
 Set - After referencing fd. 2" I.P., I set a 1" x 36" I.P. with brass
 cap attached in its place. Cap is mkd. "Douglas Co Surveyor
 T22S S33 S34 R12W S4 T23S 1982"
 The fd. 2" I.P. was buried along north edge of brass cap. A green
 metal fence post was also placed just north of cor.

C O N T . N E X T P A G E

Gregory Quibell,
 Deputy, Doug. Co.
 Surveyors Office
 Stephen Flause
 Terrie Plouff
 Karen Mosley
 May 19, 1981
 C.S. 61/24

Larry Ed Monrean
 Deputy - Douglas County Surveyor
 Witness... T.R. Plouff
 July 29, 1981
 C.S. 61 / 27

Greg Quibell
 Deputy, Doug. Co.
 Surveyors Office
 Feb. 23, 1982
 C.S. 61/30
 T. Plouff, Witness