

Douglas County Surveyor's Record of
Government Corners Renewed

T 22 T. S. R 12 R. W. W. M.

HORE-CHAPMAN CO., EUGENE, ORE. 21001

154

C O N T - - -

(Sec. cor. for 33 & 34 only)
New BO's - Boat spike stamped "BO 1" in face of 20" cherry BT. per Ren.#145 bears N.33°E., 18.8 ft.
Boat spike stamped "BO2" in top of 72" hemlock stump, bears N.69°E., 143.9 ft.
Boat spike stamped "BO3" in face of 48" hemlock stump BT per Ren. #145, bears S.53°30'E., 75.6 ft.
Boat spike stamped "BO 4" in top of 36" hemlock stump bears S.37 1/2°W., 87.9 ft.
Boat spike stamped "BO 5" in top of 65" hemlock (stump BT per Ren. #145 bears S.81°W., 39.4 ft.
Metal fence post with survey marker sign & line crossing tag bears south 25.2 ft. BT tags on all stumps.
Corner lies in new clearcut. (sketch in C.S. file)

Gregory Quibell, Deputy
Doug. Co. Surveyors
Office
T. Plouff
Feb. 23, 1982
C.S. 61/30

2/23/82

155

1/4 Corner for Sections 8 and 17
Found - Orig. 20" now 34" badly rotted spruce stump 6 ft. tall. Found reverse scribed "BT" on pitched up face.
No trace of orig. 18" spruce found.
Set - At record bearing and dist. from orig. 20" spruce (n.18 1/2°E., 44.2 ft.) I SET a 1" x 30" I.P. with brass cap attached protruding 7" out of ground. Cap is mkd.: Doug. County Surveyors Office T22S R12W S8 S17 1/4 1982
New BT's- 30" double spruce with scribed "1/4 S8 CS BT" in double blaze bears N.16°E., 17.5 ft.
20" spruce scribed "1/4 S8 CS BT" in double blaze bears N.67°E., 32.4 ft.
17" spruce scribed "1/4 S17 CS BT" in double blaze bears S.23°E., 27.5 ft.
15" fir scribed "1/4 S17 CS BT" in double blaze bears S.53°W., 19.6 ft.
Sketch in C.S. file.

Larry E. Monrean
Deputy, Dougl. Co.
Surveyors Office
Greg Quibell
Karen Reed
John Powell
April 12, 1982
C.S. 61/30

FOR CORNER REPORT
SEE C.S. 63/46

4/12/82

156

1/4 Corner for Secs. 9, & 10.
Set - Brass Cap mkd: T22S R12W WM 1/4 S9 S10 Shaner Engineering RLS 430 1982, from which a:
New BTs- 18" D. Fir, I scribed: 1/4 S10 BT, bears S.80°E., 84.3-ft.
28" hemlock, I scribed: 1/4 S9 BT, on bark, bears S.46°W., 75.0-ft.
note - Corner falls in bottom of a draw, North, 120-ft. from the top of a main ridge, which runs east-west. 6/82

Bruce A. Shaner
L.S. 430
For: Moore Mill &
Lmbr. Co.
June, 1982
RM 3 - 59

157

Center 1/4 Corner of Sec. 10.
Set - Brass Cap mkd: T22S R12W WM C1/4 S10 Shaner Engineering RLS 430 1982, from which a:
New BTs- 24" alder, I bark scribed C1/4 S10 BT, bears N87°E., 8.8-ft.
8" hemlock, I scribed C1/4 S10 BT, bears S.35°W., 43.0-ft.
32" cedar, I scribed C1/4 S10 BT, bears N.65°W., 80.3-ft.
note - Corner lies +250 ft. North of main east-west ridge.

6/82

158

Section corner for Secs. 15, 16, 22 and 21. *FO, OK 3/92 BY WILCOX M 115-4*
Found - 35" cedar stump with scribing visible on reverse at face.
26" cedar in position for the SE BT.
NE and SW BTs are missing.
Set - At the point of intersection of the record distances, SET a 2 1/2" brass cap on 2 1/2" x 30" I.P. mkd. LS 1091
BT's - 35" cedar stump bears N.44°30'W., 7.3 ft. (1889 BT)
26" cedar bears S.20°00'E., 15.8 ft. (1889 BT).
New BTs- 16" fir bears N.76°00'E., 13.9 ft. scribed T22S R12W S15 BT.
12" fir bears S.32°00'W., 5.2 ft. scribed T22S R12W S21 BT.

Robert B. Ward
For: Champion
International
Nov. 1981/June 1982
M 92 - 58

159

1/4 Corner for Secs. 15 and 22
Found - Both fir BTs with scribing visible.
Set - 2 1/2" brass cap on 2 1/2" x 30" I.P. with stamped LS 1091.
BT's - 32" fir stump bears N.8°00'W., 8.6 ft. (1889 BT)
40" fir stump bears S.83°00'W., 7.9 ft. (1889 BT)
New BTs - 14" spruce bears N.62°00'W., 21.1 ft. scribed 1/4 S15 BT
11" spruce bears S.65°00'W., 32.2 ft. scribed 1/4 S22 BT.