

Douglas County Surveyor's Record of  
Government Corners Renewed

T 22

T. S.

R 12

R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

160

Center 1/4 Sec. 22

- Set - 2 1/2" brass cap on 2 1/2" x 30" I.P. with stamped LS 1091.  
BTs - 12" alder bears N.31°30'W., 5.4 ft. scribed C 1/4 S22 BT.  
34" cedar bears S.73°00'E., 18.4 ft. scribed C 1/4 S22 BT.

1/4 Corner for Secs. 21 and 22.

- Found - No trace of 1889 GLO corner or accessories.  
Set - At point of proportionate measure set a 2 1-2" Brass cap on 2 1/2" x 30" I.P. with stamped LS 1091.  
New BTs - 13" fir bears N.72°00'W., 14.5 ft. scribed 1/4 S21 BT.  
13" fir bears S.13°00'E., 8.3 ft. scribed 1/4 S22 BT.

1/4 Corner for Secs. 22 and 23

- Found - No trace of 1879 GLO corner or accessories.  
Set - At point of proportionate measure set a 2 12/" brass cap on a 2 1/2" x 30" I.P. with stamped LS #1091.  
New BTs - 22" alder bears S.75°30'W., 9.9 ft. bark scribed 1/4 S22 BT  
21" alder bears N.12°00'E., 42.4 ft. bark scribed 1/4 S23 BT.

1/4 Corner for Secs. 22 and 27

- Found - 38" cedar snag with chopped face on north side with the following accessories:  
42" fir stump with scribing visible bears N.74°00'E., 10.4 ft. (1889 BT)  
Rotted fir stump bears S.80°00'W., 8.5 ft. (1889 BT)  
Set - A 2 1/2" Brass cap on a 2 1/2" x 30" I.P. with stamped LS #1091.  
New BTs - 15" fir bears N.87°30'E., 20.2 ft. Both scribed X BT.  
60" fir bears N.0°30'E., 43.3 ft.  
Corner tree bears N.89°12'06"W., 21.04 ft.  
Note: Corner as called by PLS 399 and Douglas Co. Surveyors Office bears S.4°17'44"W., 359.34 ft. See Renewals #19 and #104 & #168

Section corner for Secs. 9, 10, 15 and 16.

- Found - 36" spruce stump with scribing visible (SW BT) and rotten spruce stumps in position for NE and SE BTs.  
Set - At the point of intersection of the record distances set a 2 1/2" brass cap on a 2 1/2" x 30" I.P. with LS #1091 stamped.  
BTs - 36" spruce stump bears S.7°30'W., 56.4 ft. (1889 BT)  
Rotted spruce stump bears N.46°00'E., 49.4 ft. (1889 BT)  
Rotted spruce stump bears S.82°30'E., 40.5 ft. (1889 BT)  
New BTs - 12" alder bears N.48°00'E., 38.9 ft. bark scribed T22S R12W S10 BT.  
12" hemlock bears S.22°00'E., 17.1 ft. scribed T22S R12W S15 BT.  
14" hemlock bears S.44°00'W., 55.0 ft. scribed T22S R12W S16 BT.  
16" alder bears N.30°00'W., 37.9 ft. bark scribed T22S R12W S9 BT.

1/4 Corner for Secs. 10 and 15

- Found - No trace of 1889 GLO corner or accessories.  
Set - At point of proportionate measure set a 2 1/2" brass cap on a 2 1/2" x 30" I.P. with LS #1091 stamped.  
New BTs- 12" alder bears S.16°00'W., 5.5 ft. bark scribed 1/4 S15 BT.  
10" alder bears N.68°00' W., 11.2 ft. bark scribed 1/4 S10 BT.

1/4 Corner for Secs. 15 and 16

- Found - no trace of 1889 GLO corner or accessories.  
Set - At point of proportionate measure set a 2 1/2" brass cap on a 2 1/2" x 30" I.P. stamped with LS #1091.  
BTs - 10" fir bears N.20°00'E., 10.9 ft. scribed 1/4 S15 BT.  
11" hemlock bears S.46°00'W., 7.3 ft. scribed 1/4 S16 BT.

FDOK BY  
John Minor  
11-94 M121-32

Robert B. Ward Jr.  
For: Champion  
International Corp.  
Nov. 1981/June 1982  
M 92 - 58

L. ROBERTS  
SET ALUM. POST  
SERIES B.C.  
M105-30  
7/15/87  
ALSO C.S. 63/55

Robert B. Ward Jr.  
For: Champion International  
Nav. 1981/June 1982  
M 92 - 57

L. ROBERTS  
SET ALUM. POST  
SERIES B.C.  
7/15/87  
M105-30  
ALSO C.S. 63/55

RE-RENEWED SEE CORNER NO. 248