

Douglas County Surveyor's Record of
Government Corners Renewed

T 22

T. S.

R 12

R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21981

Karen Reed
John Powell
Doug. Co. Surveyors
Office
Sept. 7, 1982
C.S. 62/1

1/4 Corner Secs. 6 and 7

Found - 2" diam. iron pipe protruding 6" above the ground. Ren. #45
(Rec. 1 1/2" diam. per Ren. #1)
40 spruce stump with visible scribe bears S.29°E., 9.2 ft.
6" spruce, now 9", bears S.80°E., 11.0 ft. with a well healed
double blaze.
14" alder, now 16" bears N.1°W., 12.3 ft. with visible scribe
"1/4 S6 CS BT" in a double blaze.

No original trees found.

New BTs - 7" spruce bears N.57°W., 19.4 ft. scribed "1/4 S6 CS BT" in a
double blaze.

17" spruce bears S.37°W., 48.5 ft. scribed "1/4 S7 CS BT" in a
double blaze.

Corner falls 3.0 ft. from old fence corner. Fence running E & S approx.
10 ft. West of swamp and 200 ft. North of trailer park on easterly slope.

9/7/82

167

1/4 Corner for Secs. 22 and 27 (per Ren. #s 19 and 104)

Found - 1 1/2" iron pipe with 1973 county brass cap on east side
of cedar snag. Ren. #104

I cut off brass cap and set yellow plastic cap in pipe marked "Doug. Co.
Surveyor" as a result of original corner evidence found and recorded by
Robert Ward filed in the Douglas County Survey records as M 92 - 58. See
Renewal #163.

Found - An 18" diam. D. fir, now 28" with well healed double blaze bears
S.22°E., 18.0 ft. I open and deface scribe "1/4 S27".

A 16" D. fir, now 20" with well healed double blaze bears
S.80°W., 14.5 ft. I open and deface scribe "1/4 S27 BT".

A 14" hemlock with partially healed double blaze bears N.52°E.,
26.2 ft. I deface visible scribe "1/4 S22".

New corner position determined by Robert Ward. See M 92 - 58 and Ren. #163
8/16/82

168

Section Corner common to Sections 25 and 36. (West side)

Found - 14" Fir bears S.28°E., 28 lks., now 31" x 2 ft. high stump
S.28°E., 18.5 ft. slope distance, scribe S visible. (orig.)

Fir Post missing.

9" alder missing.

1 1/2" x 36" G.I.P. (moved by logging) Ren. #115

29" fir bears N.53°E., 98.4 ft. now 32" x 2 ft. high stump

N.53°E., 104.1 ft. to side center, but below face. Ren. #115

Yellow metal location poster on 40" fir bears N.09°W., 11.7 ft.
now 45" in place.

Set - 1 1/2" x 36" alum. pipe with 3 3/4" alum. cap marked "State Of
Oregon Department of Forestry T22S R12W S25 S36 S35 1982 LS1101"
30 inches in ground and from which a:

34" x 3ft. high cedar stump bears N.52°E., 86.3 ft. to face;
scribed T22S R12W S25 BT.

Set 4" x 4" x 72" white painted Cedar post N.75°W., 1.3 ft. from corner
pipe.

Oregon State Forestry Department metal location poster on 34" x 3ft
high cedar stump bears N.52°E., 86.3 ft.

10/12/82

169

Section corner for Secs. 8, 9, 16 and 17

Found - 30" spruce now a 36" dia. decayed stump bearing N.7°E.,
47.5 ft. We remove pitch from a previously opened blaze and
find faint scribing "T R 12". The figures R 12 being the
most legible.

Original (1857) 4 x 4 post) not found.

At record bearing and distance (S.7°W., 47.5 ft.) from the found evidence
we set a temporary point and search for the remainin- BT evidence as follows:

A 30" spruce bearing S.73°W., 18.5 ft. We find rotted remains
of a spruce, size indeterminate bears S.76°W., 13.0 ft. No
blaze or scribing found.

A spruce 18" diam. bearing N.70°W., 50.2 ft. We find a badly
decayed stump, size indeterminate bears N.70°W., 45.5 ft. No
blaze or scribing found.

We found no sign of the 5" diam. spruce at S.79°E., 25.1 ft.

170

Lloyd D. Smith
For: Dept. of
Forestry, State of
Oregon
Witness: Timothy
VanVleet
October 12, 1982
C.S. 58/164

Larry E. Monrean,
Deputy, Doug. Co.
Surveyors Office
J.M. Powell;
T.R. Fransenn
Oct 18, 1982
C.S. 62/1