Douglas County Surveyor's Record of Government Corners Renewed

T 22 T. S. R 12 R. W. W. M.

KORE-CHAPMAN CO., EUGENE, ORE. 21981

William Shull
LS #909
For: U.S.F.S.
Jan. 20, 1985
M 98 - 70

177

Section corner for 30 and 31; and 25 and 36 of T.22-13
Found - 1982 BLM alum. cap and pipe. (See also Ren. #4)
7" pine, dead, N.37°E., 23.8 ft. scribed "R12W S30 CS BT".
10" pine, N.12°W., 15.8 ft. scribed R13W S25 CS BT".
18" pine S.71°E., 15.8 ft. healed blaze.
10" fir, S.10 1/2°E. 25.4 ft. scribed "T22S R12W S31 BT".
NE cor of A-frame house bears S.64 1/4°W., 44.9 ft. not scribed.
New BT - 5" fir, N.54°E., 13.2 ft. scribed X BT.
Set - USFS alum. reference monument, a 2 1/2" x 30" alum. pipe with 3 1/4" alum. cap with magnet attached under cap. Cap stamped "T22S R13W R12W RM S82°23'E 54.8' 1984 LS 909"

FD 10/90 M 111-5

178

N 1/4 Section Corner for Section 3 only, (T23-12) REN #73
Found - 1" Galvanized Iron Pipe, (Stuntzner-1970 : Now bears S.06°W., 13.5 ft. from new corner position.
4"x4"x72" White painted cedar post bears N.33°W., 2.0 ft. dist.
BT's - 22" Fir, bears S.12°W., 72.6 ft. dist. with a bearing tree tag (Stuntzner, 1970 SW BT)
29" Fir, bears S.20°E., 76.4 ft. dist., (Stuntzner, 1970 SE BT)
11" Chittum, bears S.03°E., 13.8 ft. dist. to North side. (Stuntzner, 1970 SE BT)
SET - An OSDF 1 1/2" x 36" aluminum pipe with a 3 3/4" diam alum. cap with magnetic insert, at corner position, 34" in ground.
NEW BTs- 22" Alder, bears S.50°E., 35.6 ft. dist. Bark scribed: 1/4S3BT with a Bearing tree tag in place.

FD 10/90 M111-5

179

Closing Corner for Sections 34 and 35 on South Bdy. of Township.
SET - OSDF 1 1/2" x 36" alum. pipe with a 3 3/4" diam. alum. cap and magnetic insert. Pipe is 34" in ground.
BT's - 19" Fir, bears N.50°E., 20.3 ft. dist., scribed: T22SR12WS35CCBT, with a bearing tree tag in place.
22" Fir, bears N.10°W., 2.3 ft. dist., scribed: T22SR12WS34CCBT, with a bearing tree tag in place.
NEW BO - Set a 4"x4"x72" white painted cedar post, bearing N.74°E., 1.8 ft. dist.

Lloyd D. Smith
RPLS # 1101
For: State of Oregon.. Dept. of Forestry
January, 1986
M 100-37 and M 100-38

180

S1/4 Section Corner for Section 35 ONLY
SET - An OSDF 1 1/2" x 36" alum. pipe with a 3 3/4" diam. alum. cap and magnetic insert. Pipe is 34" in ground.
BT's - A 30" Maple clump bears N.62°E., 31.7 ft. dist., scribed 1/4S35BT, with a bearing tree tag in place.
A 19" maple, bears N.35°W., 34.2 ft. dist., scribed 1/4S35BT, with a bearing tree tag in place.
NEW BO - Set a 4"x4"x72" white painted cedar post, bearing S.17°E., 1.8 ft. dist.

181

N1/4 Section Corner for Section 2 ONLY (T23-12)
SET - An OSDF 1 1/2" x 36" alum. pipe with a 3 3/4" Diam. alum. cap and magnetic insert. Pipe is 34" in ground.
BT's - A 15" Alder, bears S.61°E., 24.7 ft. dist., bark scribed 1/4S2BT, with a bearing tree tag in place.
An 18" Alder, bears S.34°W., 13.5 ft. dist., bark scribed 1/4S2BT, with a bearing tree tag in place.
BO - Set a 4"x4"x72" white painted cedar post, bearing S.24°E., 1.8 ft. dist.

182

Closing Corner for sections 1 and 2 only on N. Bdy. of T.23-12
SET - An OSDF 1 1/2" x 36" aluminum pipe with a 3 3/4" alum. cap and magnetic insert. Pipe is 34" in ground.
Old BTs- Multi trunk myrtle (Stephens 1952) bears N.72°W., 51.8 ft. dist., Now uprooted and 10.0 ft. downhill.
BO - 3/4" iron pipe (Stephens 1952) bears West, 27.5 ft. dist. (in place)
NEW BTs- 18" Alder, bears S.14°E., 69.4 ft. dist., bark scribed: T23SR12WS1BT, with a bearing tree tag in place.

RE-RENEWED CORNER NO. # 245

CONTINUE ON NEXT PAGE.....