

Douglas County Surveyor's Record of
Government Corners Renewed

22 T. S. 12 R. W. W. M.

ROKE-CHAPMAN CO., EUGENE, ORE. 21881

CONTINUED.....

Closing Cor. for Secs. 1 & 2 only (T23-12) North Boundary. 182
 NEW BT's- 9" Alder, BEARS S.30°W., 80.3 ft. dist., bark scribed:
 T23SR12WS1BT, with a bearing tree tag in place
 NEW ~~BO~~ - Set a 4"x4"x72" white painted cedar post, bearing N.63°W., #245
 4.0 ft. dist.

Closing Corner for Sections 35 and 36 on S. bdy. of Township. 183
 SET - An OSDF 1 1/2" x 36" alum. pipe with a 3 3/4" alum cap and
 magnetic insert. Pipe buried 34" in ground.
 NEW BT's- 16" Myrtle, bears N.67°E., 33.1 ft. dist., scribed:
 T22SR12WS36CCBT, with a bearing tree tag in place.
 29" Fir, bears N.46°W., 20.0 ft. dist., scribed:
 T22SR12WS35CCBT, with a bearing tree tag in place.
 NEW BO - Set a 4"x4"x72" white painted cedar post, bearing N.43°E.,
 1.1 ft. dist.
 NOTE: Stephens 1952 Closing corner point for sections 35 and 36
 bears S.89°42'45"W., 209.93 ft. dist.
 Old BTs - 24" Fir, (Stephens) bears N.12°W., 30.0 ft. dist., (Now
 a 28" x 30" high snag in place)
 14" Fir, (Stephens) bears N.57°W., 22.6 ft. dist., (Now
 23" in place)

FD OK 2-92
H. WILCOX M 114-75

Lloyd D. Smith
RPLS # 1101
For: State of Oregon - Dept. of Forestry
January, 1986
M 100-37 and M 100-38
FO. 10/90 M 111-5

Center 1/4 Section Corner for Section 35 184
 SET - An OSDF 1 1/2" x 36" alum. pipe with a 3 3/4" alum cap and
 magnetic insert. Pipe is 34" in ground.
 BT's - 27" Myrtle, bears N.17°E., 18.3 ft. dist., scribed: C1/4S35BT,
 with a bearing tree tag in place.
 45" Fir, bears S.79°E., 40.8 ft. dist., scribed: C1/4S35BT,
 with a bearing tree tag in place.
 BO - Set a 4"x4"x72" white painted cedar post, bearing N.50°W., 1.5 ft.
 dist.

East 1/4 Section Corner to sec. 35 ONLY 185
 SET - An OSDF 1 1/2" x 36" alum. pipe with a 3 3/4" alum. cap and
 magnetic insert. Pipe is 34 ins. in ground.
 BT's - 36" Fir, bears S.16°W., 18.5 ft. dist., scribed: 1/4S35BT,
 with a bearing tree tag in place.
 25" Fir, bears N.49°W., 13.8 ft. dist., scribed: 1/4S35BT,
 with a bearing tree tag in place.
 BO - Set a 4"x4"x72" white painted cedar post, bearing N.21°W., 1.5 ft.
 dist.

1/4 Corner for Section 5; and Sec. 32 of T.21-12 186
 Found - Rotten 30" high stump (24" Spruce) N.36°W., 22.2 ft. to center
 21.1 ft. to face (N.36°W., 32 lks.=21.1 ft.) with weathered
 face mkd. "BT". Ren. No. 3 of T.21-12
 1 1/2" I.P. with fitting, flush in marsh with white plastic cap
 mkd. "Thompson RE 3683" in center. Ren. No. 114
 14" red alder stump (18") N.14°E., 18.5 ft. (N.8°30'E., 18.5
 with scribes "1/4S...3683BT".
 14" red alder snag (17") S.72°W., 51.4 ft. (S.71 1/2°W., 51.4 ft
 with scribes "1/5S5 3683".
 New BTs - 16" Sitka spruce N.26°E., 24.0 ft. mkd. "T21S R12W S32 1/4 BT".
 13" Sitka spruce S.88°E., 33.6 ft. mkd. T22S R12W S5 1/4 BT".

FOR CORNER REPORT
SEE C.S. 63/46

Section corner for Secs. 5 and 4; and 32 and 33 of T.21-12. 187
 (Did not find original evidence)
 Set by single proportion: 18" alum. rod with cap mkd. "T21SR12WS32S33T22S
 S5S4 8 ins. below surface of rock road.
 New Accessories:
 38" Sitka spruce N.46°E., 90.4 ft. mkd. T21S R12W S33 BT".
 24" D. fir S.68 1/2°E., 33.7 ft. mkd. "T22S R12W S4 BT".
 19" D. fir, S.54°W., 81.7 ft. mkd. "T22S R12W S5 BT"
 28" Sitka spruce N.49°W., 77.2 ft. mkd. "T21S R12W S32 BT".
 Inlet of corrugated metal culvert bears S.54°W., 18 ft.

Andrew T. Blachly
For: Cole & Hongell Logging
and International Paper
October 1986
M 102 - 71