Douglas County Surveyor's Record of Government Corners Renewed

T 22 T. S. R 12 R. W. W. M.

FORE-CHAPMAN CO., EUGENE, ORE. 31881

210

1/4 Corner for Sections 17 and 18
Set - Monument set is a 2 3/8" dia. brass cap marked:
Douglas County Surveyors
T 22 S
R 12 W
1/4 S18|S17
1986
on a 1" dia. (1¼ O.D.) x 32" galv. iron pipe protruding 8" above ground and surrounded by a 2 ft. dia. mound of stone.
New BTs - 6" DBH spruce scribed 1/4 S17 CS BT on a double blaze bears N.75¼°E., 44.2 ft.
16" DBH alder bark scribed 1/4 S17 CS BT bears S.37°E., 8.4 ft.
12" DBH alder bark scribed 1/4 S18 CS BT bears N.79¼°W., 23.2 ft.
10" DBH alder bark scribed 1/4 S18 CS BT bears N.44 3/4°W., 27.5'.
9/9/86

211

Section Corner for Sections 7, 8, 18 and 17.
Set - Monument set is a 2 3/8" dia. brass cap marked:
Douglas County Surveyors Office
T 22 S
R 12 W
S 7 | S 8
S 18 | S 17
1986
on a 1" dia. (1¼"O.D.) x 32" long iron pipe protruding approx. 5" above ground.
New BTs - 21" DBH spruce scribed T22S R12W S8 CS BT on a double blaze bears N.13°E., 7.5 ft.
16" DBH spruce scribed T22S R12W S7 CS BT on a double blazed bears N.11½°W., 34.6 ft.
18" DBH spruce scribed T22S R12W S17 CS BT on a double blaze, bears S.27°E., 21.9 ft.
37" DBH spruce scribed T22S R12W S18 CS BT on a double blaze bears S.21½°W., 35.1 ft.
Monument lies on a moderate southwest slope.
9/22/86

212

South 1/16 Sections 17 and 18
Set - A 2 3/8" dia. brass cap marked Douglas County Surveyors office
T 22 S
R 12 W
S 1/16 S18| S17
1986
on a 1" dia. (1¼" O.D.) x 32" long glav. iron pipe firmly set and protruding 6" from ground.
New BTs - 6" dia. spruce double blazed and scribed "S 1/16 S12 CS BT" bears N.27°E., 40.3 ft.
12" dia. alder double blazed and scribed "S 1/16 S18 CS BT" bears S.60¼°W., 16.8 ft.
14" dia. D. fir double blazed and scribed "S 1/16 S18 CS BT" bears S.15½°W., 16.7 ft.
Monument is located approx. 100 ft. north of and 20 ft. lower than crest of ridge running east and west.
9/19/86

213

Center South 1/16 Section 17
Set - 1" (1 3/8" O.D.) x 32" pipe with 2 3/8" brass cap attached stamped: Douglas County Surveyors Office
T 22 S
CS
1/16
R 12 W
1986
firmly set and protruding approx. 1 ft. above ground with a 1½ ft. dia. mound of sand stone surrounding protruding portion of monument.
New BTs - 12" DBH hemlock (pistol butt) scribed 1/16 S17 CS BT" on a double blaze bears N.14½°E., 7.0 ft.
12" DBH alder bark scribed "1/16 S17 CS BT" bears S.37°E., 18.8 ft
11" DBH spruce (pistol butt) scribed "1/16 S17 CS BT" on a double blaze bears n.79°W., 31.9 ft.
10" DBH spruce scribed "1/16 S17 CS BT" on a double blaze bears N.53°W., 13.2 ft.
12/10/86

Douglas County Surveyors Office
Janet Lundeen, Deputy
Randy Smith - Stephen Flause
Sept.-Dec. 1986
C.S. 62/43 M 101 - 18