

Douglas County Surveyor's Record of
Government Corners Renewed

T 22 T. S. R 12 R. W. W. M.

KONE-CHAPMAN CO., EUGENE, ORE. 97401

214

South 1/16 Section Corner for 17 and 16.
Set - A 2 3/8" dia. brass cap marked: Douglas County Surveyors Office

T 22 S
S 1/16
S17|S16
R 12 W
1986

on a 1" dia. (1 1/4" O.D.) x 32" long galv. iron pipe protruding
1 ft. above ground and surrounded by a 2 ft. dia. mount of
stone.

New BTs - 13" DBH spruce scribed S 1/16 S16 CS BT on a double blaze
bears N. 0 1/2° E., 44.0 ft.

8" DBH spruce scribed S 1/16 S16 CS BT on a double blaze
bears S. 08 1/2° E., 67.2 ft.

19" DBH alder bark scribed S 1/16 S16 CS BT bears N. 79° E., 24.5 ft

22" DBH alder scribed S 1/16 S17 CS BT on a double blaze bears
S. 12° W., 21.4 ft.

Monument is near bottom of very steep southeast slope and approx. 15 ft.
higher than a small creek running northeast.

9/9/86

215

North 1/16 Section corner for Secs. 17 and 18

Set - A 2 3/8" dia. brass cap marked: Douglas County Surveyors Office

T 22 S
N 1/16
S 18 | S 17
R 12 W
1986

on a 1" dia. (1 1/4" O.D.) x 32" long galv. iron pipe. Monument
is firmly set and protrudes approx. 4" above ground.

New BTs - 10" DBH spruce scribed 1/16 S18 CS BT on a double blaze bears
N. 10 1/2° W., 11.0 ft.

10" DBH spruce scribed 1/16 S18 CS BT on a double blaze bears
S. 57 1/2° W., 25.4 ft.

18" DBH spruce scribed 1/16 S17 CS BT on a double blaze bears
S. 80 1/2° E., 8.6 ft. (7.5 ft. to blaze)

9" DBH spruce scribed 1/16 S17 CS BT on a double blaze bears
N. 26° E., 9.8 ft.

Monument lies halfway down moderate slope to northwest.

9/22/86

216

Center North 1/16 Corner, Section 17.

Set - 1" (1 1/4" O.D.) x 32" pipe with a 2 1/2" brass cap marked:
Douglas County Surveyors Office

T 22 S
R 12 W
S 17
C-N 1/16
1986

Pipe/cap protrudes 4" above ground.

New BTs - 27" spruce double blazed scribed "CN 1/16 S17 CSBT" bears
S. 18° W., 31.5 ft.

32" D. fir double blazed scribed "CN 1/16 S17 CSBT" bears
N. 17 1/2° W., 12.3 ft.

24" spruce double blazed scribed "CN 1/16 S17 CS BT" bears
S. 69° E., 35.9 ft.

16" spruce double blazed scribed "CN 1/16 S17 CS BT" bears
N. 44° E., 83.0 ft.

Corner lies at the east edge of a north-south creek bottom

10/21/86

217

1/4 Corner Sections 7 and 8

Found - 1" dia. iron bar - no record, 4 1/2 ft. out of ground and in marsh.

1" I.P. bears S. 88 1/4° W., 213.97ft. (Rec. west 214.01, M57-53)
Source unknown.

Set - We leave 1" iron rod as the corner as a replacement monument
would not be as stable. As a bearing object we set 1"

(1 3/8" O.D.) x 32" pipe with 2 3/8" brass cap stamped:
Douglas County Surveyors Office BO 1 1986

N 30° E
42.8

Douglas County Surveyors Office
Janet Lundeen, Deputy
Randall Smith -- Stephen Flause
Aug-Sept. 1986
C.S. 62/43 M 101 - 18