

**Douglas County Surveyor's Record of
Government Corners Renewed**

T 22 T. S. R 12 R. W. W. M.

FORE-CHAPMAN CO., EUGENE, ORE. 91881

Douglas County Surveyors Offices
Janet Lundeen, Deputy
R. Smith - S. Flause
C.S. 62/43
M. 101 - 18

CONT - - - (1/4 Cor. Secs. 7 and 8) 217

New Accessories:
18" DBH Spruce bears N.74°W., 49.3 ft. scribed "1/4 S7 CS BT"
with double blaze.
A 2 3/8" brass cap on a 1 3/8" O.D. iron pipe protruding 4" from
ground as bearing object No. 1 marked as above, S30°W., 42.8 ft.
6" alder bears N.83°W., 5.7 ft. bark scribed "1/4 S7 CS BT".
6" alder bears S.83°E., 3.2 ft. bark scribed "1/4 S8 CS BT".
1" iron pipe bears S.88 1/4°W., 213.97 ft. (Rec. West 214.01 ft.
M57 - 53).

*FD. OK 9/92
BY WARD M115-61*

8/11/86

1/4 Corner for Secs. 7 and 18 218
Found - Orig. 15" dia. spruce now 27" dia., 5 ft. high stump with partial
scribing "1/4S" bears N.7°W., 13.2 ft. (also rec. per Gordon
1857 survey)
Orig. 15" dia. spruce now 30" dia., 4 ft. high stump with
partial scribing "1/4S" bears S.30°W., 22.4 ft. (per 1857 rec.)
Set - We find record bearings and distances fit well and set a 2 3/8"
brass cap on 1 1/4" I.D. iron pipe, 32" long protruding 6" above
ground and stamped: Douglas County Surveyors Office

T 22 S R 12 W
1/4 S 7
S 18
1986

New BTs - 17" spruce bears N.51°E., 20.4 ft. with double blaze and
scribed "1/4 S7 CS BT".
8" alder bears N.50°W., 4.5 ft. and bark scribed "CS 1/4 S7 BT".
18" Spruce bears S.69 1/2°W., 8.4 ft. with double blaze and scribed
"1/4 S18 CS BT"
16" Spruce bears S.2°E., 13.0 ft. with double blaze and scribed
"1/4 S18 CS BT".

Approx. 100 ft. east of top of ridge, as calls indicate.

7/8/86
219

Mark Hoyer
For: Douglas County,
Moore Oregon,
Menasha Corp.
June 11, 1987
M 104 - 31

Center 1/4 Corner for Section 27
Set - 1 1/2" x 36" iron pipe with brass cap stamped 2098.
BTs - 17" spruce, N.63°W., 5.5 ft. scribed and tagged.
11" hemlock, S.52°E., 20.3 ft. scribed and tagged.
(Measurements are to spikes in base.)

6/11/87

Witness Corner to the NE section corner, Sec. 3, T.23-12 220
Found - 3/4" iron pipe. Ren. #72
25" dia. D. fir, S.39°W., 28.7 ft. face visible.
26" dia. forked Maple, S.44°E., 6.0ft. scribing visible.
32" dia. Cedar, S.70°E., 61.4 ft. no scribing.
Set - I re-monument by driving a 1 1/2" x 36" I.P. with brass cap over
existing pipe and tag the three bearing trees.

Mark Hoyer, LS 2098
For: Menasha Corp.
November, 1987
M 105 - 15
C.S. 63/65

Northwest section corner Section 3, T.23-12 221
Found - 3/4" Iron pipe. Ren. #74
Myrtle Clump, S.35°W., 17.8, rotten face.
30" dia. white fir stump, N.41°E., 33.0 ft., rotten.
26" dia. D. fir stump, N.80°W., 14.9 ft. face visible.
50" dia. white fir stump, N.50°W., 20.6 ft. face visible.
Set - I re-monument by driving a 1 1/2" x 36" I.P. with brass cap over
existing pipe and tag the four bearing trees.

Nov. 20, 1987

1/4 Corner for Sections 9 and 16. 222
Found - 12" hemlock now 34" uprooted, face bears N.54°W., 23.5 ft. (Rec.
N.59°W., 37 lks.) opened face and found visible "BT" scribes.
30" spruce now 64" stump remains, S.60°E., 25.7 ft. (39 lks.)
Set - 2" x 30" I.P. with 2" alum. cap mkd "T22S R12W 1/4 S9 S16 1985
L.S. 1342".
New BTs - 23" D. fir bears N.89°E., 19.5 ft. scribed 1/4 S9 BT. 243
17" D. fir bears S.28°W., 12.0 ft. scribed 1/4 S16 BT. (faced and
painted)

Ronald Stuntzner
For: Douglas County
Land Department
April 18, 1985
M 98 - 54

4/18/85