

**Douglas County Surveyor's Record of  
Government Corners Renewed**

T 22      T. S.      R 12      R. W. W. M.

FOKE-CHAPMAN CO., EUGENE, ORE. 21891

Harvey Wilcox  
L.S. 2244  
Stuntzner Eng.  
For: Oregon Dept.  
of Fish & Wild-  
life & Doug. Co.  
Dec. 1989  
M 109 - 50

**231**

Meander Corner (No. section line, West bdy. Eel Lake)  
Found - Orig. BT, a cedar stump with machette marks and burnt face bears  
S.60°W., 19.14 ft.  
Set - 3/4" x 30" I. rod with 2" alum. cap in orig. position.  
New BTs -A 33" spruce scribed "MC S30 BT" with an X at BH and tagged  
bears N.33°W., 19.7 ft.  
A 22" D. fir scribed "MC S31 BT" with an X at BH and tagged  
bears S.15°W., 26.5 ft.

**232**

Meander Corner (No. sec. line, East bdy, Eel Lake)  
Found - Orig. BT, root hole of a down fir (no marks) bears S.34°E., 60.72 ft.  
Set - 3/4" x 30" I. rod with 2" alum. cap in orig. position.  
New BTs- A 14" spruce scribed "MC S30 BT" with an X at BH and tagged  
bears N.39°E., 10.6 ft.  
A 33" D. fir scribed "MC S30 BT" with an X at BH and tagged  
bears N.22°W., 29.6 ft.

*FOOK 11-92 J. MINOR M116-11* **233**

Section Corner for Secs. 29, 30, 31, 32  
Found - Root hole of a down fir (no marks) bears N.40°W., 17.8 ft.  
Root hole of a down fir (no marks) bears N.70°E., 22.4 ft.  
Root hole of a rotten spruce (no marks) bears S.50°E., 13.2 ft.  
Set - 3/4" iron rod with 2" alum. cap in orig. position.  
New BTs- A 16" alder bark scribed "T22S R12W S30 BT" with an X at BH and  
tagged bears N.52°W., 18.56 ft.  
A 20" D. fir scribed "T22S R12W S29 BT" with an X at BH and  
tagged bears N.19°E., 25.9 ft.  
A 22" D. fir scribed "T22S R12W S32 BT" with an X at BH and tagged  
bears S.69°E., 17.7 ft.  
A 24" D. fir scribed "T22S R12W S31 BT" with an X at BH and  
tagged bears S.44°W., 22.0 ft.

12/89

**234**

East 1/4 Corner for Section 1.  
Found - 1971 County brass cap on a 1 1/2" O.D. iron pipe, protrudes  
15" above ground. Ren. No. 80  
18" now 20" dia. 4 ft. high hemlock stump, with a rotted  
partially healed blaze scribing visible "1/4S" bears N.40°E.,  
11.3 ft. (agrees with record) Ren. No. 80  
5" now 7" dia. 7 ft. high hemlock stump, with a partially healed  
double blaze, scribing visible "1/4 S1 CS BT" bears  
N.40°W., 48.3 ft. (Rec. N.40°W., 49.2 ft. dist. is a slope  
measurement) Ren. No. 80  
New BTs - 11" dia. alder bark scribed "1/4 S1 CS BT" 4 ft. above ground  
bears S.34°W., 23.3 ft.  
8" dia. spruce double blazed and scribed "1/4 S1 CS BT" bears  
N.5 1/2°W., 37.8 ft.  
18" dia. alder double blazed and scribed "1/4 S1 CS BT" bears  
S.20 1/2°W., 44.8 ft.  
8" dia. hemlock double blazed and scribed "1/4 S1 CS BT" bears  
S.28 1/2°W., 59.3 ft.

Corner lies on a steep northeast slope, approx. 250 ft. south of state  
Hwy. 38, and 45 ft. easterly of a pwer line easement clearing.

1/23/90

**235**

Section Corner for Sec. 5 and 6 T 23-12.  
Set: A 3/4" x 30" I. Rod W/2" Alum. cap by proportion.  
BT's - A 23" fir bears N 3° E, 13.2 ft. scribed "T22S R12W S32 BT" W/an  
X at BH and tagged.  
28" fir bears S 42° W, 26.4 ft. scribed "T23S R12W S6 BT" W/an  
X at BH and tagged.  
24" fir bears bears S 52°E, 27.2 ft. scribed "T23S R12W S5 BT"  
W/an X at BH and tagged.

Douglas County  
Surveyors Office  
Randy Smith  
Steve Flause  
Jan. 23, 1990  
C.S. 64/5

*FOOK  
BY R. DOUGLASS  
CS 63/20-3  
5-93*

Harvey Wilcox  
L.S. 2244  
Stuntzner Eng.  
For: Oregon Dept.  
of Fish & Wild-  
life & Doug. Co.  
Dec. 1989  
M 109 - 52