

Douglas County Surveyor's Record of  
Government Corners Renewed

T 22 T. S. R 12 R.W.W.M.

ROKE-CHAPMAN CO. EUGENE, ORE. 21881

Douglas County  
Surveyors Office  
Jan. 18, 1990  
Randall Smith  
Steven Flause  
C.S. 64/5

Reference Monument #1, on range line, Section 1; and Sec. 6, T22-11  
Monument gone; apparently dug out. Ren. #79  
Found - A 3" "+" marked in high rock bluff approx. 4 ft. above  
ground, bears S. 55° E., 17.9 ft. Ren. #79  
(5/8" I.R. and SW "cross" from Ren. #79 NOT FOUND)  
Set - A 2 3/8" dia. DCSO brass cap on a 1 3/8" O.D. x 32" long I.P.  
at a point N.55°W., 17.9 ft. from previously described "+"  
in rock bluff. BC/IP protrudes 14" above ground is  
surrounded by a 2 1/2" ft. dia. mound of sandstone. Cap stamped  
DOUGLAS COUNTY SURVEYORS T22S RM 1 R12W S1 S6 R11W  
RESET 1990.

236

New Accessories:

5/8" x 30" long I.R. with DCSO alum. cap stamped "B0 1"  
protrudes 3" above ground under east guard rail bears  
N.24 1/2°E., 51.4 ft.  
A 5" "+" marked in high rock bluff approx 4 1/2 ft. above ground  
bears S.72°W., 10.0 ft.  
DCSO drill cap stamped "T22S RM2 R12W S1 S6 R11W 1990" bears  
N.68 1/2°W., 111.7 ft. RM 2 drill cap set 6" below ground in  
sandstone. Two boat spikes are set over drill cap for future  
magnetic declination.

Note: Following new accessories are for RM 2 only.

A found 6" "+" on high rock bluff approx 5 ft. above drill cap  
bears S.84°W., 11.4 ft.  
Marked a 6" "+" on high rock bluff approx 5 ft. above drill cap,  
bears S.10°E., 11.4 ft.  
A DCSO BC/IP marked "T22S RM1 R12W R11W S1 S6 RESET 1990" bears  
S.68 1/2°E., 111.7 ft.

1/18/90

Harvey Wilcox  
Stuntzner Eng.  
For: Ore. Fish &  
Wildlife  
July 1990  
M 112 - 9  
C.S. 63/119

1/4 Corner for Sections 29 and 32

Set - 3/4" x 30" iron rod with 2" alum. cap at proportionate  
measurement. Cap mkd. "Stuntzner Engineering 1/4 S29 S32 LS 2244"  
BTs - A 37" Fir scribed "S 1/4 S29 BT" with an X at BH and tag bears  
N.12°E., 30.1 ft.  
A 27" Fir scribed "S 1/4 S29 BT" with an X at BH and tag bears  
N.81°E., 22.8 ft.  
A 12" Cherry bears S.87°W., 24.2 ft.  
An 18" hemlock bears N.43°W., 27.1 ft.

237

7/90

Section corner for sections 18 and 19 only, T.22-11W

Found - Oregon State Board of Forestry 3" bronze cap dated 1961 on  
1 1/2" x 36" galv I.P.  
BTs - 12" fir (orig.) N.60°W., 24 lks. - now 47" x 10' high stump,  
face partially closed and burnt, some scribes visible, in place  
and U.S. Plywood tag See renewal # 23 T.22-11W  
50" fir (orig.) N.60°W., 15.8 ft. - now N 46°W., 14,3 ft.,  
47" x 10' high stump, face partially closed and burnt,  
U.S. Plywood tag.  
12" hemlock, 1910, N.72°E., 7 lks. - now uprooted stump,  
axe work visible.  
23" fir, 1960, S.9°E., 11.5 ft. - now 31" face closed,  
in place, U.S. Plywood tag.  
31" fir, 1960, N.88°W, 10.5 ft. - now 36" x 3' high stump  
face closed, in place, U.S. Plywood tag.

238

New Accessories -

5" fir, N.64°E., 14 9 ft. scribed "T22S R11W S18 BT" w/brng. tree.tag  
Orange carsonite marker N 33°E., 6.3 ft. to base.  
Orange carsonite marker S.70°E., 4.9 ft. to base.  
White painted 4 x 4 cedar post S.85°W., 2.2 ft.

6/91

Lloyd D. Smith L.S. 1101  
For: State of Oregon Dept of Forestry  
May 1, 1991  
M 112 - 29