

Douglas County Surveyor's Record of
Government Corners Renewed

T.22 T. S. R.12 W R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

East 1/4 Corner for section 24 only.

239

- Found - Oregon State Board of Forestry 3" bronze cap dated 1971,
on 1½" x 36" I.P.
- BTs - 23" burnt fir stump S.79½°W., 99.22 ft. - scribes visible, in place
37" hemlock stump N.8°W., 98.1 ft. - now 33" badly decayed,
scribes found on slabs at base of stump, in place.
White painted 4 x 4 cedar post, in place. See renewal #94
- New Accessories -
16" fir, N.19°W., 26.8 ft. scribed "1/4 S24 BT" w/bearing tree tag.
9" fir, S.82°W., 13.7 ft. scribed "1/4 S24 BT" w/bearing tree tag.
Orange carsonite marker N.31°W., 5.8 ft. to base

6/91

West 1/4 corner for section 19 only. (T. 22 R. 11)

240

- Set - Oregon State Board of Forestry 3" bronze cap dated 1991,
on 1½" x 36" Galv. I. P. 34" in ground.
- BTs - 73" fir, N.9°E., 76.6 ft. bark scribed "1/4 S19 BT" w/brng. tree tag
75" hemlock N.28°E., 49.2 ft. scribed "1/4 S19 BT" w/brng. tree tag
45" fir, N.38°E., 67.7 ft. scribed "1/4 S19 BT" w/bearng tree tag.
65" fir, South 77.0 ft. scribed "1/4 S19 BT" w/bearing tree tag.
White painted 4 x 4 cedar post S.79°E., 1.5 ft.

6/91

Section corner for sections 24 and 25 only.

241

- Found - Oregon Board of Forestry 3" bronze cap dated 1960 on 1½" x 36"
galv. I.P. in place.
- BTs - 20" alder, (orig.) N.40°W., 22 lks. - now 24" N.50°E., 14.8
ft. to face.
45" fir, 1960, S.73°W., 15.3 ft. - now 48" x 3' high rotted stump,
scribes visible, in place. See renewal # 29
27" cedar, 1960, N.56°W., 47.3 ft. - now 38" scribes visible
in place
White painted cedar 4 x 4 post, southeast 1.5 ft. in place.
- New Accessories -
24" cedar, S.82°W., 32.9 ft. scribed "T22SR12W S25 BT" with
bearing tree tag.
Orange carsonite marker S.71°W., 15.0 ft. to base, alongside
45"fir bearing tree.

6/91

Closing corner for sections 19 and 30 T.22-11W.

242

- Found - Oregon State Board of Forestry 3" bronze cap dated 1960 on
1½" x 36" galv. I.P. in place. See renewal # 39 T.22-11W.
- BTs - 12" hemlock (orig.) N.51°E., 57 lks. - now 24" x 8' high
rotted stump, axe work and scribes visible, in place.
40" cedar, (orig.) S.42°E., 53 lks. - now 66" x 4' high stump,
face open, scribes visible, in place.
30" cedar (orig.) S.42°W., 26 lks. - now 48" x 4' high stump,
face rotted, in place.
49" cedar, 1960, N. 83½°W., 26.3 ft. - now 60" x 5' high stump,
scribes visible, in place
- New Accessories -
Orange carsonite marker N.54°E., 36.1 ft. to base, alongside
12" hemlock BT.
Orange carsonite marker S.39°E., 27.1 ft/ to base, alongside
40" cedar BT.
Orange carsonite marker S/44°W., 14.5 ft. to base, alongside
30" cedar BT.
Orange carsonite marker N.82°W., 25.8 ft. to base, alongside
49" cedar BT.
White painted 4 x 4 cedar post, N.6°E., 1.6 ft.

6/91

Lloyd D. Smith L.S. 1101
For: State of Oregon Dept. of Forestry
May 1, 1991
M 112 - 29