

**Douglas County Surveyor's Record of  
Government Corners Renewed**

T. 22 T. S. R. 12 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97101

John Minor  
For: Menasha Corp.  
Nov. 1992  
M 116 - 11

252

1/4 Corner for Sections 29 & 30.  
Found - Both original BTs. by Cathcart; very rotten spruce stump formerly 50" with scribe visible N.75°E., 65 lks. (42.9')  
Very rotten spruce stump formerly 60" with scribe visible. N.86°E., 33 lks. (21.8')

Set - 1"x36" I.P. with 2" brass cap stamped T22SR12W 1/4 S30 | S291992 LS2052.  
Brass cap set at dist. intersect from faces of original BTs.

New Accessories -  
30" Spruce S.32°E., 7.3' scribed 1/4 S29 BT.  
26" D.Fir N.32°E., 15.6' scribed 1/4 S29 BT.  
29" Cedar N.01°W., 54.1' scribed 1/4 S30 BT.  
28" Spruce N.39°W., 49.4' scribed 1/4 S30 BT.

12/92

253

Corner for Sections 1 & 12 only  
Found - 1/2" dia. iron rod protruding 2 1/2 ft. above ground. Source unknown, possibly set in area of corner from a recent survey. Note- I.R. is loosely set. DCSO BC/IP not found.

Accessories Found - See Renewal # 83.  
10" now 18" dia. D.Fir with a fully healed double blaze, bears N.77 1/2°E., 21.6 ft. (rec. N.77 1/2°E., 24.0 ft. dist. could be a slope measurement)  
14" now 23" dia. D.Fir with a fully healed double blaze, bears S.40°W., 60.2 ft.  
10" now 12" dia. Maple with a fully healed single blaze, bears N.86 1/2°W., 41.5 ft. (rec. west, 41.5 ft., bearing to Maple is difficult to see)

Monument Set -  
At a position determined from bearing trees that were scribed for M42-27. Set a 2 3/8" dia. Brass Cap on a 1 3/8" O.D. by 32" long iron pipe, protrudes 6" above ground and is marked -

DOUGLAS COUNTY SURVEYORS

	T 22 S		
R	S1		R
1	S12   S6		1
2			1
W			W

1993  
OFFICE

1/2" I.R. bears N.52 1/2°W., 2.1 ft. from BC/IP.  
BC/IP is surrounded by an 18" dia. mound of sandstone.

New Accessories -  
17" Alder bark scribed "T22S R12W S12 CS BT" bears S.8°W., 37.5 ft.

Note - Corner lies in bottom of a ravine running north - south.

Center 1/4 corner for sec. 30

254

Monument set -  
3/4" x 30" I.R. with 2" aluminum cap mkd. Stuntzner Engineering, T22S,R12W, C1/4, S30, 1994 & LS1342.

New Accessories -  
27" spruce, face scribed "C1/4 S30 BT" with x-chop & tag @ BH BRS. N.63°E for 13.5' to a spike at side center.  
16" spruce, face scribed "C1/4 S30 BT" with x-chop & tag @ BH BRS. S.46°E for 16.9' to a spike at side center.  
28" spruce, face scribed "C1/4 S30 BT" with x-chop & tag @ BH BRS. N.77°W for 21.3" to a spike at side center.  
25" spruce, face scribed "C1/4 S30 BT" with x-chop & tag @ BH BRS. N.26°W for 11.5' to a spike at side center.

Douglas County Surveyor's Office  
Randall Smith, Stephen Flause  
Oct. 13, 1993  
C.S. File 64/47

Ronald Stuntzner  
M118-36  
Feb. 2, 1994  
For: Do.Co.Land Dept