

Douglas County Surveyor's Record of
Government Corners Renewed

22

T. S.

12

R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 91881

259

SEC. COR OF 18 & 19 OF T22-12; 13 & 24 OF T22-13
MON. FD. - 2½" dia. DCSO Brass cap on a 1½" Iron pipe, protrudes 4"
above ground.
5/8" I.R. protrudes 5" above ground along Northwest edge
of BC/IP (source unknown).
4"x4" x 8' high white wooden post, bears N.18°E. 1.15'.
Accessories Fd. - Brg. & dist. taken from a position determined from
Org. BT's and a Ren # 90 BT.
30" now 36" dia. 4½' high rotted spruce stump, with a
possible blaze no scribing found, bears N.15°W., 10.6'
to blaze. Center bears N.15°W., 11.8'.
24" now 46" dia. 7' high rotted spruce stump, with an
opened blaze and scribing visible "S" and other
illegible marks, bears S.72°E., 44.9' to blaze. Center
bears S.72°E., 45.9'.
30" now 26" dia. 4½' high rotted spruce stump, no blazes
or scribing found, bears S.62½°W., 32.3' to a position
that would fit a possible blaze location. Center bears
S.62½°W., 33.5'.
19" now 30" dia. spruce, with a fully healed double blaze,
bears S.56½°W., 32.1'.
18" spruce now 24" dia. D.Fir, with a fully healed double
blaze, bears, N.24°W., 32.9'.
24" now 34" dia. spruce, with a fully healed double blaze,
bears S.9 3/4°E., 68.3'.
Mon. Set - A 2 3/8" dia. DCSO Brass cap on 1 3/8" O.D. by 32" long
iron pipe. At a position determined from two remaining
original bearing trees and a bearing tree marked by
Eppstein in ren. #90. BC/IP protrudes 2" above ground.
1981 DCSO Iron pipe bears N.19¼°E., 3.5'.
Corner is S.20°W., 4.7' from 4"x4" x 8' high white wooden
post.
New Accessories -
4" dia. Cascara, double blazed and scribed "X BT", bears
S.88½°W., 9.7'.
7" dia. Alder bark, double blazed and scribed "T22S R13W
S24 CS BT", bears S.31½°W., 18.4'.
see renewal #152

Douglas County Surveyor
Randall Smith &
Stephen Flause
C.S. 64/63-12
5/31/95

260