

Douglas County Surveyor's Record of  
Government Corners Renewed

T 22

T. S.

R 13

R. W. W. M.

KORE-CHAPMAN CO., EUGENE, ORE. 97501

23

1/4 Corner for Sections 13 and 24

- Found - 1982 BLM alum. cap and pipe. (See also Ren. #4)  
9" fir, N.53 1/2°E., 21.5 ft. scribed "1/4 S13 BT".  
12" pine, S.5 1/4°E., 38.9 ft. scribed "1/4 S24 BT".  
8" fir snag, N.25 1/2°W., 5.9 ft. scribed "1/4 BT".  
8" pine snag, south, 2.6 ft. scribed "1/4 BT".
- Set - Reference monument, a USFS alum. monument, a 2 1/2" x 30" alum. pipe with 3 1/4" alum. cap with magnet attached under cap, bears S.21°12'E., 46.7 ft. Cap stamped "1/4 S24 46.7  
N21°12'W RM 1985 LS 909".

William Shull  
LS #909

For: U.S.F.S.  
Jan. 20, 1985  
M 98 - 70

24

Section corner for 25 and 36; and 30 and 31 of T.22-12

- Found - 1982 BLM alum. cap and pipe. (See also Ren. #6)  
7" pine, dead, N.37°E., 23.8 ft. scribed "R12W S30 CS BT".  
10" pine, N.12°W., 15.8 ft. scribed R13W S25 CS BT".  
18" pine S.71°E., 15.8 ft. healed blaze  
10" fir, S.10 1/2°E., 25.4 ft. scribed "T22S R12W S31 BT".  
NE cor of A-frame house bears S.64 1/4°W., 44.9 ft. not scribed.
- New BT - 5" fir, N.54°E., 13.2 ft. scribed X BT.
- Set - USFS alum. reference monument, a 2 1/2" x 30" alum. pipe with 3 1/4" alum. cap with magnet attached under cap. Cap stamped "T22S R13W R12W RM S82°23'E 1984 LS 909"  
54.8'

1/4 Corner for Sections 12 and 13

25

- Found - 2" inside dia. iron pipe (rec. 2 1/2" I.P. per Ren. #10 and 17) (agrees with Ren. #8) protrudes 1" above ground. (Source unknown).  
30" now 30" dia. 1 1/2 ft. high rotted spruce stump. No scribing or blazes found bears N.35°E., 7.0 ft. to center of stump. (Rec. dists. of 5.2 and 5.8 ft. per Ren's 5 and 8 probably would be close to face measurement)  
No evidence of SW BT from Renewal No. 5.  
16" now 34" dia. spruce with a fully healed single blaze bears N.76 1/2°E., 53.8 ft. agrees with rec. (Ren. No. 5)  
45" now 54" dia. broken top spruce with a fully healed single blaze bears S.87°E., 106.4 ft. agrees with rec. (per Ren. No. 10)  
36" dia. 3 ft. high rotted stump no face or metal tag found bears S.88°W., 64.0 ft. to center (Rec. S.88°W., 62.8 ft. to face. per ren. No. 17) (Tree's first appearance of rec. is in #17)  
NW corner of house bears S.34°W., 51.8 ft. agrees with record.
- No new monument or accessories established.  
Corner lies approx 50 ft. from high bluff that overlooks Winchester Bay.

Douglas County Surveyors Office  
Party Chief - Randall W. Smith  
Witnesses - Stephen J. Flause  
January 5, 1988  
C.S. 62/49

26

1/4 Corner for Sections 13 and 14

- Found - 1983 BLM 3 1/4" brass cap on a 2 1/4" I.P. protruding 7" above ground. 1" I.P. per Ren. #18 was not looked for. It lies under BC/IP according to 1982 BLM line notes.  
No other monuments previous to Ren. #18 were found.  
Nail with round head and a 2" shinner in AC now covered by an AC overlay, nail located with metal detector (not uncovered) bears N.71 1/2°E., 178.17 ft. agrees with record. Per Ren. No. 18  
Coast Guard telephone pole with PK nail on west side 4 ft. above ground now pole cut down and remainder protrudes 5 ft. above ground bears S.3 1/2°E., 189.57 ft. agrees with rec. Ren. No. 18  
Steel post with white paddle bears S.49°E., 1.7 ft. (Rec. East 2 ft.) per Ren. No. 18  
OSHD station "Guard 1968" has a record bearing and distance of N.57°51'E., 23.73 chains. Station Guard is OK, bearing and distance not checked.
- New Accessories:  
5" spruce double blazed and scribed "1/4 S14 CS BT" bears N.55 1/2°W., 32.6 ft.  
6" spruce double blazed and scribed "1/4 S13 CS BT" bears S.10°E., 12.0 ft.
- Perpetuated as point. Projected by Hollingsworth (M66-54) and accepted by BLM (dependent resurvey approved 1/6/84) for corner location.