

Douglas County Surveyor's Record of
Government Corners Renewed

T. 23 S. T. S. R. 2 W. R.W.W.M.

KOKE-CHAPMAN CO. EUGENE, ORE. 21891

24

Section Corner to Sections 29 - 30 - 31 - 32.

Found - Orig. 30", now 36" Hemlock Stump, N. 58°W. 44.9 ft., scribe visible on open blaze.

All other BT's. gone due to logging. No live trees available. Weyerhaeuser BT's., as follows:

40" Fir Snag N. 76°E. 56.5 ft., "W" Nail & Tag.

36" Cedar Stump S. 9°W. 87.5 ft., "W" Nail & Tag.

60" Fir Stump S. 57°E. 87.7 ft., "W" Nail & Tag.

Set - Brass Cap at Cor. Mkd: County Surveyor's T 23 S R 2 W
(Set 6' Steel Fence Post Office S 30 | S 29
alongside Brass Cap) 1969 S 31 | S 32

Do not mark any Bearing Trees, no live trees available.

25

1/4 Corner to Sections 26 and 27.

Found - Corner Stone mkd: "1/4", as called for in Orig. notes.

Orig. 8" Cedar, now 14" Snag, S. 54°E. 4.6 ft., scribe visible on unhealed blaze.

Orig. 24" Fir, now 25" Snag, S. 70°W. 13.2 ft., scribe visible.

Set - Brass Cap at Cor. Mkd: County Surveyor's T 23 S R 2 W
(Reset Stone alongside) Office, 1969 1/4 S 27 | S 26

New BT's: 18" Hemlock N. 76°E. 20.4 ft. mkd: "1/4 S26 DCS BT".

48" D. Fir N. 68°W. 24.4 ft. mkd: "1/4 S27 DCS BT".

This corner lies on steep N.W. slope, on E-W Lane, Douglas County Line.

26

1/4 Corner to Sections 29 and 32.

Found - No marked Stone found.

Orig. 20", now 26" Fir, broken off, N. 30°W. 23.8 ft., "1/4 S" scribe on log & reverse "BT" on remains of stump.

Orig. 40", now 48" Fir, alive, S. 45°W. 21.1 ft., log of turnout lying over blaze.

Set - Brass Cap at Cor. Mkd: County Surveyor's T 23 S R 2 W
Office S 29
1969 S 32

New BT's: 13" Hemlock N. 27°E. 35.5 ft. mkd: "1/4 S29 CS BT".

15" Cedar S. 33°E. 24.3 ft. mkd: "1/4 S32 CS BT".

This corner lies on very steep, westerly slope.

27

1/4 Corner to Sec. 34, T23-2W. & Sec. 3, T24-2W.

Found - Corner Stone with partial "1/4", "4" chipped off, and 1894 BT's.

20", now 30" Hemlock, alive, S. 76 1/2°E. 12.5 ft., shows good scar.

18", now 22" Hemlock, dead, N. 4° W. 5.3 ft., scribe visible on unhealed blaze.

Set - Brass Cap at Cor. Mkd: County Surveyor's T23S R2W 1/4 S 34
(Reset stone alongside) Office, 1969 T24S S 3

New BT's: 8" Hemlock N. 22°W. 49.4 ft. mkd: "1/4 S34 CSBT".

12" Hemlock S. 82°W. 28.1 ft. mkd: "1/4 S 3 CS BT".

This corner lies about 160 ft. west of creek, 2' wide, course S.W.

28

Section Corner to Secs. 33 & 34, T23-2W and Secs. 3 & 4, T24-2W.

Found - Orig. 36", now 48" Fir, alive, S. 25°E. 46.2 ft., open & scribe visible.

Orig. 18" Hemlock N. 11°E. 5.3 ft., down, face up.

Other Orig. BT's. gone.

Set - Brass Cap at Cor. Mkd: County Surveyor's T23S R2W 1/4 S 33 | S 34
Office, 1969 T24S S 4 | S 3

New BT's: 8" Hemlock N. 49°E. 12.5 ft. mkd: "T23S R2W S34 CS BT".

12" Hemlock S. 74°W. 45.5 ft. mkd: "T24S R2W S 4 CS BT".

No other trees suitable.

Brass Cap lies toward easterly end of root-wad of Orig. BT. to N. E.

29

Section Corner to Secs. 34 & 35, T23-2W. and Secs. 3 & 2, T24-2W.

Found - Orig. 8", now 12" Chinquapin, alive, N. 85°E. 13.2 ft., scribe visible.

Orig. 24", now 30" Fir, alive, S. 48°E. 21.1 ft., (Rec. S68E), shows good scar.

Orig. 24", now 28" Fir, alive, S. 38°W. 11.9 ft., shows good scar.

We Rescribe: "T24S R2W S 3 CS BT".

(cont. over)

Vernon "Ray" Tracy
Jack Heritage & V. Perron
July, 1969 C.S. File No. 54/27

RE-RENEWED. SEE CORNER NO. #33