

**Douglas County Surveyor's Record of  
Government Corners Renewed**

T. 23 S. T. S. R. 2 W. R. W. W. M.

FOKE-CHAPMAN CO., EUGENE, ORE. 21821

(C o n t .)

Gregory E. Quibell  
Deputy, Doug. County  
Surveyors Office  
Debbie Stewart, wit.  
Sept. 8, 1981  
C.S. 61 / 27

New BO's- "W" nail 1.0-ft. above ground in 80" Fir stump, bears N.62°E.,  
31.5-ft.  
"W" nail near ground of orig. 30", now 33" Fir stump, bears  
S.29°E., 35.6-ft.  
44" Fir bears N.85°W., 12.9-ft., scribed "T23S R2W S35 CS BT"  
in single blaze. Old axe marks fd. above new blaze.  
9/8/81

38

Gregory E. Quibell  
Deputy Doug. County  
Surveyors Office  
Debbie Stewart, witness  
Sept. 9, 1981  
C.S. 61/27

1/4 corner for Sec. 36 and Sec. 1 of T.24-2.  
Found - Brass Cap buried under several large logs. After removing  
the logs, I find the B.C. firmly set, protruding 1" above  
the ground, properly marked. Ren. # 13.  
BT's - 13" Hemlock (orig. 12"), alive, bears N.66 1/2 °W., 6.5-ft.  
(Rec. N.64°W., 6.6-ft.) with scribed "S36 CS BT" visible in  
unhealed blaze. Ren. # 13.  
12" Hemlock (orig. 10"), alive, bears S.8°W., 16.5-ft. (Rec.  
S.6°W.) with scribed "S1 CS BT" visible on unhealed blaze.  
"W" nail in base of 38" Fir snag, 17-ft. tall C.S. 58/8.  
bears S.3°W., 11.6-ft. Also found a  $\blacktriangle$  cut deeply in bark.  
9/9/81

39

Donald Peel LS #752  
For: Weyerhaeuser  
Company  
August 17, 1982  
M 92 - 78

Center 1/4 Corner for Section 33  
Set - 1 1/2" x 40" iron pipe with brass cap marked: T23S R2W C 1/4  
S33 PLS 752 1982.  
BTs - 46" fir, N.33°E., 23.0 ft.  
54" fir, S.23°E., 53.5 ft.

40

Helmut Kreidler  
for: Weyerhaeuser Co.  
Assisted by Ken Perkins  
May 13, 1982  
C.S. 58/271

1/4 Corner for Secs. 34 and 33  
Found - 12" now 30" hemlock (orig.) bears S.30°E., 21.8 ft. Open face  
scribing with Douglas County Tag.  
36" now 46" fir (orig.), face grown over bears N.72°W., 25.1 ft.  
with BLM tag  
16" hemlock, S.20°W., 46.3 ft. scribing visible, face open with  
Douglas Co tag. Ren. #22  
1969 Douglas County brass cap. Ren. #22  
New BT - 60" fir, bears S.25 1/2°W., 40.3 ft. with "W" nail and plate.  
"W" nail and plate added to 30" hemlock.

41

Gregory Quibell  
Deputy, Doug. Co.  
Surveyors Office  
Karen Reed, Terrie  
Plouff  
C.S. 62/1  
Oct. 20, 1982

Witness corner, 1/4 Corner Sections 28 and 33  
Found - Hub & tack in center of logging road as per M 92 - 78  
All orig. evidence has been destroyed by road construction, however the  
corner has been perpetuated by Weyerhaeuser June 1, 1976 and again Dec. 12,  
1981 and July 27, 1982. See attached Weyerhaeuser renewal notes received  
Sept. 28, 1982. (in C.S. file 62/1)  
Found - 56" fir per Weyerhaeuser, now 73" fir stump bears N.46 3/4°W.,  
102.6 ft. to "W" nail near center of stump, as per record.  
56" fir snag per Weyerhaeuser, now 65" stump bears S.20°E.,  
40.7 ft. to "W" nail in face, as per record.  
24" cedar stump per Weyerhaeuser, bears N.88 1/2°E., 69.6 ft.  
(Rec. East) to "W" nail in face.  
60" fir at S.48°E., 75.2 ft. is down and out of place., as  
per Weyerhaeuser.  
Set - Since corner fell in rock road, I SET a 1" x 30" iron pipe with  
brass cap attached, north 40.0 ft. for witness corner. Cap mkd.  
"Douglas Co Surveyor Wit Cor 40 ft south to T23S 1/4 S28 S33  
R2W 1982"  
New BTs - 17" cedar scribed "X CS BT" in double blaze bears S.55 1/2°E.,  
175.9 ft.  
22" fir scribed "X CS BT" in double blaze bears S.31°W., 292.4 ft.  
DCSO BT tags on all trees.

42

10/20/82