

Douglas County Surveyor's Record of
Government Corners Renewed

23 T. S. 3 R. W. W. M.

ROYE-CHAPMAN CO., EUGENE, ORE. 97106

Gilbert A. Gardner
Sur. for Woodard Lumber Co.
August, September &
November, 1953
See file No. 41/222

$\frac{1}{4}$ corner between secs. 28 and 33.
Set 12 inch X 12" X 20" stone and 1 inch iron pipe.
Marked Two trees:
8 inch dead Yew bears N.36°E, 25.4 feet.
10 Yew bears S.80°E., 140.7 feet.

Center $\frac{1}{4}$ corner section 34.
Set 4" square Yew post, 4 ft. long,
at point of intersection for center of sec. 34.
Marked 2 bearing trees:
18 inch Hemlock - bears S.49°W., 11.0 feet.
12 inch Hemlock - bears S.65°E., 26.0 feet.

Northwest corner Sec. 34.
Set a 2 inch iron pipe X 48 inch iron pipe 2 inches above ground
for cor. N.0°36'E., 2596.2 feet from the $\frac{1}{4}$ cor. between secs.
33 and 34 T 23 S, R 3 W., and also S.89°25'W., 2650.9 feet from
the $\frac{1}{4}$ cor. between secs. 27 and 34, said Township and Range.
Marked new bearing trees;
6 inch Douglas Fir N.43 $\frac{1}{2}$ °E., 31.0 feet, marked S 27 R S BT.
6 inch Hemlock bears N.48°W., 8.0 feet, marked S 28 R S BT.
46 inch Douglas Fir which has old markings "BT", bears
S.39°E., 16.0 feet, rescribed S 30 R S BT.
6 inch Douglas Fir bears S. 45 $\frac{1}{2}$ °W. 27.3 feet, marked S 33 R S BT.

This location has been used as a NW cor. of Sec. 34 for a number of ~~4~~
years and shows surveyor and cruiser marks, and although the BT marked
in the 46 inch Douglas Fir does not face the right direction, the
distances and bearings to this location are approximately the same as
those given in the original field notes. No evidence of other bearing
trees was found, and it is believed that this is the best location
possible with available evidence for this corner.

Gilbert A. Gardner
Witness: Robert Barta
Dec. 28, 1953
Sur. file 41/239

Section Corner common to Secs. 27, 28, 33 and 34. C.S. 53/107 also
GLO Survey Record - All evidence lost.
Found 1 $\frac{1}{2}$ " I. P., scribed Yew Post & Witness Trees which are the
accessories of G.A. Gardner survey filed in the Surveyor's Office.
50" Fir Stump S.38°E. 16.0 ft., partial scribing on bark.
7" Fir N.43°E. 31.0 ft., scribed S27 RS BT
7" Hemlock N.47°W. 8.1 ft., scribed S28 RS BT
8" Fir S.47°W. 27.0 ft. scribed S33 RS BT
Referenced by Marion D. Hale (plates and "W" nails only) Declination 20°. Rev. #3
50" Fir Stump S.38°E. 16.0 ft.
8" Fir S.47°W. 27.0 ft.
5" Fir N.63°W. 7.3 ft.
9" Hemlock N.56°E. 46.1 ft.

$\frac{1}{4}$ Section Corner Common to Sections 28 and 33. C.S. 53/107 ALSO
GLO Survey Record All evidence lost.
Found 1 $\frac{1}{2}$ " Iron Pipe, Stone & Witness Trees below which are the
accessories of G.A. Gardner survey filed in Surveyor's office. Declin 20°. Rev. #1
20" Dead Yew N.36°E. 25.7 ft. scribed $\frac{1}{2}$ S BT; BLM plate
18" Yew S.83°E. 140.7 ft. scribed $\frac{1}{2}$ S BT; BLM plate
Referenced by Marion D. Hale (plates and "W" nails only)
Declination 20°
44" Fir Stump N.75°E. 27.0 ft.
36" Fir Stump S.40°W. 30.8 ft. Fo. O.K. Oct. 1967 V.R.T.

$\frac{1}{4}$ Section Corner Common to Sections 27 and 28. C.S. 53/107 9150
GLO Survey Record All evidence lost.
Set $\frac{1}{2}$ " x 36" gal. Iron Pipe for corner by single proportionate method.
Referenced by M.D. Hale (plates and "W" nails only) Declin. 20°.
30" Hemlock Stump S.16°W. 53.3 ft.
36" Cedar Stump S.09°E. 132.0 ft.

Fo. O.K. Oct. 1967 V.R.T.

Marion D. Hale
Wit: H.E. Case & W.W. Dixon
For: Weyerhaeuser Timber Co.
Filed: June 19, 1959
C. S. File No. 51/25